

HITACHI

air365 Max

VARIABLE REFRIGERANT FLOW SYSTEM
HEAT RECOVERY TYPE



Localize Contents

Company Name

CUSTOMER SERVICE

SALES OFFICE

SPARE PARTS

DISTRIBUTOR

CERTIFICATION



Concerning [Quality Management Systems]
ISO 9000 series
Hitachi-Johnson Controls Air Conditioning, Inc.
Shimizu Factory
JQA-1084 obtained in November 1995



Concerning [Environmental Management Systems]
ISO 14000 series
Hitachi-Johnson Controls Air Conditioning, Inc.
Shimizu Factory
EC97J1107 obtained in October 1997



Concerning [Occupational Health and Safety Management Systems]
ISO45001/ OHSAS 18001
Hitachi-Johnson Controls Air Conditioning, Inc.
Shimizu Factory
WC18J0002 obtained in July 2018

*Not all the products listed in this catalogue are not manufactured in Shimizu Factory.
Please consult the distributor for more details.

WARRANTY

SOCIAL MEDIA



Index

03

Message

13

Outdoor units

17 | End-to-end solution

49 | Air source heat recovery type (Line up)

63

Indoor units

79 | Ducted units

85 | Ceiling cassette

93 | Other indoor units

111

Ventilation

115 | Ventilation solutions

117 | Dx-kit

119

Controllers

121 | Centralized controllers

127 | Individual controllers

137 | Accessories

139 | H-link



The beauty of balance

No matter what the weather is like outside, when you're indoors, you want to have complete control over your environment. At work or play, awake or asleep, you're free to create your own atmosphere; balancing energy with calm, sound with silence and light with shade. It's the same for cooling and heating.

When the air around you is in balance, you can enjoy life indoors that much more.

Air. It's a wonderful thing.

Invisible, silent and life-giving, air makes our entire world possible. It surrounds us, continuously energizing, cooling and warming. It can be unpredictable and sometimes challenging, but when air is in harmony with us, everything seems that much easier.

This is our vision.
To create the air that makes life better.



Living Harmony

At Hitachi Cooling & Heating we like to think of this as creating harmony with your interior environment. When we achieve that wonderful balance, productivity, learning, happiness and health can thrive.

We call this 'Living Harmony' and it's at the center of everything we do.



The future together

Living Harmony puts people first. By balancing the human needs of our customers with an uncompromising approach to innovation and quality, we can continue to create the technologies for a more comfortable and balanced world.

Your world. We live in it together.



Adapted to your spaces



Office



FLEBILITY

- A COMPLETE solution for whole office spaces; Large ESP Ducted IDU or AHU integrated to VRF for large entrance & conference room, Twin-Sense panel 4-way cassette for meeting rooms, Ventilation units and VRF indoor units for any working space
- Any shape of buildings including high-rise one can be suitable for VRF unit, with max 110m height difference & total 1,000m piping length availability
- During cold months, server rooms are cooled using the exhaust energy from heated rooms

SUSTAINABLE GROWTH

- Highest EER max up to 5.50 & specially optimized operation for part-load operation thanks to SmoothDrive 2.0 technology
- Achieve green-building certificate by more greenery appearance of buildings thanks to less-ODU occupied space & less-refrigerant necessary unit
- Smart monitoring and control: to cut the wasteful energy consumption by each checking status of units from airCloud Pro anywhere anytime
- Heat Recovery delivers additional energy savings >> improves energy efficiency by transferring excess heated or cooled air to zones needing extra cooling or heating

WELL-BEING

- Right temperature: Heat recovery systems offer simultaneous cooling and heating to meet individual needs
- Right Feeling; airflow control with sensor & original technology + less noise operation!
- Right Purity: many IAQ supporting units



Hotel



FLEBILITY

- Compact yet powerful cabinet of modular combination capability is SPACE-SAVING solutions, enabling placement on anywhere and transportation can be easier
- Higher flexibility of piping length can help ODUs installed all in one place so that whole installation cost can be decreased & for maintenance ease & less indoor noise bothering
- During cold months, server rooms are cooled using the exhaust energy from heated rooms

SUSTAINABLE GROWTH

- Less is More!: thanks to max 200% IDU combination capacity, purchase fewer ODUs is okay!
- Efficiency designed-in; Highest EER max up to 5.50 + with other intelligent operations (Auto-Save or Setback function) + SmoothDrive 2.0 technology optimizing part-load smooth operation leading to better and lower running cost!
- Thanks to airCloud Tap (installation & service support app), you can minimize the time and cost for VRF configuration and regular maintenance
- Heat Recovery delivers additional energy savings >> improves energy efficiency by transferring excess heated or cooled air to zones needing extra cooling or heating

WELL-BEING

- Right temperature: Heat recovery systems offer simultaneous cooling and heating to meet individual patient's needs
- Right Feeling; airflow control with sensor & original technology + less noise operation!
- Right Purity: many IAQ supporting units



School



FLEBILITY

- Quicker installation can be achieved by 1. large-capacity yet smaller-footprint and lighter weigh outdoor units 2. both H-LINK & airCloud Tap features can help installers work quickly and efficiently within the limited time (like off-school time on weekends)
- Several types of IDUs to meet any type of application or room shapes for easier installation and better cost-performance balance.
- During cold months, server rooms are cooled using the exhaust energy from heated rooms

SUSTAINABLE GROWTH

- Help decrease the running cost thank to 1. Highest EER max up to 5.50 & 2. specially optimized operation for part-load operation by SmoothDrive 2.0 technology
- "Individual controller LOCK mode" for safer operation which prevents inappropriate operation by young students.
- Smart monitoring and control: to cut the wasteful energy consumption by each checking status of units from airCloud Pro anywhere anytime

WELL-BEING

- Right Purity: many IAQ supporting units from several ventilations to filters
- Easy removal of air filters in each indoor unit for the quicker and regular cleaning to keep your air conditioner clean



Hospital



FLEBILITY

- Quicker installation can be achieved by 1. large-capacity yet smaller-footprint and lighter weigh outdoor units 2. both H-LINK & airCloud Tap features can help installers work quickly and efficiently, so that installation work won't cause troubles to the patients
- Flexible combination available with AHU or Ventilation units integrated to VRF system to minimize your initial cost

SUSTAINABLE GROWTH

- Highest EER max up to 5.50 & specially optimized operation for part-load operation thanks to SmoothDrive 2.0 technology
- Smart monitoring and control: to cut the wasteful energy consumption by each checking status of units from airCloud Pro anywhere anytime
- Heat Recovery delivers additional energy savings >> improves energy efficiency by transferring excess heated or cooled air to zones needing extra cooling or heating

WELL-BEING

- Right temperature: Heat recovery systems offer simultaneous cooling and heating to meet individual guest needs
- Right Feeling; airflow control with sensor & original technology + less noise operation!
- Right Purity: many IAQ supporting units

Adapted to everyone's needs

Features, advantages and benefits at a glance

This table sets out the features and benefits of the air365 MAX range with your needs in mind.



For Architects

Those who design the building

EASY TO WORK WITH

Optimize your building by freeing more space from ODU occupied area for the greenery or solar-panel

DESIGN

- Large capacity yet smaller-footprint units (1.26m² for 28HP)
- Require fewer ODUs by IDU connection ratio up to 200%
- Move ODUs to indoor spaces for better building aesthetics
- One solution that works in all ambient conditions

INCREDIBLE ENERGY EFFICIENCY

Achieve the green building certification by our air365 Max latest cabinets

- Lowering direct environmental impact with air365 Max solution
- One of the world's most efficient VRF solutions: EER up to 5.50 / COP up to 5.21
- SmoothDrive 2.0 confirmed for 39% less energy-consumption at 33% part load operation
- Uses 10% less refrigerant in average
- Demand control operation available to achieve forcible entire power saving
- Additional energy savings by transferring excess heated or cooled air to zones needing extra cooling or heating



For System Designer (Contractor or Consultant)

Those who design the HVAC solution

EASY TO WORK WITH

Make your offering more attractive than ever from both initial cost and running cost perspective, by our Easy-to-Work solutions

DESIGN

- Design faster with airCloud Select
- Large capacity yet smaller-footprint units (1.26m² for 28HP)
- Require fewer ODUs by IDU connection ratio up to 200%
- Move ODUs to indoor spaces with EPS up to 80Pa
- One solution that works in all ambient conditions
- Max 200m piping length & max 110m height difference flexibility
- Widest choice of IDUs for any shape of rooms
- Single or multi-port CH-Box for any shape of buildings

INSTALL

- Less communication wiring with H-Link
- Less configuration time by airCloud Tap
- Easier & lower delivery cost by large capacity yet smaller-footprint cabinet
- Easier and quicker thanks to no-drain-connection required design

OPERATE

- Easy for building managers to operate, schedule and automate whole VRF system with airCloud Pro anytime & anywhere
- Easy operation for any end-users by multiple design award-winning remote controllers with user-friendly UX/UI

MAINTAIN

- Anti-corrosion & gecko-proof cabinet available as options
- Automatic reduction of the risk of failure by compressor rotation control
- Even in case of failure, emergency operation mode backs up
- Patented oil-return control technology leading to more reliable yet comfortable operation
- Quicker and easier maintenance work thanks to airCloud Tap

INCREDIBLE ENERGY EFFICIENCY

Meeting the top-priority requirement "energy efficiency" of your end user in both rated & part-load operation

- One of the world's most efficient VRF solutions: EER up to 5.50 / COP up to 5.21
- SmoothDrive 2.0 confirmed for 39% less energy-consumption at 33% part load operation
- Uses 10% less refrigerant in average
- Additional energy savings by transferring excess heated or cooled air to zones needing extra cooling or heating



For Installer

Those who install & service the solution

EASY TO WORK WITH

Significantly upgraded ease of installation & maintenance by our proprietary technology and solutions

DELIVER

- Easier delivery and unloading with reduced ODU footprint and forklift support point
- Best-in-class lightweight and smaller CH-Box for easier transportation

INSTALL

- Less communication wiring with H-Link
- Easier & lower delivery cost by large capacity yet smaller-footprint cabinet
- Unit base holes for safer installation with equipments and piping works
- 4 directions with 9 options for piping connection
- Significantly easier and quicker configuration for both outdoor units & indoor units by airCloud tap of copy-paste setting features

COMMISSION

- Quicker and easier commissioning, by Service Checker, since it can download continuous operation data for the whole VRF system all at once and create a commissioning report easily
- Easier and quicker thanks to no-drain-connection required design

OPERATE

- Intuitive simplicity designed-in Centralized Controllers airCloud Pro for your easier and quicker operation in case of necessity.

MAINTAIN

- Significantly faster access to operational data by airCloud Tap without opening the front-cover cabinets



For End Customer (Investor/Owner)

Those who pay for the system

SEAMLESS COMFORT

From small spaces to the largest buildings, your preferred living harmony are created

- SmoothDrive 2.0 to keep the constant indoor temperature
- Low-Noise operation available for less trouble to the neighborhood
- Comfort features via supporting IDUs including FloorSense, FeeWarm, Crowd-Sense and more
- Smart Changeover for the fair indoor environment cooling and heating by 3 different voting system
- Smart Defrosting & Networked Smart Defrosting for better and constant indoor heating situation
- Several IAQ products available from ventilations to filters & ionizers to keep the indoor air clean and purified
- Heat recovery systems offer simultaneous cooling and heating to meet individual needs

INCREDIBLE ENERGY EFFICIENCY

Reward you with superior performance as well as significant energy and cost savings

- Lowering direct environmental impact with air365 Max solution
- One of the world's most efficient VRF solutions: EER up to 5.50 / COP up to 5.21
- SmoothDrive 2.0 confirmed for 39% less energy-consumption at 33% part load operation
- Uses 10% less refrigerant in average
- Demand control operation available to achieve forcible entire power saving

EASY TO WORK WITH

Less stress and less expense by our user-friendly controllers and applications

OPERATE

- Easy for building managers to operate, schedule and automate whole VRF system with airCloud Pro anytime & anywhere
- Easy operation for any end-users by multiple design award-winning remote controllers with user-friendly UX/UI

MAINTAIN

- Significantly faster access to operational data by airCloud Tap without opening the front-cover cabinets

Our past shapes the future

The first manufacturing site of current Johnson Controls-Hitachi Air Conditioning was born in 1943 in Shimizu ward, Shizuoka Prefecture, Japan, then, in 1952, a small team of Japanese engineers set out to realize a unique vision: to help people around the world create their perfect indoor environment.


Today, we remain true to our legacy of fine Japanese design and engineering. Every Hitachi Cooling & Heating system is designed to perform reliably with innovative technology that sets the benchmark for the industry.

This is our commitment to you. Cooling and heating technologies to help create your interior Living Harmony.



“What makes us unique is that we are creating products and services by thinking thoroughly and from a holistic point of view.”

Mr. Katsuaki Nagahashi,
Research & Development



“Because our inverter calculates at an extremely high speed, even 1 micro-second of disruption during testing makes a difference.”

Mr. Rei Kasahara,
Engineer for Inverter Control



“If we are advertising that the heating function works in an environment down to -20°C, we will test up to -24°C.”

Mr. Tomokazu Inaba,
Quality Assurance

Our heritage in Cooling & Heating

1943 Shimizu Factory founded

1951 Japan's 1st window mounted air conditioner, installed in a Kyoto hotel

1952 Refrigerator Compressor

1953 Roller for mill

1956 Large casting fan for tunnel

1958 Hitachi's 1st Packaged AC (Water-cooled Floor Standing type)

1961 1st Large Split system exported from Shimizu to the U.K.

1963 1st air-cooled Unitary Large Split for export market

1965 1st overseas factory established in Taiwan

1970 1st training school established

1971 Indoor unit: Floor Exposed type (RPF)

1972 Outdoor unit: Large Split controlled by built-in micro-computer

1973 Indoor unit: Ceiling Suspended type (RPC)

1976 Outdoor unit: Ceiling Cassette type

1978 Outdoor unit: for low-ambient temperature markets

1979 2nd overseas factory established in Brazil

1981 Indoor unit: Wall Mounted type (RPK)

1982

1983 Hitachi's first VRF "High-Multi" series with multiple reciprocating compressors and individual indoor unit control available

1984 5th overseas factory opens in the Philippines

1986 1st Scroll Compressor factory established in China

1988 6th overseas factory opens in China

1990 1st cloud-basis centralized controller airCloud Pro

1991 Contactless setting and data-check for HVAC professionals airCloud Tap

1996 **VRF 1ST GENERATION**

1999 **VRF 3RD GENERATION**
Up to 5 indoor units
World 1st IGBT Inverter-driven VRF up to 115 Hz 1986

2003 **VRF 5TH GENERATION 30HP**
Up to 12 indoor units (130% in capacity)
Newly R407C adopted VRF "SET FREE FSG": Heat-Pump type
"SET FREE FXG": Heat-Recovery type

2005 **VRF 7TH GENERATION 54HP**
Heat Pump/Heat Recovery compatible modular VRF system "SET FREE FSXN"

2011 World 1st slim modular VRF SideSmart

2012

2016 **VRF 2ND GENERATION**
Hitachi's 1st Inverter-driven VRF with built-in Scroll Compressor

2019 **VRF 4TH GENERATION 10 HP**
Up to 8 indoor units (130% capacity)
World 1st IGBT built-in Inverter VRF achieves quietest operation

2020 **VRF 6TH GENERATION 32 HP**
New R410A adopts VRF "SET FREE FSN": Heat Pump type
"SET FREE FXN": Heat Recovery type

2021 **VRF 8TH GENERATION 96HP**
Hitachi's new generation VRF SET FREE Σ, developed over 33 years in the industry

2022 **VRF 9TH GENERATION 112HP**
air365 Max

2023 **VRF 9TH GENERATION 112HP**
red dot winner 2021 Red Dot Design Award Best-of-the-Best winning

OUTDOOR UNITS

17 End-to-end solution

- 19 Best-in-class efficiency
- 25 Easy to work with
- 39 Seamless comfort

49 Line up (Air Source Heat Recovery Type)

51 Specifications

- 62 Option / Accessories

End-to-end solution

For HVAC professionals, architects & building owners looking for a modern HVAC solution that is cost efficient and adaptable, air365 Max is an end-to-end solution that's easy to work from design to installation, operation and maintenance, offering incredible energy efficiency and seamless comfort for users



Technology

SmoothDrive technology

Hitachi's direct capacity control technology utilizes precise temperature monitoring and control of scroll compressor frequency to reduce compressor on/off cycles and improve temperature stability under part-load conditions. Up to 39% more efficient under the part-load conditions that regulatory energy efficiency ratings do not account for.

airCloud Tap + NFC technology

airCloud Tap app, designed for installers and service engineers enables 4X faster configuration of outdoor units and 6X faster data checking via a smartphone, and removes the need to open the outdoor unit cabinet. Simply 'tap' a smartphone on the outside of the unit, and configure everything inside the app.

Gas-injection Scroll Compressor

With 10 to 140rps (by 0.1Hz step) driven by DC inverter motor, our gas injection Scroll Compressor extends compressor operating range and increases heating/cooling capacity, leading to a wider outdoor unit operating temperature range & better efficiency. Other proprietary technologies in our latest Scroll Compressor include an internal oil circulation structure and intermediate gas pressure structure, contributing to the best balance of performance and reliability.

Oil-return technology

As well as reducing lubricating oil loss, this patented oil return control cycle consumes less energy and produces much less noise—resulting in higher efficiency and greater comfort for occupants

- Every hour, oil-return operation activates for just 60 seconds (cooling mode) / 120 seconds (heating mode)
- During oil return mode, indoor units can continue to operate normally

Smart Defrost

For Heat Recovery and Heat Pump types:
 Defrosting frequency shortened by 2X for single ODU configurations
 Operate in up to -25C ambient
 Defrosts the ODU in cold temperatures while minimizing the resulting downtime of the indoor units
 Patented intelligent sensing technology detects when defrosting is required and instantly adjusts the exterior case temperature to eliminate ice and frost, so that it can reduce frequent and unnecessary defrosting operation.
 Defrosting frequency reduced by more than 50%, requiring a defrosting cycle as little as every 250mins

Patented Sigma-shape with patented path structure

Σ shape!

Our proprietary sigma-shaped (Σ) heat exchanger has around 6000 pieces aluminum fins as thin as of 0.1mm and characterized with its complicated surface to expand heat-transfer area. Around 350 copper tubes with special inner structure, and a new 3-way path structure which expands the heat-transfer area and efficiency enormously.







Plate Fin




Tube



Spiral shape inside the tube

Strong structure Resistant up to 60m/s (134mph)

Increased rigidity in the front and back of the frame reduces the possibility of damage from external impacts & supports reliable operation even under super windy weather up to 60m/s (134mph) which is enough strong to collapse the wooden houses.



End-to-end solution



1 Best-in-class efficiency

Offers significant improvements in energy consumption thanks to the higher EER & SmoothDrive technology which helps to reduce running costs during part-load operation. This can lead to reduced CO₂ emissions for customers as well.

6 key claims

- ✓ All-new heat exchanger and gas injection scroll compressor enables best-in-class VRF energy efficiency up to EER 5.50
- ✓ **(Original)** SmoothDrive 2.0 confirmed for 39% less energy-consumption at 33% part load operation
- ✓ Uses 10% less refrigerant in average
- ✓ Demand Response Enabling Device (DRED) support through both remote controller & centralized controller
- ✓ Reduce energy consumption and carbon footprint by 47%
- ✓ Additional energy savings by transferring excess heated or cooled air to zones needing extra cooling or heating

2 Easy to work with

A complete solution that saves time and money at every stage of your project, from Design to Maintenance. Our complete ecosystem of indoor & outdoor units, smart apps and hardware features work together as a complete solution.

6 key claims

- ✓ [Design] User fewer ODUs with single unit capacity up to 28HP and 200% IDU connection capacity
- ✓ [Deliver] Load up to 14% more AC capacity in a single vehicle
- ✓ [Install] **(Original)** Up to 4X faster configuration of units with airCloud Tap
- ✓ [Commission] Quicker & easier commissioning with Service Checker - get instant reports and visualize detailed operational data
- ✓ [Operate] Easy monitoring by airCloud Pro anytime anywhere
- ✓ [Maintain] **(Original)** Fast access to error data by using airCloud Tap

3 Seamless comfort

Seamless comfort for building occupants, anywhere, anytime. Solves common problems of HVAC solutions including unstable temperatures, cold or hot drafts, direct air, hot and cold rooms during season changes, and more.

5 key claims

- ✓ **(Original)** Constant indoor temperature even during part-load operation with SmoothDrive 2.0
- ✓ Original & leading-edge technology including GentleCool and CrowdSense, for enhanced occupant comfort
- ✓ Neighborhood-friendly outdoor unit with 3dB(A) lower noise output in average by Night Shift Mode in average
- ✓ Purifying your indoor air with our affordable IAQ solutions including ViroSense filters and the AqtiV-Ion ionizer kit
- ✓ Heat recovery systems offer simultaneous cooling and heating to meet individual needs

Boost your energy efficiency


With air365 Max, discover how you can make significant improvements in your energy consumption fee.

High efficiency ratio


- Best-in-class efficiency
- EER up to 5.50 / COP up to 5.21

All-new heat exchanger and gas injection scroll compressor enables best-in-class VRF energy efficiency. By installing air365 Max, and you can realize significant energy savings.


Cooling EER



Heating COP



NOTES:
 1. The graphs above show the EER/COP of single units.
 2. The above values indicate the EER/COP per outdoor unit when it is combined with specified indoor units.
 3. The specification of EER/COP of each country is different according to the regulation. Please contact to the Sales person for more information.



Cooling & Heating




Ideal for Renovation Projects

- Reduce energy consumption and carbon footprint by 47%*

Our technology is improving every year. Replace outdated HVAC solutions and achieve a 50% reduction in energy consumption and carbon footprint*


Electricity consumption reduction

Comparison of (for a system equivalent to 10HP class (28.0kW))
 Between [RAS-FSN Hitachi inverter VRF of 15years ago]
 VS [air365 Max RAS-HNCC**]



CO₂ emission reduction

CO₂ emissions
 (for a 10HP class (28.0kW) equivalent system)



NOTE
 Condition:
 1. Both simulation of Seasonal power consumption & CO₂ emissions are a trial calculation value based on JIS B 8616: 2015 (Tokyo office).
 (cooling: Apr-19 to Nov-11)(Heating Dec-3 to Mar-15)
 (District; Tokyo) (Application: Office)
 (AC usage: 6days per week, 8am to 8pm)

2. The CO₂ emissions coefficient is 0.441 kg-CO₂ /kWh. Based on Electric Power Industry Council for a Low Carbon Society in FY20
 3. As reference in Japanese domestic model

Less refrigerant required

- Uses 10% less refrigerant in average*

Compared with our previous generation VRF product air365 Max uses 10% less refrigerant in average & 14.6% less in maximum, helping to reduce the environmental footprint and maintenance costs.


Comparison of (for a system equivalent to 16HP class (45.0kW))
 Between [RAS-FSNS previous model VRF of 5years ago] VS [air365 Max RAS-HNCC**]

System	Previous top flow VRF	air365 MAX
Initial charge	9.9kg	9.5kg
Additional charge	14.5kg	13.0kg
Total	24.4kg	21.5kg

-12% refrigerant* used!

* Simulation condition; Comparison between Single 8-28HP class (tier 2) under 95% connection ratio

** Condition:16HP class ODU (45.0kW) *1
 3HP class IDU (8.0kW) * 5
 Total piping length; 120m
 IDU connection ratio: 89%



SmoothDrive™ 2.0 : Superior compressor control

• Verified 39% less energy-consumption at part-load operation

Most of the time HVAC systems are under part-load because of ambient conditions, set temperature, occupancy and over-specification of the system. As organizations look to improve energy efficiency and reduce carbon footprint by mandating set temperatures within a reasonable range, part-load becomes even more important. Hitachi air365 Max utilizes direct capacity control which combines accurate temperature sensing with precise compressor control to balance load and capacity with less fluctuation. And its effect on energy consumption is verified formally at 3rd party testing facility.

<Testing Condition>
 (at Cooling Operation, Load Factor: Approx. 33%)
 Without SmoothDrive; average power consumption 2.46kW
 With SmoothDrive; average power consumption 1.49kW

VRF ODU: (RAS-AP280DG3 = RAS-10FSNS)
 VRF IDU: 4-way cassette indoor units (RCI-AP140K5 = RCI-5.0FSRP)
 Indoor Unit Inlet Temperature: 27°C (Dry Bulb) / 19°C (Wet Bulb)
 Ambient Temperature at Air Volume *High*: 23°C (Dry Bulb)
 Piping Length between Indoor Unit and Outdoor Unit: 15m
 Testing Location: Environment Testing Facility at Kansai Denryoku (power supply company)

VRF air conditioners in buildings experience all kinds of changes during the day...

People coming and going...

Changes in outdoor weather conditions...

Variations in temperature preferences...



This causes VRF systems to operate at partial load

More than 70% of the time during a year, a VRF System will be running under part-load conditions, with most systems operating at 50% or less of their capacity*1.

These unpredictable part-load conditions cause real-world performance to deviate significantly from official published energy efficiency data.

It's a key reason why your customer may not fully experience all the energy savings they expected from new equipment.

The simplicity of SmoothDrive

We believe the key to energy efficiency at part load is how generating capacity is controlled. In a normal VRF system this capacity control can be complex, combining both control of refrigerant evaporation temperatures and compressor operation. But at Hitachi Cooling & Heating we've developed a more simple approach called SmoothDrive.

Why SmoothDrive ?


Part-load conditions cause real-world performance to deviate significantly from official published energy efficiency data. Which is why Hitachi's patented direct capacity control technology delivers...

- real-world energy efficiency**
Improved energy efficiency under part-load operation, which regulatory energy efficiency ratings do not account for.
- temperature stability**
With continuous monitoring and adjustment of the capacity based on compressor speed, indoor temperatures can be maintained more accurately.
- smoother compressor operation**
Compressor rotation frequency is more precise and stable. On/Off cycles are reduced, while peaks and drops are diminished, reducing wear on the compressor.


Real-world energy efficiency**

Improved energy efficiency under part-load operation, which regulatory energy efficiency ratings do not account for

COP in Cooling mode



COP in Heating mode




■ without SmoothDrive
 ■ with SmoothDrive
 * Averaged power/load are calculated for 5 hours from start
 * COP = Averaged load / Averaged power


Temperature stability**

With continuous monitoring and adjustment of the capacity based on compressor speed, indoor temperatures can be maintained more accurately

Cooling 50% Load



Cooling 35% Load




Set temp: 27°C
 Initial IDU temp: 27°C / 19°C
 — Air Inlet temperature of IDUs (without SmoothDrive)
 — Air Inlet temperature of IDUs (with SmoothDrive)


Smoother compressor operation**

Compressor rotation frequency is more precise and stable. On/Off cycles are reduced, while peaks and drops are diminished, reducing wear on the compressor.


Cooling 50% Load



Cooling 35% Load



** Outdoor Unit; 10HP class. Indoor Unit: 5HP Class 4-way cassette unit * 2 pcs. In our own company's fixed-load testing facility(Dimension of the room per one indoor unit :5.6m×2.5m×3.1m). Outdoor temp (DB / WB): 29°C / 19°C. Load per room (Sensible / Latent): 4.9kW / 0.0kW. Set temperature: 27°C. Initial Indoor unit temperature (DB / WB) : 27°C / 19°C. Indoor unit fan airflow rate: Hi-mode.



*1. JIS B 8616:2015(Japanese packaged air conditioners standard) to arrange the performance test for the system.

QR Please refer to the leaflet for details

Add YouTube video or SmoothDrive brochure link


Demand control

- Manage your electricity during peak periods
- Peak-cut Control
- Moderate Control

A Demand Response Enabling Device (DRED) air conditioner allows your electricity provider to control the system at various pre-programmed levels, to manage your demand on the power grid during peak periods.

The aim is to reduce overall power consumption to the supply network at critical peak load times.


This feature can be enabled and disabled on an individual or centralized Hitachi controller. No additional equipment is required.




Better energy saving operation (Motion Sensor Control)

- Compatible internal units (IDUs) can automatically detect occupancy and automate operation accordingly

The presence sensor makes it possible to control operation based on the persons present in the climate controlled space. If the VRF unit is installed in a room in which the presence of persons is not constant, the sensor makes it possible to automatically control operation in such a way as to reduce consumption and achieve energy savings.



Automatically saves ability by detecting the amount of human activity



- Standard operation**
In a room with a lot of people moving, standard operation
- Save Power**
Moderate air conditioning when there is little movement of people
- Save more**
When there are no people for a certain period of time, the air conditioning is even more modest
- Forgetting to turn off**
If the absence continues for more than 30 minutes, the operation can be stopped by setting
- Resume**
Resume standard operation when people return



Lowering direct environmental impact

- Complied Regulation

"Localize Contents" []


- Eco-friendly packaging

Our unit packages are all designed for easy disposal
ODU: Wood/Paper packaging only
IDU: Classification marks for easier recycling of plastic



A complete solution at every stage

From design to installation, operation and maintenance, air365 Max is here to make your work easier.




Larger capacity, smaller footprint

- Single module capacity up to 28HP per unit
- Up to 28% smaller cabinet footprint*
- Maximum combination up to 112HP
- Maximum IDU connection ratio up to 200%
- Supports vertical stacking of ODUs to save space


Lower initial cost through faster and easier installation
 Occupies less space in buildings, rooftops or balconies
 Enables more real estate for greenery or photovoltaic systems

Single module capacity




Smaller cabinet footprint


In case of 28HP



In case of 56HP



In case of 84HP




Thanks to 200% IDU connection ratio

In case that IDU total capacity are 52HP

Before


2 ODU Operate 12 IDU
 (The least ODU you need to purchase was 40HP unit (HNCQ L-size*2))



$IDU\ 52HP = ODU\ 40HP * 130\%$

1 ODU Operate 12 IDU

(The least ODU you need to purchase is 26HP (NEW cabinet L-size*1))




$IDU\ 52HP = ODU\ 26HP * 200\%$




Thanks to large capacity & installation flexibility

In case that ODU total capacity is 320HP

16 units on the roof




12 units on the roof (Larger Capacity but Smaller units)




Point 1

Effective use of space, such as rooftop greenery and solar panel installation



Point 2


Vertical installation is available now to save the ODU occupied space almost half




High external static pressure (ESP)

- Total 4 steps of ESP
- Maximum up to 80Pa

The High External Static Pressure (ESP) setting for air365 Max units enables them to be located inside ventilated machine rooms, rather than just outdoors. This may reduce installation costs as well as reducing impact on the external facade of the building.





System Design


More flexible piping configuration

- Maximum piping length up to 200m
- Maximum height difference up to 110m

Longer pipe runs and greater height differences enable more flexibility for use in retrofit or renovation projects
 Supports installation in high-rise buildings
 Depending on building design, enables location of all units on the rooftop for faster installation and easier maintenance
 Enables more discrete placement further away from visual and noise sensitive spaces

Maximum Piping Length

	Mark	Allowable Piping Length
Total Piping Length	Total Liquid Piping Actual Length	≤ 1,000m
Maximum Piping Length	Actual Length	≤ 200m
	Equivalent Length	≤ 225m
Maximum Piping Length between Multi-kit of 1st Branch and Each Indoor Unit	L1	≤ 100m
Maximum Piping Length between Each Multi-kit / CH-Box (Multiple Branch Type) and Each Indoor Unit	L3*3	≤ 40m
Total Piping Length between CH-Box and Each Indoor Unit	e+f+g+h+i	≤ 40m
Piping Length between Piping Connection Kit 1 and Each Outdoor Unit	La, Lb, Lc, Ld	≤ 25m
Height Difference between Outdoor Units and Indoor Units	O.U. is Higher	110(50)*1
	O.U. is Lower	110(40)*2
Height Difference between Indoor Units	H2	≤ 40m*4
Height Difference between Indoor Units using the Same Branch of CH-Box	H3	≤ 4m
Height Difference between CH-Boxes	H4	≤ 40m*4
Height Difference between Outdoor Units	H5	≤ 2.0m
Height Difference between CH-Box and Indoor Units	H6	≤ 15m



- Notes:
- The maximum piping length of 110m is available on request. The following restrictions apply when the height difference between the outdoor units and the indoor units (the outdoor unit is higher) are 50m or more.
 - The maximum outdoor temperature during cooling operation is 43°C.
 - The height difference between the outdoor units and the indoor units must be 50m or less when the outdoor units are operated at an outside temperature of -10°C or less.
 - The connectable indoor unit capacity ratio is ≤ 100%.
 - To protect the system, the thermo OFF may be activated to turn the system off when the outside temperature is 38°C or more.
 - Performance priority mode is disabled.
 - The maximum piping length of 110m is available on request. The following restrictions apply when the height difference between the outdoor units and the indoor units (the outdoor unit is lower) are 40m or more.
 - The maximum outdoor temperature during cooling operation is 43°C.
 - The minimum outdoor temperature during cooling operation is 10°C.
 - The connectable indoor unit capacity ratio is ≤ 130%.
 - The piping length calculation is not included the Multi-Kit between CH-Box and Indoor Unit(s). (Lm in following examples are NOT L3.)
 - If the height difference between indoor units or the height difference between CH-Boxes exceed 15m, the liquid lines after the Multi-kitof first branch should be selected according to Height Difference between Indoor Units Restriction.

Widest choice of indoor units

- Total 18 types
- Design award winning design

With more than 100 different indoor units to choose, air365 Max supports a wide range of building layouts and interior design requirements
 Includes units that can be hidden to suit indoor aesthetics
 Exposed units that minimize installation costs
 Best balance of cost and aesthetics can be supported by the unique Silent-Iconic 4-way cassette panel




Anytime & Anywhere


- Cooling in 52 ~ -10°C
- Heating in 16 ~ -25°C
- Normal operation even under up to 60m/s
- JRA anti-corrosion treatment available

Because we live in a diverse and changeable world, our air365 Max units are designed to operate faultlessly in any climates and weather situation

Summer temperature




Cooling operation from up to 52°C ambient temperature




*Only in the case where the outside temperature (outdoor unit air inlet temperature) rises temporarily due to, for example, the installation condition, the system can be used at a temperature up to 52°C.

Winter temperature




Heating operation from as low as -25°C ambient temperature



**The range is intended for only a limited amount of time, for example, starting up the system early in the morning and is not for continuous stable operation for a long period of time.

Wind-proof cabinet



Test machine: RAS-FSNS (confirmed that it has the same structure and has the same durability of air365 Max RAS- HNCC)
 Test conditions: Experiment of blowing wind equivalent to 60m/s
 Test results: Operation is possible with no scattered parts or cracks in the refrigerant pipes.
 Assessment site: by Large fan at Tsukuba Techno Center of Ryuki Engineering Inc.

Anti-Corrosion Cabinet + Gecko-proof treatment

If your project is located in an extreme weather environment, consider applying an anti-corrosion treatment to your air365 Max outdoor units. Treatment can be arranged in factory based on the JRA9002 standard, with multiple layers on every component of the unit. With this treatment, the life expectancy in marine salty-air environments can be doubled. It is also effective against lizards/geckos.



Corrosion Resistance


Life-expectancy comparison In salty-air-location

Standard	1x
Anti-corrosive Treatment Custom Order	2 times longer!
Heavy anti-corrosive Treatment Custom Order	2 times longer!

Corrosion-resistance improved Heat Exchanger

3 Coating Layers

- Hydrophilic Resin Film
- Corrosion-Resistance Resin Film
- Phosphoric Acid Chromate Treatment
- Aluminum Fin



*Considered JRA9002: Criteria and Testing of Corrosion-proof for Refrigeration and Air Conditioning Equipment against Salty Air
 *Please consult Hitachi distributors for more details
 *Both "Anti-corrosive treatment" and "Heavy anti-corrosive treatment" are by custom order



System Design

Ch-Box (Change-Over Box)

- Lightweight, smaller and easy to install
- No drain connection required
- Widest lineup (From Single up to 16 multi-ports system configuration)

Connecting the outdoor and indoor units, the CH-Box is a key component in the performance of the air365Max of Heat Recovery operation, because it can affect the initial installation cost, also the indoor comfort of quietness too.

Our CH-Box now offers greater flexibility in both single-port or multi-port models, with a new compact and lightweight body, and requires no drain connection.


Depending on the building shape, you can select the best port, which will optimize the best performance & cost balance.



Wider lineup


Type	Single-Port		Multi-Port				
	CH-AP160SSX	CH-AP280SSX	CH-AP04MSSX	CH-AP08MSSX	CH-AP12MSSX	CH-AP16MSSX	
Model							
Dimensions (H×W×D)	mm 191×301×214	191×301×214	260×303×352	260×543×352	260×783×352	260×1,023×352	
N/W	kg 6	6	14	25	36	47	
Electrical Details	Power Supply	1~/N, [220-240V/50Hz]					
	Power Input	W 5	5	11.2	22.4	33.6	44.8
	Current	A 0.1	0.1	0.2	0.4	0.6	0.8
Maximum Total Capacity Index	kW 16	28	44.8	85	85	85	
Number of port (for IDU)	1	1	4	8	12	16	
Maximum Connectable IDUs per Port	7	8	6	6	6	6	
Maximum Piping length	Total piping length between CH-Box and each indoor unit per branch	m 40	40	40	40	40	40
	between CH-Box	m 40	40	40	40	40	40
	Between CH-Box and IDU	m 15	15	15	15	15	15
Maximum Height difference	Between Indoor Units Connected to Each Branch of Same CH-Box (Multiple-Port Type)	m 15	15	15	15	15	15
	Between Indoor Units using the Same Branch of CH-Box	m 4	4	4	4	4	4

System configuration




Which is better?

“Long narrow building” application



Single-Port	Item	Multi-port
58m	Total piping Length	136m
6	Needed multi-kit sets	0
92 points (Brazing: 57/Flare: 32)	Connection Points	34 points (Brazing: 6/Flare: 28)
14	Hanging Rods for CH-Box	4
14 pieces	Total Ceiling Access Panel	8 pieces

“Central CH-Box location” application



Single-Port	Item	Multi-Port
60m	Total piping Length	63m
6	Needed multi-kit sets	1
92 points (Brazing: 57/Flare: 32)	Connection Points	40 points (Brazing: 12/Flare: 28)
14	Hanging Rods for CH-Box	8
14 locations	Total Ceiling Access Panel	9 locations

System Design



airCloud Select

• “airCloud Select” is the new software created by Hitachi to help you quickly finish the unit selection for your VRF design project.

- Enjoy a super intuitive and modern interface
- Select the suitable VRF equipment for each project
- Generate automatic report for your customers



airCloud Select is available upon request. Availability varies per country. For more information, please contact your Hitachi Cooling & Heating representative or visit www.hitachi-aircon.com




Delivery

Easier delivery

- Load up to 14% more AC capacity in a single vehicle




Our air365 Max units are designed to work in harmony with your outdoor and indoor spaces. Lighter and smaller than ever before, they are easier and cheaper to transport.



In case of 40ft container

Now air365 Max: L cabinet up to 28HP class) can be loaded by 14pcs
Previously, L cabinet (RAS-FSNS/HNCQ) was up to 24HP class
So, just simply if it is the comparison of single module combination, 14% more load.



Before



In case of 10ft van

L size up to 10pcs
So, previously, 80HP cabinet (LLLL) *2, and 48HP cabinet (LL) *1 was full of 10ft van.
Now air365 Max: 80HP cabinet (LLL) *2, and 48HP cabinet (LL)*1 is not FULL yet
You can have another two cabinet of LL too! So even same capacity, but still 20% more space left!!!

Before





Safer unloading

- The holes for hanging by Sling belt by crane trucks
- The holes for the hand/fork lifters

New cabinet design features more holes for forklifting or craning
Center holes are for forklift trucks or hand-lifters
Outer two holes are used for sling belts to lift the units with a crane

- ① Package shows the part to be hung by lifting cranes too
- ② In case of forklift or handlifer, even without pallet, there is a special hole to be transported






Installation

Easy delivery with holes


- 4 different types of all delivery can be easily arranged

Our air365 Max units are designed to work in harmony with your outdoor and indoor spaces. Lighter and smaller than ever before, they are easier and cheaper to transport.

Package shows the part to be hung by lifting cranes too




In case of forklift or handlifer, even without pallet, there is a special hole to be transported



Mobile deck can be supported by the front bottom part



Large yet small footprint cabinet >> fit in the lift




Choice of piping direction



- 4 directions, 9 options

To make the installation as easy as possible, air365 Max unit can be piped from the front and base of the units via 9 different piping options. Bottom piping connection is large enough for refrigerant piping with standard insulation.

Front



Back



[Front]

- Through the piping port on the front panel cover
- Through the Unit base hole
- [To the right]**
- Through the piping port on the front cover
- From bottom of the cabinet
- Through the Unit base hole

[To the left]

- Through the piping port on the front cover
- From bottom of the cabinet
- Through the Unit base hole
- [To the rear]**
- Through the Unit base hole




H-LINK: flexible route of communication wiring


- Faster wiring with H-LINK

Hitachi H-LINK is a powerful, proprietary communication system that lets you control multiple outdoor and indoor units from one control point. For installers and service engineers, H-LINK simplifies the whole building wiring works by enabling units to 'daisy chain' together - making wiring connections from the closest available unit, regardless of the type. This can reduce installation time and costs.

H-LINK



Company A



- ODU configuration: 4X faster
- IDU/controller configuration: 2X faster

Faster configuration using our patented airCloud Tap mobile app and NFC (Near-field communication) technology embedded in the outdoor unit and individual controllers

All settings are available with convenient descriptions inside the phone app


Operators can 'copy and paste' settings for one ODU (or IDU via individual controller) to multiple units using their phone

Ideal for hotels, classrooms, businesses with multiple meeting rooms or large buildings with multiple VRF outdoor units installed

Download airCloud Tap!




76% time reduction (ODU configuration)




- 1) Conventional way to open and close the cover and manipulate dip/power switch: >>> takes 40min 40sec
 - 2) By using airCloud Tap without opening the cabinets: takes 9min 40 sec [Simulation scenario]
- total 4 ODUs initial setting
 - total 5 items setup; ODU number, Refrigerant cycle number, Higher ESP setting, Power Supply setting, and Compressor manual-off setting.

53% time reduction (IDU + CTRL configuration)



- 1) Conventional way: takes 103min 16sec
 - 2) By using airCloud Tap: takes 47min 40 sec [Simulation scenario]
- Total 20 controller setting
 - Total 7 items of setup: Room name, Time, Language, Temperature unit, Backlight of the screen, Operation schedule from Monday to Friday 08:30-18:30 28°C, Upper and lower limit of setting temperature for both cooling and heating



Commission


Service Checker

- Quicker & easier commissioning

Service Checker is a dedicated service device for HVAC technicians. It can connect to the ODU PCB to download continuous operation data for the whole VRF system and create a commissioning report easily.

Key features

- Display and storage of all operation data
- Graphical visualization of operation data
- Rapid report creation
- Access to all unit settings/configuration





Operation

Monitoring app airCloud Pro

- Control is in your hands. 24/7 control at your fingertips on smartphone, tablet, or PC.



For stand-alone and multi-site applications.





✓ **Intuitive simplicity**
airCloud Pro is designed to make your job easier. An intuitive app that anyone can use, airCloud Pro makes managing your VRF systems easier than ever before.

✓ **Control from anywhere**
Enjoy the freedom of remote access from your smartphone, tablet or laptop. airCloud Pro allows you to remotely control your VRF system(s) from a single app, saving you travel time.

Localize (add YouTube link at your side)

Individual controllers PC-ARFG1 / PC-ARC



- A new generation of room controllers with User friendly UX/UI

ADVANCED-COLOR CONTROLLER (PC-ARFG1-*)



Complete controls in a rich interface

- Colored screen displaying visual charts and descriptive texts
 - Access to all existing Hitachi VRF indoor unit features including user features settings, installation & maintenance features settings.
 - Energy consumption monitoring
 - Ideal for indoor units with motion sensors, cassettes with elevating grilles
 - Multiple languages available
- *Except Sleep Mode timer



reddot winner 2021



Localize (add YouTube link at your side)

ECO-COMPACT CONTROLLER (PC-ARC-*)



Value without compromise

- Segment screen displaying pictograms
- Essential controls in a glimpse
- On/Off weekly schedule
- Some extra advanced features such as GentleCool, Power-Saving Peak-Cut mode and Sleep Mode Timer
- Embedded IR receiver, ideal for ducted units

Localize (add YouTube link at your side)




Maintenance

Compressor rotation control

- Extend ODU lifecycle

manages equal loading on multi-compressor configurations, ensuring equal lifespan of each compressor in the system

Compressor rotation frequency control (example)




*1 At least 2 outdoor units are required for this function.
*2 Comparison between the rotation operation function and non-rotation operation function based on the same system.

Emergency operation mode

- Continue HVAC operation in the event of a unit failure

In multi-unit installations, the Backup Operation Function prevents the system from coming to a complete stop if an outdoor unit failure occurs. If one outdoor unit should fail, the system can continue to operate using the remaining outdoor units. Emergency operation can be performed up to 8 hours after unit stoppage.




* Emergency operation can be performed within 8 hours after unit stoppage. Emergency operation cannot be performed when 8 hours have elapsed since unit stoppage.

Oil-return control

- Patented oil control for lower noise and higher energy efficiency

As well as reducing lubricating oil loss, this patented oil return control cycle consumes less energy and produces much less noise—resulting in higher efficiency and greater comfort for occupants

- Every hour, oil-return operation activates for just 60 seconds (cooling mode) / 120 seconds (heating mode)
- During oil return mode, indoor units can continue to operate normally



airCloud Tap for faster maintenance



- 6X faster access to unit operational data*
- 80% time reduction (ODU data check)

Previously, a maintenance engineer would need to open both the front panel of the cabinet and electricity box panel, then check error codes on the PCB.

Now with the airCloud Tap app, an engineer can simply 'tap' the outdoor units with their smartphone to access a full range of configuration settings and download operational data if required for basic troubleshooting.


No need to open the panel to check simple data anymore!!!

The technology is also embedded in individual controllers enabling access to indoor unit settings.

Download airCloud Tap!




Before



FINISH
3 minutes to complete

Using the airCloud Tap, operate the app, touch the ODU, and obtain the data >>> total 30sec



FINISH
30 seconds to complete

Note.
Test simulation scenario: Check the alarm cause [Previously] open up the cabinet panel, open the electricity box cabinet panel, check the 7segment of the PCB, then, close the two cabinet panels.
>>> minimum takes 3min
[Now] just activate the airCloud Tap application, and, operate the screen, and TAP the outdoor unit and obtain the data >>> takes 30sec!

NEW

Powerful support app for your quick configuration & maintenance



Available on the App Store

ANDROID APP ON Google Play

Localize (add YouTube link at your side)

Enjoy the perfect air anywhere, anytime


Indoor comfort

ORIGINAL GENTLECOOL

- Prevents cold drafts all the time

When starting up air conditioners can discharge very cold air to quickly reach the required temperature for the room, but this can result in cold drafts making occupants uncomfortable. With GentleCool you can adjust the balance between achieving a lower room temperature quickly and avoiding cold drafts.

Because you can now set your preferable WIND temperature, as well as ROOM temperature.



DIRECT/INDIRECT CONTROL


- Occupants can choose whether they want to directly feel airflow

The presence of occupants is detected through a motion sensor which divides the room into 4 zones – one for each louvre. For each of the 4 zones served by a cassette, air can be served either Direct or Indirect. Therefore one zone could receive direct airflow while another has indirect airflow.

Indirect air flow

Horizontal air flow, for circulation above and around occupants without air blowing directly on them.

(Image) during cooling




Detect people

Direct Air Distribution

Conditioning the air by Auto-Swing airflow so that people can feel the direct cold air

(Image) during cooling




Detect people

HOTEL SETBACK

- Interlocks with hotel key card to automate operation based on guest entry


Hotel Setback temperature with interlock to key card reduces AC operation when the guest leaves but maintains room temperature within a comfortable range. Win-win feature for both hotel guests & hotel managers to achieve Comfort-satisfaction & energy saving operation



ORIGINAL CROWDSENSE

- Maintains a stable temperature as the number of occupants change


With CrowdSense technology, our VRF cassette units can determine how many people are in a space and adjust the cooling or heating capacity accordingly, so the room will never get too hot or cold, whether it's crowded or almost empty.



FLOOR-SENSE COOLING

- Prevents over-cooling of the floor area in cooling mode

In cooling scenarios, FloorSense Cool can prevent the floor area from overcooling by controlling airflow and cooling capacity so that the air at floor level does not get as cool as air above knee height.




FEET-WARM HEATING

- Intelligent heated air distribution, tailored for the human body.


In room heating scenarios, it's common to hear users complain of cold feet because heat naturally rises. FeetWarm helps to solve this problem by optimizing airflow in heating mode to ensure that the leg zone is consistently heated.

Conventional heating



Average temperature 30cm above the floor = 15.4°C

Heating with FeetWarm




Average temperature 30cm above the floor = 17.9°C

Low Noise Operation

- Neighborhood-friendly outdoor unit with 3dB(A) lower noise output* in average

Balance is the key to harmony, so air365 Max incorporates features to ensure a more peaceful environment, both indoors and out. Enjoy quiet comfort indoors with less disturbance to the outside environment. You can set this feature from your individual controller easily.

#Normal Sound Pressure (SPL) in Full Anechoic VS #Night-shift mode (SPL) in Full Anechoic Average -3.0dB(A)
Reference: Architectural Institute of Japan "Sound insulation performance standards and design guidelines for buildings"




ORIGINAL DIRECT capacity control SmoothDrive™ 2.0

- Constant indoor temperature even during part-load operation

With continuous monitoring and adjustment of the capacity based on compressor speed, indoor temperatures can be maintained more accurately.

Localize (add YouTube link at your side)




- SmoothDrive helps the scroll compressor to run continuously and smoothly even at part-load condition.
- Our original load-speculation technology helps reduce energy loss caused by scroll compressor switching on/off.
- Consequently, constant room temperature & energy savings can be achieved.

50% Load


Cooling Mode

Set temp: 27°C
Initial IDU temp: 27°C / 19°C




Heating Mode

Set temp: 20°C
Initial IDU temp: 20°C / 14°C



— Air Inlet temperature of IDUs (without SmoothDrive)
— Air Inlet temperature of IDUs (with SmoothDrive)



* Outdoor Unit; 10HP class. Indoor Unit: 5HP Class 4-way cassette unit * 2 pcs. In our own company's fixed-load testing facility(Dimension of the room per one indoor unit :5.6m×2.5m×3.1m). Outdoor temp (DB / WB): 29°C / 19°C. Load per room (Sensible / Latent): 4.9kW / 0.0kW. Set temperature: 27°C. Initial Indoor unit temperature (DB / WB) : 27°C / 19°C. Indoor unit fan airflow rate: HI-mode.



IAQ matter


ViroSense S filter

Our standard VRF filter has been upgraded to ion technology

Contains a silver ion that is released in the presence of moisture, binding to cellular enzymes of microbes and inhibiting enzyme activity of the cell wall, membrane, and nucleic acids.

Anti-virus (>99% inhibition) / Anti-bacteria (>99% inhibition) / Anti-mold (100% growth stop)

Standard-equipped filter
ViroSense S filter



BENEFITS

ANTI-VIRUS



over 99% Inhibition

ANTI-BACTERIA



over 99% Inhibition

ANTI-MOLD



100% growth stop

ViroSense Z2 Filter

This optional filter can help to reduce the risk of secondary SARS-CoV-2 infections in a room

Contains Zinc Ion - in the presence of moisture it is able to bind to virus and bacteria and inhibit.

Anti-virus (>99.7% inhibition) / Anti SARS-CoV-2 (>99.9% inhibition) / Anti-bacteria (>99% inhibition)

Optional accessory filter
ViroSense Z2 Filter



BENEFITS



SARS-CoV-2
Inhibition by
over 99.9%



Virus
Inhibition by
over 99.7%



Bacteria
removal by
over 99%



Life span of
up to 4 years



Quick
anti-virus
transformation


AQtiv-Ion Kit

AQtiv-Ion Kit for Ducted units

- Easily installed in a VRF ducted indoor unit
- A low-maintenance non-intrusive way of purifying air without installing separate purification units
- Generates negative ions and emits through AC airflow, binding to pollutants sending them to the floor
- Plug & play: convert your ducted IDU into an air-purifying IDU

- More than 99.9% effective on SARS-CoV-2 virus
- Up to 96.85% capturing of Influenza virus
- Up to 74.90% removal of odors (formaldehyde)
- Minimum impact on energy consumption & noise compared to external air purifier
- Electrical power consumption: max 3W

Optional accessory filter
AQtiv-Ion Kit



BENEFITS


SARS-CoV-2	Escherichia coli	Influenza virus	Staphylococcus aureus	PM2.5	Formaldehyde	Ammonia
-99.9% (Inhibition rate)	-96.64% (Inhibition rate)	-96.85% (Removal rate)	-93.88% (Inhibition rate)	-94.46% (Removal rate)	-74.90% (Removal rate)	-73.20% (Removal rate)

Smart cool/heat changeover

· Optimized comfort for all users during season changes

With Heat Pump type system, you can control how the system decides to switch between heating and cooling modes.

- Based on how many areas require cooling vs heating (majority voting)
- Based on total gap between set and ambient temperature across all rooms
- Based on prioritized rooms




Example of 3 modes

1 Majority mode

Under the conditions

Request for cooling mode: 2 units
Request for heating mode: 6 units

Demand



Result

Adopted Heating mode




2 Larger gap mode

Under the conditions

Cooling demand: temp. differences is total Δ8°C
Heating demand: temp. differences is total Δ5°C

Demand



Result

Adopted Cooling mode




3 Priority unit mode

Under the conditions


Priority indoor unit requests cooling mode

Demand



Result

Adopted Cooling mode






*Please consult Hitachi distributors for more details

Smart Defrosting

- Defrosting frequency shortened by 2X for single ODU configurations


For Heat Pump types:
 Operate in up to -25°C ambient
 Defrosts the ODU in cold temperatures while minimizing the resulting downtime of the indoor units
 Patented intelligent sensing technology detects when defrosting is required and instantly adjusts the exterior case temperature to eliminate ice and frost, so that it can reduce frequent and unnecessary defrosting operation.
 Defrosting frequency reduced by more than 50%, requiring a defrosting cycle as little as every 250mins



Networked Defrosting optimization

- Continuous operation in extreme cold weather for multi-ODU configurations

Enables multi-ODU configurations to maintain continuous operation by avoiding all ODU's defrosting at the same time



* To activate this feature, all outdoor units need to be under one centralized communication wiring system (H-LINK)


Simultaneous Cooling And Heating

The Heat Recovery range is ideal for highly insulated buildings in mild climates that vary by season.




Limit your total cooling and heating costs

By using and transferring excess energy from one zone to another, Heat Recovery systems minimize compressor operation to provide simultaneous cooling and heating. This means energy consumption is greatly optimized leading to low energy costs in the mid-season. Besides, in the case of rooms requiring cooling only all year long, heat recovery -by installing a cooling only indoor unit without CH-Box- can cover this need, thus sparing the need to install an extra dedicated cooling device.




Customized comfort

Thermal needs vary in each room of a building—some people might feel a little too warm, and some a bit chilly. This depends on the individuals, and also on the room's sunlight exposure and equipment functions. With heat recovery, every occupant can benefit from either cooling or heating at any time, based on his/her preferred set temperature.



Consistent temperature in large zones

The air365 Max Heat Recovery range allows simultaneous cooling and heating, even inside the same zone of the same refrigerant system. It is particularly ideal in large zones where some areas are subject to specific conditions (such as near a sunny window). Thanks to the automatic changeover function, each indoor unit automatically switches from cooling to heating to evenly reach the set temperature.




Heat Recovery or Heat Pump?

All buildings do not require simultaneous heating or cooling, such as those in areas with clearly defined seasons or with large, open-plan areas. Your Hitachi supplier can help you select the system best suited to your building.

Auto changeover superior defrosting performance

- Optimized heat recovery ensures greater energy savings
- Indoor unit thermostat or individual remote control can be used for temperature sensing

Consistency is the key to a harmonious interior environment. To ensure a consistent interior climate air365 Max can switch automatically from cooling to heating in any zone, by harvesting the waste heat from other zones.




Air Source Heat Recovery Type

LINE UP


(HP Class/Cooling Capacity/Heating Capacity/Net Weight/Operating Sound SPL (Full-anechoic) dB(A) in cooling mode)

Single module up to 28HP class!




Footprint 0.76m²

8HP class/22.4kW/25.0kW/210kg/52.0dB(A)
10HP class/28.0kW/31.5kW/215kg/55.0dB(A)
12HP class/33.5kW/37.5kW/230kg/57.0dB(A)




Footprint 0.96m²

14HP class/40.0kW/45.0kW/285kg/59.0dB(A)
16HP class/45.0kW/50.0kW/286kg/61.0dB(A)
18HP class/50.4kW/56.0kW/286kg/61.0dB(A)



Footprint 1.26m²

20HP class/56.0kW/63.0kW/368kg/59.0dB(A)
22HP class/61.5kW/69.0kW/368kg/59.0dB(A)
24HP class/67.0kW/77.5kW/368kg/61.0dB(A)
26HP class/73.0kW/81.5kW/393kg/62.0dB(A)
28HP class/77.5kW/86.0kW/393kg/62.0dB(A)



Footprint 3.51m²

62HP class/173.4kW/194.0kW/1,022kg/64.5dB(A)
64HP class/178.9kW/202.5kW/1,022kg/65.2dB(A)
66HP class/184.4kW/211.0kW/1,022kg/65.8dB(A)



Footprint 3.81m²

68HP class/190.0kW/215.5kW/1,104kg/64.5dB(A)
70HP class/195.5kW/224.0kW/1,104kg/65.2dB(A)
72HP class/201.0kW/232.5kW/1,104kg/65.8dB(A)
74HP class/207.0kW/236.5kW/1,129kg/66.1dB(A)
76HP class/213.0kW/240.5kW/1,154kg/66.5dB(A)
78HP class/219.0kW/244.5kW/1,179kg/66.8dB(A)
80HP class/223.5kW/249.0kW/1,179kg/66.8dB(A)
82HP class/228.0kW/253.5kW/1,179kg/66.8dB(A)
84HP class/232.5kW/258.0kW/1,179kg/66.8dB(A)



Footprint 1.73m²

30HP class/83.9kW/93.5kW/516kg/62.5dB(A)



Footprint 1.93m²

32HP class/90.4kW/101.0kW/571kg/63.1dB(A)
34HP class/95.4kW/106.0kW/572kg/64.0dB(A)
36HP class/100.8kW/112.0kW/572kg/64.0dB(A)



Footprint 2.23m²

38HP class/106.5kW/119.0kW/654kg/63.1dB(A)
40HP class/111.9kW/125.0kW/654kg/63.1dB(A)
42HP class/117.4kW/133.5kW/654kg/64.0dB(A)



Footprint 4.78m²

86HP class/240.4kW/271.5kW/1,390kg/66.1dB(A)
88HP class/245.9kW/280.0kW/1,390kg/66.6dB(A)
90HP class/251.4kW/288.5kW/1,390kg/67.0dB(A)



Footprint 5.08m²

92HP class/257.0kW/293.0kW/1,472kg/66.1dB(A)
94HP class/262.5kW/301.5kW/1,472kg/66.6dB(A)
96HP class/268.0kW/310.0kW/1,472kg/67.0dB(A)
98HP class/274.0kW/314.0kW/1,497kg/67.3dB(A)
100HP class/280.0kW/318.0kW/1,522kg/67.5dB(A)
102HP class/286.0kW/322.0kW/1,547kg/67.8dB(A)
104HP class/292.0kW/326.0kW/1,572kg/68.0dB(A)
106HP class/296.5kW/330.5kW/1,572kg/68.0dB(A)
108HP class/301.0kW/335.0kW/1,572kg/68.0dB(A)
110HP class/305.5kW/339.5kW/1,572kg/68.0dB(A)
112HP class/310.0kW/344.0kW/1,572kg/68.0dB(A)



Footprint 2.53m²

44HP class/123.0kW/138.0kW/736kg/62.0dB(A)
46HP class/128.5kW/146.5kW/736kg/63.1dB(A)
48HP class/134.0kW/155.0kW/736kg/64.0dB(A)
50HP class/140.0kW/159.0kW/761kg/64.5dB(A)
52HP class/146.0kW/163.0kW/786kg/65.0dB(A)
54HP class/150.5kW/167.5kW/786kg/65.0dB(A)
56HP class/155.0kW/172.0kW/786kg/65.0dB(A)



Footprint 3.20m²

58HP class/162.3kW/181.0kW/940kg/65.2dB(A)
60HP class/167.8kW/189.5kW/940kg/65.8dB(A)

Specification Notes

- (Note 1) The cooling and heating performances are the values when combined with our specified indoor units.
[Cooling: 27°C DB/19°C WB indoor side, 35°C DB outdoor side] [Heating: 20°C DB indoor side, 7°C DB/6°C WB outdoor side]
Piping Length: 7.5 Meters Piping Lift: 0 Meter
- (Note 2) The electric characteristics show values of single outdoor unit.
- (Note 3) The operating sound is based on the following conditions. 1 Meter from the unit service cover surface, and 1.5 Meters from floor level.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- (Note 4) The dimensions show values when a space between outdoor units is 20 mm.
- (Note 5) In case of setting low ambient temperature at cooling operation, the minimum capacity of connectable indoor unit should be 2.5HP.
- (Note 6) When 0.6HP indoor unit is combined, the total capacity of combined indoor units should be not over 150% against the outdoor unit capacity.
- (Note 7) Refrigerant piping has some installation limitation in specific condition. Please refer to technical manual for more details.
- (Note 8) When connection ratio of outdoor unit and indoor unit is over 130%, additional setting is required. Air volume of indoor unit is restricted under some of condition. Please refer to technical manual for more details.
- (Note 9) Outside temperature (-10°C) is for special application requiring optional accessory [snow protection hood]. The number <-> shows Interval Operation Range. Please refer to technical manual for more details.
- (Note 10) It is recommended to follow "Recommended IDU number" to avoid the cold draft during the heating operation. Please refer to technical manual for more details.
- (Note 11) Some restrictions would be applied when the height difference between outdoor units and indoor units is more than [50m: in case of ODU above IDU] or [40m: in case of IDU above ODU]. Please refer to technical manual for more details.

Specifications

S



M



L



Capacity range	Unit	8HP class	10HP class	12HP class	14HP class	16HP class	18HP class	20HP class	22HP class	24HP class	26HP class	28HP class	
Outdoor unit model		RAS-080RNCCLW	RAS-100RNCCLW	RAS-120RNCCLW	RAS-140RNCCLW	RAS-160RNCCLW	RAS-180RNCCLW	RAS-200RNCCLW	RAS-220RNCCLW	RAS-240RNCCLW	RAS-260RNCCLW	RAS-280RNCCLW	
Combination of modules													
Power supply	-	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	
Cooling capacity	kW	22.4	28.0	33.5	40.0	45.0	50.4	56.0	61.5	67.0	73.0	77.5	
Heating capacity	kW	25.0	31.5	37.5	45.0	50.0	56.0	63.0	69.0	77.5	81.5	86.0	
Outer dimensions (W x D x H)	mm	975×775×1,805	975×775×1,805	975×775×1,805	1,235×775×1,805	1,235×775×1,805	1,235×775×1,805	1,625×775×1,805	1,625×775×1,805	1,625×775×1,805	1,625×775×1,805	1,625×775×1,805	
Weight	Net weight	kg	210	215	230	285	286	368	368	368	393	393	
	Gross weight	kg	229	234	249	306	307	392	392	392	417	417	
Noise	Cooling rating	SPL (Full-anechoic) dB(A)	52.0	55.0	57.0	59.0	61.0	59.0	59.0	61.0	62.0	62.0	
	Night shift mode (noise reduction setting)	SPL (Full-anechoic) dB(A)	49.0	50.0	52.0	57.0	58.0	57.0	56.0	57.0	57.0	60.0	
Electric characteristics	Power consumption	Cooling	kW	4.07	5.73	7.21	8.55	9.91	11.71	12.44	13.84	16.17	18.73
		Heating	kW	4.80	6.18	7.81	9.91	12.12	13.04	12.91	15.64	19.93	24.23
	Operating current	Cooling	A	6.9	10.2	14.0	16.9	19.1	22.2	23.0	25.6	30.0	34.7
		Heating	A	8.1	10.9	14.8	19.1	22.7	24.5	23.6	28.6	36.5	44.4
	Breaker (A)	A	25	25	32	32	40	50	50	50	63	80	80
MAX current	A	16.1	20.0	23.3	27.7	32.7	39.7	40.0	42.7	53.0	58.3	59.4	
Energy efficiency	Outdoor Unit only	Cooling EER	-	5.50	4.89	4.65	4.68	4.54	4.30	4.50	4.44	4.14	3.90
		Heating COP	-	5.21	5.10	4.80	4.54	4.13	4.29	4.88	4.41	3.89	3.36
Compressor	Compressor type	-	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	
	Motor output	kW	4.12	5.4	6.72	8.48	10.42	11.22	5.5×2	6.77×2	8.7×2	10.55×2	12.98×2
Outdoor unit Fan	Rated air volume	m ³ /min	175	175	198	256	239	329	329	348	375	375	
	Number of Fan Motors	-	1	1	1	2	2	2	2	2	2	2	
Main pipe size	Heat Recovery	Gas Piping (Low Pressure)	mm	19.05	22.2	25.4	25.4	28.58	28.58	28.58	28.58	31.75	31.75
		Gas Piping (High/Low Pressure)	mm	15.88	19.05	22.2	22.2	22.2	22.2	22.2	25.4	25.4	28.58
	Liquid Piping	mm	9.52	9.52	12.7	12.7	12.7	15.88	15.88	15.88	19.05	19.05	
	Tube connection method	-	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	
Operating temperature range	Cooling	°C DB	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	
	Heating	°C WB	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	
Maximum External Static Pressure	Pa	80	80	80	80	80	80	80	80	80	80	80	
Maximum Total piping length	m	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	
Maximum piping length	Between ODU and IDU	Actual	m	200	200	200	200	200	200	200	200	200	
		Equivalent	m	225	225	225	225	225	225	225	225	225	
	Between "Piping connection kit" and each ODU single module	m	-	-	-	-	-	-	-	-	-	-	
	Between "1st branch Multi Kit" and farthest IDU	m	100	100	100	100	100	100	100	100	100	100	
	Between "Multi Kit" and each connected IDU	m	40	40	40	40	40	40	40	40	40	40	
Between "CH-Box" to each IDU	m	40	40	40	40	40	40	40	40	40	40		
Between each single module of 1 ODU	m	-	-	-	-	-	-	-	-	-	-	-	
Maximum height difference	Between ODU and IDUs	ODU above IDU (*)	m	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	
		IDU above ODU (*)	m	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	
	Between IDUs	m	40	40	40	40	40	40	40	40	40	40	
	Between CH-Box and indoor units	m	15	15	15	15	15	15	15	15	15	15	
	Between CH-Boxes	m	40	40	40	40	40	40	40	40	40	40	
Between indoor units after single CH-Box	m	4	4	4	4	4	4	4	4	4	4		
Refrigerant	Type	-	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
	Initial charge amount	kg	5.6	5.6	8.3	8.9	9.5	10.2	11.2	11.2	11.5	11.5	
	Maximum additional charge amount	kg	28.0	28.0	36.0	40.0	40.0	40.0	46.0	46.0	46.0	56.0	
Refrigerant control mode	-	Microcomputer-controlled electronic expansion valve					Microcomputer-controlled electronic expansion valve						
Refrigerant oil	Type	-	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	
	Charge amount	L	6.0	6.0	6.0	6.9	6.9	6.9	8.4	8.4	8.4	8.4	
With Indoor Unit	Maximum Connected capacity ratio	%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	
	Number of connectable units (recommended number of units)	-	20 (8)	25 (10)	30 (10)	36 (16)	40 (16)	45 (16)	50 (18)	55 (20)	60 (26)	64 (32)	
	Connectable minimum capacity	-	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	

Specifications

MS



MM



LM



LL



Capacity range	Unit	30HP class	32HP class	34HP class	36HP class	38HP class	40HP class	42HP class	44HP class	46HP class	48HP class	50HP class	
Outdoor unit model		RAS-300RNCCLW	RAS-320RNCCLW	RAS-340RNCCLW	RAS-360RNCCLW	RAS-380RNCCLW	RAS-400RNCCLW	RAS-420RNCCLW	RAS-440RNCCLW	RAS-460RNCCLW	RAS-480RNCCLW	RAS-500RNCCLW	
Combination of modules		RAS-180RNCCLW RAS-120RNCCLW	RAS-180RNCCLW RAS-140RNCCLW	RAS-180RNCCLW RAS-160RNCCLW	RAS-180RNCCLW RAS-180RNCCLW	RAS-220RNCCLW RAS-160RNCCLW	RAS-220RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-180RNCCLW	RAS-220RNCCLW RAS-220RNCCLW	RAS-240RNCCLW RAS-20RNCCLW	RAS-240RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-240RNCCLW	
Power supply	-	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	
Cooling capacity	kW	83.9	90.4	95.4	100.8	106.5	111.9	117.4	123.0	128.5	134.0	140.0	
Heating capacity	kW	93.5	101.0	106.0	112.0	119.0	125.0	133.5	138.0	146.5	155.0	159.0	
Outer dimensions (W x D x H)	mm	2,230×775×1,805	2,490×775×1,805	2,490×775×1,805	2,490×775×1,805	2,880×775×1,805	2,880×775×1,805	2,880×775×1,805	3,270×775×1,805	3,270×775×1,805	3,270×775×1,805	3,270×775×1,805	
Weight	Net weight	kg	286+230	286+285	286+286	286+286	368+286	368+286	368+286	368+368	368+368	393+368	
	Gross weight	kg	307+249	307+306	307+307	307+307	392+307	392+307	392+307	392+392	392+392	417+392	
Noise	Cooling rating	SPL (Full-anechoic) dB(A)	62.5	63.1	64.0	64.0	63.1	63.1	64.0	62.0	63.1	64.0	
	Night shift mode (noise reduction setting)	SPL (Full-anechoic) dB(A)	58.2	60.0	60.5	60.0	60.5	60.0	60.0	60.0	60.0	61.8	
Electric characteristics	Power consumption	Cooling	kW	18.92	20.26	21.62	23.42	23.75	25.55	27.88	27.68	30.01	32.34
		Heating	kW	20.85	22.95	25.16	26.08	27.76	28.68	32.97	31.28	35.57	39.86
	Operating current	Cooling	A	36.2	39.1	41.3	44.4	44.7	47.8	52.2	51.2	55.6	60.0
		Heating	A	39.3	43.6	47.2	49.0	51.3	53.1	61.0	57.2	65.1	73.0
	Breaker (A)	A	50+32	50+32	50+40	50+50	50+40	50+50	63+50	50+50	63+50	63+63	80+63
MAX current	A	63.0	67.4	72.4	79.4	75.4	82.4	92.7	85.4	95.7	106.0	111.3	
Energy efficiency	Outdoor Unit only	Cooling EER	-	4.43	4.46	4.41	4.30	4.48	4.38	4.21	4.44	4.28	4.14
		Heating COP	-	4.48	4.40	4.21	4.29	4.29	4.36	4.05	4.41	4.12	3.89
Compressor	Compressor type	-	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	
	Motor output	kW	11.22+6.72	11.22+8.48	11.22+10.42	(11.22)×2	6.77×2+10.42	6.77×2+11.22	8.7×2+11.22	(6.77×2)×2	8.7×2+6.77×2	(8.7×2)×2	10.55×2+8.7×2
Outdoor unit Fan	Rated air volume	m ³ /min	263+198	263+239	263+256	263×2	329+256	329+263	348+263	329×2	348+329	348×2	375+348
	Number of Fan Motors	-	2+1	2+2	2+2	2+2	2+2	2+2	2+2	2+2	2+2	2+2	
	Motor output	kW	0.38×2+0.43	0.38×2+0.3×2	0.38×2+0.35×2	(0.38×2)×2	0.4×2+0.35×2	0.4×2+0.38×2	0.47×2+0.38×2	(0.4×2)×2	0.47×2+0.4×2	(0.47×2)×2	0.58×2+0.47×2
Main pipe size	Heat Recovery	Gas Piping (Low Pressure)	mm	31.75	31.75	31.75	38.1	38.1	38.1	38.1	38.1	38.1	
		Gas Piping (High/Low Pressure)	mm	28.58	28.58	28.58	28.58	31.75	31.75	31.75	31.75	31.75	31.75
		Liquid Piping	mm	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05
	Tube connection method	-	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	
Operating temperature range	Cooling	°C DB	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	
	Heating	°C WB	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	
Maximum External Static Pressure	Pa	80	80	80	80	80	80	80	80	80	80	80	
Maximum Total piping length	m	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	
Maximum piping length	Between ODU and IDU	Actual	m	200	200	200	200	200	200	200	200	200	
		Equivalent	m	225	225	225	225	225	225	225	225	225	
	Between "Piping connection kit" and each ODU single module	m	25	25	25	25	25	25	25	25	25	25	
	Between "1st branch Multi Kit" and farthest IDU	m	100	100	100	100	100	100	100	100	100	100	
	Between "Multi Kit" and each connected IDU	m	40	40	40	40	40	40	40	40	40	40	
	Between "CH-Box" to each IDU	m	40	40	40	40	40	40	40	40	40	40	
Between each single module of 1 ODU	m	2	2	2	2	2	2	2	2	2	2		
Maximum height difference	Between ODU and IDUs	ODU above IDU (*)	m	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	
		IDU above ODU (*)	m	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	
	Between IDUs	m	40	40	40	40	40	40	40	40	40	40	
	Between CH-Box and indoor units	m	15	15	15	15	15	15	15	15	15	15	
	Between CH-Boxes	m	40	40	40	40	40	40	40	40	40	40	
Between indoor units after single CH-Box	m	4	4	4	4	4	4	4	4	4	4		
Refrigerant	Type	-	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
	Initial charge amount	kg	18.5	19.1	19.7	20.4	20.7	21.4	21.7	22.4	22.7	23.0	
	Maximum additional charge amount	kg	56.5	56.5	56.5	56.5	56.5	56.5	56.5	63.0	63.0	63.0	
	Refrigerant control mode	-	Microcomputer-controlled electronic expansion valve				Microcomputer-controlled electronic expansion valve						
Refrigerant oil	Type	-	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	
	Charge amount	L	12.9	13.8	13.8	13.8	15.3	15.3	15.3	16.8	16.8	16.8	
Maximum Connected capacity ratio	%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	50~200%	
With Indoor Unit	Number of connectable units (recommended number of units)	-	64 (32)	64 (32)	64 (32)	64 (32)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	
	Connectable minimum capacity	-	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	

Specifications

LL



LMM



LLM



LLL



Capacity range		Unit	52HP class	54HP class	56HP class	58HP class	60HP class	62HP class	64HP class	66HP class	68HP class	70HP class	72HP class	
Outdoor unit model			RAS-520RNCCLW	RAS-540RNCCLW	RAS-560RNCCLW	RAS-580RNCCLW	RAS-600RNCCLW	RAS-620RNCCLW	RAS-640RNCCLW	RAS-660RNCCLW	RAS-680RNCCLW	RAS-700RNCCLW	RAS-720RNCCLW	
Combination of modules			RAS-260RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-280RNCCLW	RAS-220RNCCLW RAS-180RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-180RNCCLW RAS-180RNCCLW	RAS-220RNCCLW RAS-220RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-220RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-220RNCCLW RAS-220RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-220RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-240RNCCLW	
Power supply		-	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	
Cooling capacity		kW	146.0	150.5	155.0	162.3	167.8	173.4	178.9	184.4	190.0	195.5	201.0	
Heating capacity		kW	163.0	167.5	172.0	181.0	189.5	194.0	202.5	211.0	215.5	224.0	232.5	
Outer dimensions (W x D x H)		mm	3,270×775×1,805	3,270×775×1,805	3,270×775×1,805	4,135×775×1,805	4,135×775×1,805	4,525×775×1,805	4,525×775×1,805	4,525×775×1,805	4,915×775×1,805	4,915×775×1,805	4,915×775×1,805	
Weight		Net weight	kg	393+393	393+393	393+393	368+286+286	368+286+286	368+368+286	368+368+286	368+368+368	368+368+368	368+368+368	
		Gross weight	kg	417+417	417+417	417+417	392+307+307	392+307+307	392+392+307	392+392+307	392+392+307	392+392+392	392+392+392	392+392+392
Noise		Cooling rating	SPL (Full-anechoic) dB(A)	65.0	65.0	65.0	65.2	65.8	64.5	65.2	65.8	64.5	65.2	
		Night shift mode (noise reduction setting)	SPL (Full-anechoic) dB(A)	63.0	63.0	63.0	61.8	61.8	61.8	61.8	61.8	61.8	61.8	61.8
Electric characteristics		Power consumption		Cooling	kW	37.46	39.48	41.50	37.26	39.39	41.72	44.05	43.85	
				Heating	kW	48.46	53.68	58.90	41.72	46.01	44.32	48.61	52.90	51.21
		Operating current		Cooling	A	69.4	73.1	76.8	70.0	74.4	73.4	77.8	82.2	81.2
				Heating	A	88.8	98.3	107.8	77.6	85.5	81.7	89.6	97.5	93.7
		Breaker (A)		A	80+80	80+80	80+80	50+50+50	63+50+50	50+50+50	63+50+50	63+63+50	63+50+50	63+63+50
MAX current		A	116.6	117.7	118.8	122.1	132.4	125.1	135.4	145.7	138.4	148.7	159.0	
Energy efficiency		Outdoor Unit only		Cooling EER	-	3.90	3.81	3.73	4.36	4.24	4.40	4.29	4.19	
				Heating COP	-	3.36	3.12	2.92	4.34	4.12	4.38	4.17	3.99	4.21
Compressor		Compressor type		-	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	
				Motor output		kW	(10.55×2)×2	12.98×2+10.55×2	(12.98×2)×2	6.77×2+(11.22)×2	8.7×2+(11.22)×2	(6.77×2)×2+11.22	8.7×2+6.77×2+11.22	(8.7×2)×2+11.22
Rated air volume		m ³ /min	375×2	375+375	375×2	329+263×2	348+263×2	329×2+263	348+329+263	348×2+263	348+329×2	348×2+329	348×3	
Outdoor unit Fan		Number of Fan Motors		-	2+2	2+2	2+2	2+2+2	2+2+2	2+2+2	2+2+2	2+2+2	2+2+2	
		Motor output		kW	(0.58×2)×2	0.58×2+0.58×2	(0.58×2)×2	0.4×2+(0.38×2)×2	0.47×2+(0.38×2)×2	(0.4×2)×2+0.38×2	0.47×2+0.4×2+0.38×2	(0.47×2)×2+0.38×2	0.47×2+(0.4×2)×2	(0.47×2)×2+0.4×2
Main pipe size		Heat Recovery		Gas Piping (Low Pressure)	mm	38.1	38.1	44.45	44.45	44.45	44.45	44.45	44.45	
				Gas Piping (High/Low Pressure)	mm	31.75	31.75	38.1	38.1	38.1	38.1	38.1	38.1	38.1
		Liquid Piping		mm	19.05	19.05	19.05	19.05	19.05	19.05	19.05	19.05	22.2	22.2
		Tubing connection method		-	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection
Operating temperature range		Cooling		°C DB	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	
		Heating		°C WB	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C
Maximum External Static Pressure		Pa	80	80	80	80	80	80	80	80	80	80	80	
Maximum Total piping length		m	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	
Maximum piping length		Between ODU and IDU		Actual	m	200	200	200	200	200	200	200	200	
				Equivalent	m	225	225	225	225	225	225	225	225	225
		Between "Piping connection kit" and each ODU single module		m	25	25	25	25	25	25	25	25	25	25
		Between "1st branch Multi Kit" and farthest IDU		m	100	100	100	100	100	100	100	100	100	100
		Between "Multi Kit" and each connected IDU		m	40	40	40	40	40	40	40	40	40	40
		Between "CH-Box" to each IDU		m	40	40	40	40	40	40	40	40	40	40
Between each single module of 1 ODU		m	2	2	2	2	2	2	2	2	2	2		
Maximum height difference		Between ODU and IDUs		ODU above IDU (*)	m	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	
				IDU above ODU (*)	m	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)
		Between IDUs		m	40	40	40	40	40	40	40	40	40	
		Between CH-Box and indoor units		m	15	15	15	15	15	15	15	15	15	
		Between CH-Boxes		m	40	40	40	40	40	40	40	40	40	
Between indoor units after single CH-Box		m	4	4	4	4	4	4	4	4	4			
Refrigerant		Type		-	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
		Initial charge amount		kg	23.0	23.0	23.0	31.6	31.9	32.6	32.9	33.2	33.9	34.2
		Maximum additional charge amount		kg	63.0	63.0	63.0	63.0	63.0	63.0	63.0	63.0	73.0	73.0
		Refrigerant control mode		-	Microcomputer-controlled electronic expansion valve				Microcomputer-controlled electronic expansion valve					
Refrigerant oil		Type		-	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D		
		Charge amount		L	16.8	16.8	16.8	22.2	22.2	23.7	23.7	23.7	25.2	
Maximum Connected capacity ratio		%	50~200%	50~200%	50~180%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%		
With Indoor Unit		Number of connectable units (recommended number of units)		-	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)		
		Connectable minimum capacity		-	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	

Specifications

LLL



LLLLM



LLLLL



Capacity range		Unit	74HP class	76HP class	78HP class	80HP class	82HP class	84HP class	86HP class	88HP class	90HP class	92HP class	94HP class		
Outdoor unit model			RAS-740RNCCLW	RAS-760RNCCLW	RAS-780RNCCLW	RAS-800RNCCLW	RAS-820RNCCLW	RAS-840RNCCLW	RAS-860RNCCLW	RAS-880RNCCLW	RAS-900RNCCLW	RAS-920RNCCLW	RAS-940RNCCLW		
Combination of modules			RAS-260RNCCLW RAS-240RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-260RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-260RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-260RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-280RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-280RNCCLW RAS-280RNCCLW	RAS-240RNCCLW RAS-220RNCCLW RAS-220RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-220RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-240RNCCLW RAS-180RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-220RNCCLW RAS-220RNCCLW	RAS-240RNCCLW RAS-240RNCCLW RAS-240RNCCLW RAS-220RNCCLW		
Power supply		-	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz		
Cooling capacity		kW	207.0	213.0	219.0	223.5	228.0	232.5	240.4	245.9	251.4	257.0	262.5		
Heating capacity		kW	236.5	240.5	244.5	249.0	253.5	258.0	271.5	280.0	288.5	293.0	301.5		
Outer dimensions (W x D x H)		mm	4,915×775×1,805	4,915×775×1,805	4,915×775×1,805	4,915×775×1,805	4,915×775×1,805	4,915×775×1,805	6,170×775×1,805	6,170×775×1,805	6,170×775×1,805	6,560×775×1,805	6,560×775×1,805		
Weight		Net weight	393+368+368	393+393+368	393+393+393	393+393+393	393+393+393	393+393+393	368+368+368+286	368+368+368+286	368+368+368+286	368+368+368+368	368+368+368+368		
		Gross weight	417+392+392	417+417+392	417+417+417	417+417+417	417+417+417	417+417+417	417+417+417	392+392+392+307	392+392+392+307	392+392+392+307	392+392+392+392	392+392+392+392	
Noise		Cooling rating	SPL (Full-anechoic) dB(A)	66.1	66.5	66.8	66.8	66.8	66.1	66.6	67.0	66.1	66.6		
		Night shift mode (noise reduction setting)	SPL (Full-anechoic) dB(A)	63.0	64.0	64.8	64.8	64.8	64.8	63.0	63.0	63.0	63.0	63.0	
Electric characteristics		Power consumption	Cooling	kW	51.07	53.63	56.19	58.21	60.23	62.25	55.56	57.89	60.22	60.02	62.35
			Heating	kW	64.09	68.39	72.69	77.91	83.13	88.35	64.25	68.54	72.83	71.14	75.43
		Operating current	Cooling	A	94.7	99.4	104.1	107.8	111.5	115.2	103.4	107.8	112.2	111.2	115.6
			Heating	A	117.4	125.3	133.2	142.7	152.2	161.7	118.2	126.1	134.0	130.2	138.1
		Breaker (A)	A	80+63+63	80+80+63	80+80+80	80+80+80	80+80+80	80+80+80	80+80+80	63+50+50+50	63+63+50+50	63+63+63+50	63+63+63+50	
		MAX current	A	164.3	169.6	174.9	176.0	177.1	178.2	178.1	188.4	198.7	191.4	201.7	
Energy efficiency		Outdoor Unit only	Cooling EER	-	4.05	3.97	3.90	3.84	3.79	3.73	4.33	4.25	4.17	4.28	4.21
			Heating COP	-	3.69	3.52	3.36	3.21	3.05	2.92	4.23	4.09	3.96	4.12	4.00
Compressor		Compressor type	-	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)		
		Motor output	kW	10.55×2+(8.7×2)×2	(10.55×2)×2+8.7×2	(10.55×2)×3	12.98×2+(10.55×2)×2	(12.98×2)×2+10.55×2	(12.98×2)×3	8.7×2+(6.77×2)×2+11.22	(8.7×2)×2+6.77×2+11.22	(8.7×2)×3+11.22	(8.7×2)×2+(6.77×2)×2	(8.7×2)×3+6.77×2	
Outdoor unit Fan		Rated air volume	m ³ /min	375+348×2	375×2+348	375×3	375+375×2	375×2+375	375×3	348+329×2+263	348×2+329+263	348×3+263	348×2+329×2	348×3+329	
		Number of Fan Motors	-	2+2+2	2+2+2	2+2+2	2+2+2	2+2+2	2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	
		Motor output	kW	0.58×2+(0.47×2)×2	(0.58×2)×2+0.47×2	(0.58×2)×3	0.58×2+(0.58×2)×2	(0.58×2)×2+0.58×2	(0.58×2)×3	0.47×2+(0.4×2)×2+0.38×2	(0.47×2)×2+0.4×2+0.38×2	(0.47×2)×3+0.38×2	(0.47×2)×2+(0.4×2)×2	(0.47×2)×3+0.4×2	
Main pipe size		Heat Recovery	Gas Piping (Low Pressure)	mm	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8		
			Gas Piping (High/Low Pressure)	mm	44.45	44.45	44.45	44.45	44.45	44.45	44.45	44.45	44.45	44.45	
			Liquid Piping	mm	22.2	22.2	22.2	22.2	22.2	22.2	22.2	22.2	25.4	25.4	25.4
		Tube connection method	-	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	
Operating temperature range		Cooling	°C DB	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C		
		Heating	°C WB	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	
Maximum External Static Pressure		Pa	80	80	80	80	80	80	80	80	80	80	80		
Maximum Total piping length		m	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000		
Maximum piping length		Between ODU and IDU	Actual	m	200	200	200	200	200	200	200	200	200		
			Equivalent	m	225	225	225	225	225	225	225	225	225	225	
		Between "Piping connection kit" and each ODU single module	m	25	25	25	25	25	25	25	25	25	25	25	
		Between "1st branch Multi Kit" and farthest IDU	m	100	100	100	100	100	100	100	100	100	100	100	
		Between "Multi Kit" and each connected IDU	m	40	40	40	40	40	40	40	40	40	40	40	
		Between "CH-Box" to each IDU	m	40	40	40	40	40	40	40	40	40	40	40	
Between each single module of 1 ODU		m	2	2	2	2	2	2	2	2	2	2	2		
Maximum height difference		Between ODU and IDUs	ODU above IDU (*)	m	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)		
			IDU above ODU (*)	m	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)		
		Between IDUs	m	40	40	40	40	40	40	40	40	40	40	40	
		Between CH-Box and indoor units	m	15	15	15	15	15	15	15	15	15	15	15	
		Between CH-Boxes	m	40	40	40	40	40	40	40	40	40	40	40	
Between indoor units after single CH-Box	m	4	4	4	4	4	4	4	4	4	4	4			
Refrigerant		Type	-	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A		
		Initial charge amount	kg	34.5	34.5	34.5	34.5	34.5	34.5	44.1	44.4	44.7	45.4	45.7	
		Maximum additional charge amount	kg	73.0	73.0	73.0	73.0	73.0	73.0	73.0	73.0	93.0	93.0	93.0	
		Refrigerant control mode	-	Microcomputer-controlled electronic expansion valve						Microcomputer-controlled electronic expansion valve					
Refrigerant oil		Type	-	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D		
		Charge amount	L	25.2	25.2	25.2	25.2	25.2	25.2	32.1	32.1	32.1	33.6	33.6	
Maximum Connected capacity ratio		%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%		
With Indoor Unit		Number of connectable units (recommended number of units)	-	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)		
		Connectable minimum capacity	-	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class		

Specifications

LLLL



Capacity range	Unit	96HP class	98HP class	100HP class	102HP class	104HP class	106HP class	108HP class	110HP class	112HP class	
Outdoor unit model		RAS-960RNCCLW	RAS-980RNCCLW	RAS-H00RNCCLW	RAS-H02RNCCLW	RAS-H04RNCCLW	RAS-H06RNCCLW	RAS-H08RNCCLW	RAS-H10RNCCLW	RAS-H12RNCCLW	
Combination of modules		RAS-240RNCCLW RAS-240RNCCLW RAS-240RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-240RNCCLW RAS-240RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-260RNCCLW RAS-240RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-260RNCCLW RAS-260RNCCLW RAS-240RNCCLW	RAS-260RNCCLW RAS-260RNCCLW RAS-260RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-260RNCCLW RAS-260RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-280RNCCLW RAS-260RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-280RNCCLW RAS-280RNCCLW RAS-260RNCCLW	RAS-280RNCCLW RAS-280RNCCLW RAS-280RNCCLW RAS-280RNCCLW	
Power supply	-	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	3N~ 380-415V 50Hz	
Cooling capacity	kW	268.0	274.0	280.0	286.0	292.0	296.5	301.0	305.5	310.0	
Heating capacity	kW	310.0	314.0	318.0	322.0	326.0	330.5	335.0	339.5	344.0	
Outer dimensions (W x D x H)	mm	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	6,560×775×1,805	
Weight	Net weight	kg	368+368+368+368	393+368+368+368	393+393+368+368	393+393+393+368	393+393+393+393	393+393+393+393	393+393+393+393	393+393+393+393	
	Gross weight	kg	392+392+392+392	417+392+392+392	417+417+392+392	417+417+417+392	417+417+417+417	417+417+417+417	417+417+417+417	417+417+417+417	
Noise	Cooling rating	SPL (Full-anechoic) dB(A)	67.0	67.3	67.5	67.8	68.0	68.0	68.0	68.0	
	Night shift mode (noise reduction setting)	SPL (Full-anechoic) dB(A)	63.0	64.0	64.8	65.4	66.0	66.0	66.0	66.0	
Electric characteristics	Power consumption	Cooling	kW	64.68	67.24	69.80	72.36	74.92	76.94	78.96	80.98
		Heating	kW	79.72	84.02	88.32	92.62	96.92	102.14	107.36	112.58
	Operating current	Cooling	A	120.0	124.7	129.4	134.1	138.8	142.5	146.2	149.9
		Heating	A	146.0	153.9	161.8	169.7	177.6	187.1	196.6	206.1
	Breaker (A)	A	63+63+63+63	80+63+63+63	80+80+63+63	80+80+80+63	80+80+80+80	80+80+80+80	80+80+80+80	80+80+80+80	80+80+80+80
MAX current	A	212.0	217.3	222.6	227.9	233.2	234.3	235.4	236.5	237.6	
Energy efficiency	Outdoor Unit only	Cooling EER	-	4.14	4.07	4.01	3.95	3.90	3.85	3.81	3.77
		Heating COP	-	3.89	3.74	3.60	3.48	3.36	3.24	3.12	3.02
Compressor	Compressor type	-	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	Hermetic (Scroll)	
	Motor output	kW	(8.7×2)×4	10.55×2+(8.7×2)×3	(10.55×2)×2+(8.7×2)×2	(10.55×2)×3+8.7×2	(10.55×2)×4	12.98×2+(10.55×2)×3	(12.98×2)×2+(10.55×2)×2	(12.98×2)×3+10.55×2	(12.98×2)×4
Outdoor unit Fan	Rated air volume	m ³ /min	348×4	375+348×3	375×2+348×2	375×3+348	375×4	375+375×3	375×2+375×2	375×3+375	
	Number of Fan Motors	-	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	2+2+2+2	
	Motor output	kW	(0.47×2)×4	0.58×2+(0.47×2)×3	(0.58×2)×2+(0.47×2)×2	(0.58×2)×3+0.47×2	(0.58×2)×4	0.58×2+(0.58×2)×3	(0.58×2)×2+(0.58×2)×2	(0.58×2)×3+0.58×2	(0.58×2)×4
Main pipe size	Heat Recovery	Gas Piping (Low Pressure)	mm	50.8	54.0	54.0	54.0	54.0	54.0	54.0	
		Gas Piping (High/Low Pressure)	mm	44.45	50.8	50.8	50.8	50.8	50.8	50.8	
		Liquid Piping	mm	25.4	25.4	25.4	25.4	25.4	25.4	25.4	
	Tubing connection method	-	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	Welding connection	
Operating temperature range	Cooling	°C DB	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	-5°C (-10°C)~48<52>°C	
	Heating	°C WB	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	<-25°C> -15°C~16°C	
Maximum External Static Pressure	Pa	80	80	80	80	80	80	80	80	80	
Maximum Total piping length	m	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	1,000	
Maximum piping length	Between ODU and IDU	Actual	m	200	200	200	200	200	200	200	
		Equivalent	m	225	225	225	225	225	225	225	
	Between "Piping connection kit" and each ODU single module	m	25	25	25	25	25	25	25	25	
	Between "1st branch Multi Kit" and farthest IDU	m	100	100	100	100	100	100	100	100	
	Between "Multi Kit" and each connected IDU	m	40	40	40	40	40	40	40	40	
	Between "CH-Box" to each IDU	m	40	40	40	40	40	40	40	40	
Maximum height difference	Between each single module of 1 ODU	m	2	2	2	2	2	2	2	2	
	Between ODU and IDUs	ODU above IDU (*)	m	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	110 (50)	
		IDU above ODU (*)	m	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	110 (40)	
	Between IDUs	m	40	40	40	40	40	40	40	40	
	Between CH-Box and indoor units	m	15	15	15	15	15	15	15	15	
	Between CH-Boxes	m	40	40	40	40	40	40	40	40	
Between indoor units after single CH-Box	m	4	4	4	4	4	4	4	4		
Refrigerant	Type	-	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
	Initial charge amount	kg	46.0	46.0	46.0	46.0	46.0	46.0	46.0	46.0	
	Maximum additional charge amount	kg	93.0	93.0	93.0	93.0	93.0	93.0	93.0	93.0	
	Refrigerant control mode	-	Microcomputer-controlled electronic expansion valve				Microcomputer-controlled electronic expansion valve				
Refrigerant oil	Type	-	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	FVC68D	
	Charge amount	L	33.6	33.6	33.6	33.6	33.6	33.6	33.6	33.6	
With Indoor Unit	Maximum Connected capacity ratio	%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	50~150%	
	Number of connectable units (recommended number of units)	-	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	64 (38)	
	Connectable minimum capacity	-	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	0.6HP class	



Option

1) Piping Connection Kit

*For Heat Recovery (3 Pipes)

Model name	Applicable Outdoor Unit		Remarks
	Combined X modules	air365 Max	
MC-NP21SX1	2	30 to 48 HP	for Low PRESS. Gas : 1 for High/Low PRESS. Gas : 1 for Liquid : 1
MC-NP22TX		50 to 56 HP	
MC-NP31TX	3	58 to 84 HP	for Low PRESS. Gas : 2 for High/Low PRESS. Gas : 2 for Liquid : 2
MC-NP40TX	4	86 to 112 HP	for Low PRESS. Gas : 3 for High/Low PRESS. Gas : 3 for Liquid : 3

2) Multi-Kit

*For Heat Recovery (3 Pipes)

Line branch

(First branch)

Model Name	Outdoor Unit HP
MW-NP282X3	8 ~ 10
MW-NP452X3	12 to 16
MW-NP562X3	18 ~ 20
MW-NP692X3	22 ~ 24
MW-NP902X3	26 to 54
MW-NP2682X3	56 to 112

(After First Branch)

Model Name	Total Indoor Unit HP
MW-NP142X3	< 5.99
MW-NP282X3	6 to 11.99
MW-NP452X3	12 to 17.99
MW-NP562X3	18 to 21.99
MW-NP692X3	22 to 25.99
MW-NP902X3	26 to 55.99
MW-NP2682X3	≥ 56

Header Branch

Model Name	Total Indoor Unit HP	No. of Header branches
MH-NP288A	10HP to less	8

Accessories

1) Air Outlet Duct Kit



Side

Air Outlet Duct Kit (Available upon order)	
S cabinet	FDK-TP20A
M cabinet	FDK-TP20B
L cabinet	FDK-TP20C

2) Protection Net



Back

	Protection Net	
	Back	Right & LeftSide
S cabinet	PN-TP30BA	PN-TP30LR x 2
M cabinet	PN-TP30BB	PN-TP30LR x 2
L cabinet	PN-TP30BC	PN-TP30LR x 2

3) Air Inlet Grille



Back

Side

	Air Inlet Grille	
	Back	Right & LeftSide
S cabinet	PSN-TP30BA	PSN-TP30LR x 2
M cabinet	PSN-TP30BB	PSN-TP30LR x 2
L cabinet	PSN-TP30BC	PSN-TP30LR x 2



Comfort first

For each space its own indoor unit. Our wide range of units can meet any type of requirement and space layout, and seamlessly integrate with interiors.

With seamless and quiet operation, your customers can relax and enjoy the air while using only the amount energy needed. Advanced functions such as GentleCool and AutoBoost allow you to customize the air in each space to suit your customers' preferences, while smart design minimizes the need for maintenance.

INDOOR UNITS

66 Line-up summary

67 Our key indoor features

75 Indoor Air Quality

79 Solutions

79 Ducted units

82 High ESP [RPIH-HNAUN1Q, RPI-FSNQ] (AC) **NEW**

High ESP [RPIH-HNDUSQ] (DC) **NEW**

83 Medium ESP [RPIM-HNAUN1Q, RPI-FSN3Q] (AC) **NEW**

Low ESP [RPIL-HNAUN1Q] (AC) **NEW**

84 Compact [RPIZ-HNATN1Q] (AC) **NEW**

Compact [RPIZ-HNDTS1Q] (DC) **NEW**

85 Ceiling cassettes

87 Silent-Ionic™ (4-way cassette design panel)

89 4-way cassette [RCI-FSRP, RCI-FSKDN1Q] (DC) **NEW**

90 4-way compact cassette [RCIM-FSRE] (DC)

91 2-way cassette [RCD-FSR] (DC)

92 1-way cassette [RCS-FSR] (DC)

93 Other indoor units

95 Wall mounted [RPK-FSRM] (DC)

96 Wall mounted [RPK-HNBUSQ] (DC)

97 Floor/Ceiling convertible [RPFC-FSNQ] (AC)

98 Ceiling suspended [RPC-FSR] (DC)

99 Floor concealed [RPFI-FSNQ] (AC)

100 Specifications & accessories



Line-up summary

Over 18 types available!

DUCTED | The ultimate invisibility.

NEW

HIGH ESP (AC)
RPIH-HNAUN1Q, RPI-FSNQ



NEW

HIGH ESP (DC)
RPIH-HNDUSQ



NEW

MEDIUM ESP (AC)
RPIM-HNAUN1Q, RPI-FSN3Q




NEW

LOW ESP (AC)
RPIL-HNAUN1Q




NEW

COMPACT (AC)
RPIZ-HNATN1Q



NEW

COMPACT (DC)
RPIZ-HNDTS1Q



CASSETTE | Consistent air reaching every corner of a room.

4-WAY CASSETTE (DC)
RCI-FSRP



NEW


4-WAY CASSETTE (DC)
RCI-FSKDN1Q



TWIN-SENSE SYSTEM
RCI-FSRP+ P-AP160NAE2
RCI-FSKDN1Q+ P-AP160NAE2+OPT-EZJ01



**Silent-Iconic™
Design Panel**
P-GP160NAP, P-GP160NAPU, P-GP160KAP



4-WAY COMPACT CASSETTE (DC)
RCIM-FSRE



2-WAY CASSETTE (DC)
RCD-FSR



1-WAY CASSETTE (DC)
RCS-FSR



OTHERS | Minimal installation or retrofit works.

WALL MOUNTED (DC)
RPK-FSRM



WALL MOUNTED (DC)
RPK-HNBUSQ



FLOOR/CEILING CONVERTIBLE (AC)
RPFC-FSNQ



CEILING SUSPENDED (DC)
RPC-FSR



FLOOR CONCEALED (AC)
RPFI-FSNQ



Our key indoor features

Hitachi air, making a difference.

EXCLUSIVE

GENTLECOOL (FOR COOLING OPERATION)



Set not only your desired room temperature, but the cooled air temperature!

Without GentleCool, the unit might blow cooler air than expected when adjusting the indoor air temperature, causing a cool draft sensation at the beginning of operation.

With GentleCool, users have control over how discharged air reaches a preferred temperature setting, ensuring a smoother cooling down effect.

GentleCool might affect the speed of the room's cooling down to the set temperature.

Potential discomfort.

>8.0°C
→ COLD DRAFT

GentleCool
OFF

GentleCool : no cold draft.

>12.0°C

GentleCool
OFF

>14.0°C


GentleCool
LOW

>16.0°C

GentleCool
MED

EXCLUSIVE

CROWD-SENSE: PREDICTIVE ADJUSTMENT TO OCCUPANCY VARIATIONS



Ideal for meeting rooms, restaurants, museums and other venues experiencing rapid changes of occupancy.

With conventional air conditioning, the arrival of more occupants creates new sources of heat and may naturally disrupt indoor thermal comfort. With Crowd-Sense predictive control, enjoy a stable indoor temperature whenever the size of the crowd changes.

- Hitachi Twin-Sense cassette detects the crowd's arrival or departure.
- Using AI, the cassette can anticipate the addition or reduction of human heat sources and immediately adjusts the air conditioning accordingly.

Crowd-Sense action during cooling.

TRADITIONAL CONTROL

a) The room temperature becomes too high.

b) The air conditioning power increases after detection of too hot room temperature.

CROWD-SENSE PREDICTIVE CONTROL

a) Predicts and anticipates room temperature rise. Proactively increases air conditioning power to compensate for additional human heat sources.

b) Room temperature remains stable.

Crowd-Sense action during heating.

TRADITIONAL CONTROL

a) The room temperature becomes too high.

b) The air conditioning thermal operation turns off after detection of too hot room temperature.

CROWD-SENSE PREDICTIVE CONTROL

a) Predicts and anticipates room temperature rise. Proactively reduces air conditioning power to accommodate additional human heat sources.

b) Room temperature remains stable.

----- Target set temperature
 — Power
 — Room temperature
 → Time

Crowd-Sense may not be effective or might be less effective in the following cases:

- Multiple indoor units are in operation in the same zone.
- The difference between the radiant temperature of the room (floor and walls) and the radiant temperature of the human body is minimal.
- The room temperature is high before operation.
- During the heating process, when the number of occupants decreases.

68

Our key indoor features

Our key indoor features

Hitachi air, making a difference.

FEETWARM (FOR HEATING OPERATION)




Head to toe comfort during winter.

Intelligent heated air distribution, tailored for the human body.

FeetWarm is complex yet effortless comfort function integrating various parameters together. Available in our Twin-Sense cassette, it prevents the natural effect of cold air sinking and hot air rising, to create enveloping warmth for all occupants.


FeetWarm's boasts 4 intelligent features:

- Thanks to the Twin-Sense radiant sensor, it can detect heat stratification effects inside the room, which usually cause the floor and lower levels to be cooler.
- A 2-step action to first create consistent warmth, then to maintain it.
- Advanced heat air flow optimization, by sophisticated control of the 4-way cassette's individual louvers.
- The lower levels of the room (floor level, feet level, leg level) reach desired temperatures, for total comfort.



How does it work?

Step 1.




- 1 The radiant sensor detects a temperature drop in the floor and around your feet.
- 2 The cassette partially closes two louvers automatically.
- 3 The air flow strengthens through the two remaining open louvers, and targets the floor to warm it up quickly¹. Louver openings alternate every three minutes from wide open to partially closed to cover a wider floor area.
- 4 As louver openings close, suction increases in the central inlet grill for a faster warming effect.

¹ Caution: when the indoor unit changes to heating, the sudden change in air flow might cause occupants to feel a cold draft sensation.

Effect of FeetWarm- Step 1.


Temperature distribution around the area of the feet (30min after air conditioning heating operation starts).



[Image based on calculation results]

Step 2.


- 1 When the radiant temperature sensor detects that the lower level is no longer cold, FeetWarm shifts to its second step for a more even temperature everywhere in the room.
- 2 One louver remains closed.
- 3 Three remaining open louvers follow Auto-Swing air flow direction, continuously moving up/down. This leads to faster circulation of the warm air in all areas of the room.
- 4 Suction of colder air remains facilitated thanks to the one partially closed louver.



Effect of FeetWarm- Step 2.

FeetWarm: Step 1 (end)

FeetWarm Step 2 (after 20min)




[Measurement condition Based on Hitachi research]. See simulation result under the following conditions above. Unit capacity: 8.0kW, room size: height 3.2m, length 6.3m, width 6.3m, indoor initial temperature: 7 °C, outdoor temperature: 7 °C, indoor airflow temperature: 30 °C for 0-5 minutes, Gradually rise from 30 °C to 40 °C after 5 minutes, Multi-function remote control setting: Airflow heat control "effective / long". (Note) The effect varies depending on the size of the room and the load.



Our key indoor features

Hitachi air, making a difference.

FLOORSENSE COOL (FOR COOLING OPERATION)




Prevents floor overcooling.

When the room has undergone prolonged cooling, the floor may overcool, due to cold air sinking below layers of warmer air. The radiant sensor can detect when the floor becomes too cold. The air conditioning automatically blows softer to prevent overcooling.*¹

*¹ When a group of people return to the room or the room temperature rises due to sunlight, the cooling operation returns to normal.



CHOICE OF DIRECT OR INDIRECT AIR FLOW



Want to feel the air? Or do you prefer imperceptible air? Choose the preferred air sensation and let the air conditioner adjust the louver direction to your liking.

Our 4-zone motion sensor divides the room into 4 areas and can detect presence in each of them.

- Choose Direct air flow: the Twin-Sense cassette will target the corners with human activity.
- Choose Indirect air flow: Twin-Sense cassette will avoid the corners where occupants are detected.




Notes:
 When room vacancy is detected, the air is directed in the way the controller (PC-ARFG) is set up. (Note) 4-zone motion sensor may not be effective in the following cases:
 - If the room is occupied but the movement is minimal, the system might consider the room as vacant.
 - If an object with a temperature different to the surrounding is in motion, it might be considered as human presence.


Our key indoor features

Hitachi air, making a difference.

HOTEL SETBACK




AUTO-SAVE (WITH MOTION SENSOR)



Save more energy while improving comfort!

When adding a motion sensor to the indoor unit, auto-save function will adjust the air conditioning output to the human activity level.

HOW DOES IT WORK?



Indoor Air Quality

Live and work in harmony



Hitachi IAQ accessory Line-up

	01 ViroSense S filter	02 ViroSense Z2 filter	03 AQtiv-Ion Kit
Type of purchase	Now fitted as standard	Optional upgrade Model: F-160L-ZV	Optional upgrade Model: JK-LAZQ
For those who...	<ul style="list-style-type: none"> want to save additional cost want to create the cleaner indoor environment 	<ul style="list-style-type: none"> want to reduce the risk of secondary infection/pollution reduce spread of SARS-CoV-2 don't want to compromise airflow or additional noise 	<ul style="list-style-type: none"> Looking for low-maintenance non-intrusive ways of purifying air without installing separate purification units Looking for both pollutant and odor reduction solutions
Key Features	<ul style="list-style-type: none"> Lasts up to 5 years (12500h) Anti-virus (>99% inhibition) Anti-bacteria (>99% inhibition) Anti-mold (100% growth stop) 	<ul style="list-style-type: none"> Lasts up to 4 years (10000h) Quick & easy to install/change from existing filters Anti-virus (>99.7% inhibition): better than Ion filter Anti SARS-CoV-2 (>99.9% inhibition) Anti-bacteria (>99% inhibition) 	<ul style="list-style-type: none"> Lasts up to 6 years (15000h) Generates negative ions and emits through AC airflow, which binds to pollutants and odors, sending them harmlessly to the floor Plug & play; converts your ducted IDU into an air-purifying IDU Up to 96.85% capturing of Influenza virus Up to 74.90% removal of Formaldehyde

STANDARD-EQUIPPED FILTER

VIROSENSE S FILTER

We have renewed our standard air filter for some of our Hitachi VRF indoor units with leading-edge ion-technology, and, now it has THREE benefits for you & more assures indoor environment. Our STANDARD Air Filter with Ion Purification feature, ViroSense S filter, will catch & reduce them, then help create the cleaner indoor environment.



over 99% Inhibition



over 99% Inhibition



100% growth stop

Testing information

[Anti-virus test]

Test Laboratory: Guangdong Detection Center of Microbiology
Test Report # 2021FM05008R01
Test Procedure: Based on ISO 18184:2019
Textiles - Determination of antiviral activity of textile products

[Anti-bacterial test]

Test Laboratory: Guangdong Detection Center of Microbiology
Test Report # 2021FM05005R01
Test Procedure: Based on JIS Z 2801:2010
Antibacterial products-Test for antibacterial activity and efficacy

[Anti-mold test]

Test Laboratory: Guangdong Detection Center of Microbiology
Test Report # 2021FM05006R01
Test Procedure: Based on JIS Z 2911:2018 (A)
Methods of test for fungus resistance

UNIT STANDARDIZED WITH VIROSENSE S FILTER

4-way Cassette (RCI-FSRP)						4-way Cassette (RCI-FSKDN1Q)	
TWIN-SENSE 4-way Panel White	Standard 4-way Panel White	Standard 4-way Panel Black	Silent-Ionic White	Silent-Ionic Auto-elevating grille White	Silent-Ionic Black	Standardized Panel	TWIN-SENSE 4-way Panel White
P-AP160NAE2	P-AP160NA3	P-AP160KA3	P-GP160NAP	P-GP160NAPU	P-GP160KAP	(Standard Equipped)	P-AP160NAE2 + OPT-EZJ01
2-way Cassette (RCD-FSR)		1-way Cassette (RCS-FSR)		Ceiling Suspended (RPC-FSR)			
P-AP90DNA/P-AP160DNA		P-AP36CNA/P-AP56CNA/P-AP80CNA		RPC-1.5FSR~6.0FSR			

Note: for the additional filter purchase, it is treated as "service part". Please consult your distributors.



ViroSense Z2 filter

OPTIONAL ACCESSORY FILTER

VIROSENSE Z2 FILTER



Model: F-160L-ZV

ViroSense Z2 filter can help reduce the risk of secondary infection in a room. We have confirmed the proven effect that can inhabit certain viruses attached to the air conditioner's filter already before. And in 2022, we have confirmed that it can inhibit the SARS-CoV-2 as well under the laboratory test.

BENEFITS



SARS-CoV-2 Inhibition by over 99.9%

The efficiency of the ViroSense Z2 filter against SARS-CoV-2 been confirmed with inhibition rate up to more than 99.9%.



Virus Inhibition by over 99.7%

The efficiency of the ViroSense Z2 filter against certain viruses has been confirmed with inhibition rate up to more than 99.7%.



Bacteria removal by over 99%

Efficiency of ViroSense Z2 filter against Certain types of Bacterial has been confirmed too with inhibition rate up to more than 99%.



Life span of up to 4 years


With regular maintenance and cleaning of the filter, the filter can have a life span of up to 4 years.



Quick anti-virus transformation

Your existing 4-way cassette panel can be quickly adapted for the anti-virus version, once you change your existing filter to the ViroSense Z2 filter. The same, usual attachment!

EFFICIENCY PROVEN



[Testing data]

Testing Laboratory: Japan Textile Products Quality and Technology Center
Test Report No. : 21KB080432-1
Test Procedure: ISO 18184 : 2019 "Textiles -- Determination of antiviral activity of textile products." application
Tested Virus: Severe acute respiratory syndrome coronavirus 2 (SARS-CoV-2)

Anti Virus

[Testing data]

Testing Laboratory: Japan Textile Products Quality and Technology Center
Test Report No. : 20KB-070036
Tested Target: Feline infectious peritonitis virus ATCC VR-2127
Test Procedure: Based on ISO 18184; Textiles -- Determination of antiviral activity of textile products
Effect: Antiviral activity value (Mv) is at least 2.6 (>99.7% inhibition ratio)

Anti Bacteria

[Testing data]

Testing Laboratory: Kaken Test Center
Test Report: OS-20-09344-1
Test target: (1) Staphylococcus aureus ATCC 6538 (2) Klebsiella pneumoniae ATCC 4352
Test procedure: ISO 20743:2013 (Textiles - Determination of antibacterial activity of textile products)
Effect: Antibacterial activity ratio is at least (1) 2.6 (>99% death ratio) (2) 3.1 (>99.9% death ratio)

COMPATIBLE INDOOR UNITS WITH VIROSENSE Z2 FILTER

4-way Cassette (RCI-FSRP)						4-way Cassette (RCI-FSKDN1Q)	
TWIN-SENSE 4-way Panel White	Standard 4-way Panel White	Standard 4-way Panel Black	Silent-Ionic White	Silent-Ionic Auto-elevating grille White	Silent-Ionic Black	Standardized Panel	TWIN-SENSE 4-way Panel White
P-AP160NAE2	P-AP160NA3	P-AP160KA3	P-GP160NAP	P-GP160NAPU	P-GP160KAP	(Standard Equipped)	P-AP160NAE2 + OPT-EZJ01

Indoor Air Quality

Live and work in harmony

OPTIONAL ACCESSORY FILTER
AQTIV-ION KIT



Model: JK-LZAQ

Combine your air conditioner with AQtiv-Ion Kit, and provide a better and healthier indoor environment.

Efficient combination with air conditioning

As AQtiv-Ion Kit is integrated into the air conditioning system, AQtiv-Ion Kit does not require its own fan, but uses the airflow from the air conditioner instead. That means, your new air purification device has minimal impact on the noise level and energy consumption, as it fits inside the pre-installed air conditioner.



AQtiv-Ion Kit

COMMON FACTORS AFFECTING INDOOR AIR QUALITY



Various pathogenic factors including bacteria and certain viruses caused by insufficient ventilation.



Breeding of bacteria, mold and damage to household items, allergies caused by high humidity in wet season.



Formaldehyde, ammonia, benzene and a variety of volatile organic compounds released by decoration materials.



Second-hand smoking and kitchen oil fume.



Dust and mites from fabrics, such as beddings and pet dander might cause allergies.

HOW AQTIV-ION KIT WORKS



Inactivation of SARS-CoV-2 by more than 99.9%



Up to 96.85% capture of certain viruses and bacteria



Down to PM0.3 micro particle removal




Removal of pollutants




Active oxygen generation

AQTIV-ION KIT TECHNOLOGY

The AQtiv-Ion Kit generates negative ions, which when released into the air, combine with the oxygen (O₂) naturally present in the air. These newly created oxygen molecules trap the impure particles, certain viruses and bacteria and deactivate them.



Fight Against The Multiple Invisibles



AQTIV-ION KIT DEACTIVATION PERFORMANCE

SARS-CoV-2 -99.9% (Inhibition rate)	Escherichia coli -96.64% (Inhibition rate)	Influenza virus -96.85% (Removal rate)	Staphylococcus aureus -93.88% (Inhibition rate)	PM2.5 -94.46% (Removal rate)	Formaldehyde -74.90% (Removal rate)	Ammonia -73.20% (Removal rate)
--	---	---	--	---	--	---

AQTIV-ION KIT APPLICATIONS



Classroom

Condominium

Meeting Room


Hotel

HOW TO INSTALL?


Plug and play!

Up to your installation condition, you can choose from two options for AQtiv-Ion Kit to be fixed to.

(1) Inside the indoor unit (air outlet)



(2) Inside the air duct (air outlet)



TECHNICAL SPECIFICATIONS

Model	JK-LZAQ
Wiring Length	1 meter
Rated power supply	220~240V, 50/60Hz
Electrical Power consumption	(Max) 3W
Operating temperature	-10~50 °C
Operating humidity	20~80%RH
Value of negative ion amount	15,000,000 pcs/cc
Certification	CE/CB

TESTING

[Escherichia coli] [Staphylococcus aureus]	
Laboratory	Guangdong Detection Center of Microbiology
Testing standard	GB 21551.3-2010 Appendix A
Test Report	2019FM10157R01
[PM2.5]	
Laboratory	Guangdong Detection Center of Microbiology
Testing standard	APIAC/LM 01-2015
Test Report	2019FM10157R02
[Influenza virus]	
Laboratory	Guangdong Detection Center of Microbiology
Testing standard	Regulation of disinfection technique in healthcare settings <2002, 2-1-3>
Test Report	2019FM10157R03
[Formaldehyde] [Ammonia]	
Laboratory	Guangdong Detection Center of Microbiology
Testing standard	QB/T2761-2006 etc
Test Report	2019FM10157R04

Please consult your Hitachi Cooling & Heating representative for more details concerning the test reports.

COMPATIBLE INDOOR UNITS WITH AQTIV-ION KIT

HIGH ESP (AC) RPIH-**HNAUN1Q	HIGH ESP (DC) RPIH-**HNDUSQ	MEIDIUM ESP (AC) RPIM-**HNAUN1Q	LOW ESP (AC) RPI-**HNAUN1Q	COMPACT (AC) RPIZ-**HNATN1Q	COMPACT (DC) RPIZ-**HNDTS1Q

(*) For RPI-8.0/10.0FSNQH, please fix the AQtiv-Ion Kit to the indoor unit air-outlet.

Solutions

Ducted units

AIR CONDITIONING TURNED INVISIBLE!

Our 6 types of ducted units offer variety of ESP level, to facilitate integration into your project.

NEW



HIGH ESP (AC) [RPIH-HNAUN1Q, RPI-FSNQ]

- High ESP (90/120/180Pa).
- Slim & space saving design thanks to a height of 300mm only (RPIH-HNAUN1Q).
- Compatible with AQtiv-Ion Kit (Optional accessory)

NEW



HIGH ESP (DC) [RPIH-HNDUSQ]

- Single-Phase DC motor unit
- Adjustable external pressure up to 150pa
- Compatible with AQtiv-Ion Kit (Optional accessory)

NEW



MEDIUM ESP (AC) [RPIM-HNAUN1Q, RPI-FSN3Q]

- Medium ESP: 50/80Pa (0.8-2.5HP) or 100Pa (8.0-10.0HP).
- Slim & space saving design thanks to a height of 270mm only (0.8-2.5HP) or 470mm only (8.0-10.0HP).
- Compatible with AQtiv-Ion Kit (Optional accessory)

NEW



LOW ESP (AC) [RPIL-HNAUN1Q]

- Low ESP (30Pa for 0.8-2.5HP, 60Pa for 3.0-6.0HP).
- Space saving design thanks to a height of only 270mm (0.8-2.5HP) or 350mm (3.0-6.0HP).
- Compatible with AQtiv-Ion Kit (Optional accessory)


NEW



COMPACT (AC) [RPIZ-HNATN1Q]

- 192mm height! Ideal for installations above closets or windows.
- Drain-pump with 900mm lift as standard optional part.
- Quiet noise level down to 20dB(A).
- Compatible with AQtiv-Ion Kit (Optional accessory)

NEW



COMPACT (DC) [RPIZ-HNDTS1Q]

- 192mm height! Ideal for installations above closets or windows.
- Drain-pump with 900mm lift as standard optional part.
- Quiet noise level down to 20dB(A).
- Fan speed: 6 taps available.
- Compatible with AQtiv-Ion Kit (Optional accessory)

FROM 2.2KW TO 28KW

Ducted indoor units	Cooling (kW)	2.2	2.8	3.6	4.0	4.3	5.0	5.6	6.3	7.1	8.0	8.4	9.0	11.2	14.0	14.2	16.0	18.0	22.4	28.0	
NEW HIGH ESP (AC) [RPIH-HNAUN1Q, RPI-FSNQ]												●	●	●		●	●		●	●	
NEW HIGH ESP (DC) [RPIH-HNDUSQ]																				●	●
NEW MEDIUM ESP (AC) [RPIM-HNAUN1Q, RPI-FSN3Q]		●	●	●		●	●	●	●	●									●	●	
NEW LOW ESP (AC) [RPIL-HNAUN1Q]		●	●	●		●	●	●	●	●		●	●	●		●	●				
NEW COMPACT (AC) [RPIZ-HNATN1Q]		●	●	●	●		●	●	●	●											
NEW COMPACT (DC) [RPIZ-HNDTS1Q]		●	●	●	●		●	●	●	●											

FEATURES COMPARISON

Model	NEW HIGH ESP (AC) RPIH-HNAUN1Q	NEW HIGH ESP (DC) RPIH-HNDUSQ	HIGH/MEDIUM ESP (8/10HP) (AC) RPI-FSNQ RPI-FSN3Q	NEW MEDIUM/LOW ESP (AC) RPIM-HNAUN1Q RPIL-HNAUN1Q	NEW COMPACT (AC) RPIZ-HNATN1Q	NEW COMPACT (DC) RPIZ-HNDTS1Q
Temperature Setting Rate	1.0°C	1.0°C	1.0°C	1.0°C	1.0°C	1.0°C
Fan Speed	3 taps	6 taps	1 tap	3 taps	3 taps	6 taps
Louver Direction	-	-	-	-	-	-
Individual Louver Setting	-	-	-	-	-	-
Auto Louver Setting	-	-	-	-	-	-
Dry mode Availability	●	●	●	●	●	●
Setback (Away Function)	-	-	-	-	-	-
Cold Draft Prevention (*1)(*4)	●	●	●	●	●	●
Comfort setting	Control Cool Air (GentleCool) (*2)	-	-	-	-	-
Direct/Indirect louver direction in COOL	-	-	-	-	-	-
Direct/Indirect louver direction in HEAT	-	-	-	-	-	-
FeetWarm air flow control	-	-	-	-	-	-
FloorSense Cool air flow control	-	-	-	-	-	-
Power Saving with Motion Sensor (*2)	-	-	-	-	-	-
Outdoor Unit capacity control (*2)	Peak cut control	-	-	-	-	-
	Moderate control	-	-	-	-	-
Indoor Unit Rotation Control (*2)	Indoor Unit Address	-	-	-	-	-
	Indoor Air Temperature difference	-	-	-	-	-
Automatic Fan Operation	●	●	●	●	●	●
AutoBoost (quick function) (*2)	-	-	-	-	-	-
Daylight Saving Time	●	●	●	●	●	●
Power Consumption visualization (*2)	-	-	-	-	-	-
Weekly Schedule Setting	●	●	●	●	●	●
Power-Saving Setting (*2)	-	-	-	-	-	-
Filter cleaning reminder	●	●	●	●	●	●
Check Menu	Sensor Condition Check	●	●	●	●	●
	Model Display (*2)	-	-	-	-	-
	Indoor/Outdoor PCB Check	●	●	●	●	●
	Alarm History Display	●	●	●	●	●
Motion Sensor	-	-	-	-	-	-
Receiver Kit for wireless remote controller	PC-RLH11 PC-ALHZ1	PC-RLH11 PC-ALHZ1	PC-RLH11 PC-ALHZ1	PC-RLH11 PC-ALHZ1	PC-RLH11 PC-ALHZ1	PC-RLH11 PC-ALHZ1
Drain-up mechanism availability	DUPI-361Q	DUPI-810AQ	DUPI-15H2Q	DUPI-131Q DUPI-361Q	● (*3)	● (*3)
Air filter	KW-PP9/10Q	KW-PP14Q F-10LP1E F-10HP1E	-	KW-PP7/ 8/9/10Q	KW-PP5Q KW-PP6Q	KW-PP5Q KW-PP6Q
AQtiv-Ion Kit	●	●	-	●	●	●

(*1) This function is utilized to prevent cold discharged air at start-up of heating operation, after defrosting operation, etc.
 (*2) Advanced wired remote controller PC-ARF1 needs to be connected.
 (*3) Included as standard equipment.
 (*4) Please consult your distributor.

AQtiv-Ion Kit



Leads to the better Indoor Air Quality

- Features**
- Up to 96.85% capture of viruses and bacteria
 - Down to PM0.3 micro particle removal
 - Pollutant removal
 - Active oxygen generation
 - Inactivation of SARS-CoV-2 by more than 99.9%

Success that sparks **NEW**

Information
 Labs Tower Cyprus
 FFOTI PITTA 4, CYPRUS, 1065
<https://labstower.cy/>

General Information

Year of Installation : 2022
 Project type : Retrofit
 Vertical application: Commercial multi-tenant building
 Installed unit :
 Total 384H With all-Ducted Indoor Units



Solutions


Ducted units

NEW
HIGH ESP HIGH EXTERNAL STATIC PRESSURE
 (AC) [RPIH-HNAUN1Q, RPI-FSNQ]




- 1) High ESP. (90/120/180Pa)
- 2) Space saving design thanks to a height of only 300mm. (RPIH-HNAUN1Q)
- 3) Flexible installation. Options allow for multiple configurations.
- 4) Optional drain pump. Drain-up mechanism can be supplied as optional part.
- 5) Compatible with AQtiv-Ion Kit (Optional accessory)


③ L-shaped space



U-shaped space



④




NEW
HIGH ESP HIGH EXTERNAL STATIC PRESSURE
 (DC) [RPIH-HNDUSQ]




- 1) High external pressure up to 150Pa
- 2) Flexible installation allowing for multiple configurations
- 3) Optional drain-pump: Drain-up mechanism can be supplied as optional accessory
- 4) Compatible with AQtiv-Ion Kit (Optional accessory)


② L-shaped space



U-shaped space



③



Solutions

Ducted units




NEW

MEDIUM ESP MEDIUM EXTERNAL STATIC PRESSURE

(AC) [RPIM-HNAUN1Q, RPI-FSN3Q]

- 1) Medium ESP. (50/80Pa for 0.8-2.5HP class, 100Pa for 8.0-10.0HP class)
- 2) Space saving design thanks to a height of only 270mm. (0.8-2.5HP class) or 470mm (8.0-10.0HP class)
- 3) Flexible installation. Options allow for multiple configurations.
- 4) Optional drain pump. Drain-up mechanism can be supplied as optional part.
- 5) Compatible with AQtiv-Ion Kit (Optional accessory)




NEW

LOW ESP (LOW EXTERNAL STATIC PRESSURE)

(AC) [RPIL-HNAUN1Q]

- 1) Low ESP. (30Pa for 0.8-2.5HP class, 60Pa for 3.0-6.0HP class)
- 2) Space saving design thanks to a height of only 270mm (0.8-2.5HP class) or 300mm (3.0-6.0HP class).
- 3) Optional drain pump. Drain-up mechanism can be supplied as optional part.
- 4) Compatible with AQtiv-Ion Kit (Optional accessory)




NEW

COMPACT

(AC) [RPIZ-HNATN1Q]

- 1) Ideal for installation over closets or windows thanks to a more compact design, 192mm high.
- 2) Drain-pump with 900mm lift as standard optional part.
- 3) Quiet operation level. (as low as 20dB(A))
- 4) Fan air flow rate up to 6 taps. (DC motor model only)
- 5) Compatible with AQtiv-Ion Kit (Optional accessory)





NEW

COMPACT

(DC) [RPIZ-HNDTS1Q]

- 1) Ideal for installation over closets or windows thanks to a more compact design, 192mm high.
- 2) Drain-pump with 900mm lift as standard optional part.
- 3) Quiet operation level. (as low as 22.5dB(A))
- 4) Fan air flow rate up to 6 taps. (DC motor model only)
- 5) Compatible with AQtiv-Ion Kit (Optional accessory)



Solutions

Ceiling cassettes

PREMIUM DESIGN & INNOVATIVE FEATURES

Meet with our newly upgraded offer, for upgraded comfort!



4-WAY CASSETTE (DC) [RCI-FSRP]


- (with P-AP160NAE2)
 - Greater performance & Greater comfort can be achieved
- (with P-GP160NAP)
 - Award-winning Silent-Iconic™ to fit your indoor aesthetics.
 - We have also Black type Silent-Iconic™, and, Gray/Beige normal panel.
- (with P-GP160NAPU)
 - Maintenance will be enormously improved by the auto-elevation grille.
 - Compatible with ViroSense Z2 filter!
 - ViroSense S filter as standard!



Color variation (RCI-FSRP)



Silent-Iconic™ with elevation grille



NEW 4-WAY CASSETTE (DC) [RCI-FSKDN1Q]

- With area of air distribution with 7 directions of louvers (distribution with distance available with optional parts (duct flange))
- Individual four-way louvers for greater comfort for individual users
- Ideal for a higher ceiling location for installation (up to 5.5m in cooling mode)
- Setback temperature control available, leading to better operation.
- GentleCool control to ensure you are not bothered by cold draft
- Compatible with ViroSense Z2 filter!
- ViroSense S filter as standard!



4-WAY COMPACT CASSETTE (DC) [RCIM-FSRE]

- Made to give you greater design flexibility as the dimensions fit 600mm×600mm architectural module ceiling specifications
- Quiet operation level (as low as 24.5dB(A))
- Wide range of air flow rate ideal for high ceiling installation with 4.6m air blow down in cooling mode
- Setback temperature control available, leading to better operation.
- Motion sensor available for better energy saving operation
- GentleCool control to ensure you are not bothered by cold draft



2-WAY CASSETTE (DC) [RCD-FSR]

- Motion sensor available for better energy saving operation
- Ideal for a higher ceiling location for installation (up to 4.6m in cooling mode)
- Individually operated louvers give room occupants more comfort
- Quiet operation level (as low as 27dB(A))
- Setback temperature control available, leading to better operation.
- GentleCool control to ensure you are not bothered by cold draft
- ViroSense S filter as standard!



1-WAY CASSETTE (DC) [RCS-FSR]

- Motion sensor available for better energy saving operation
- Optimum air flow conditions are created by either downward air discharge or frontal air discharge (via optional grille) or a combination of both
- Quiet operation level (as low as 27dB(A))
- Setback temperature control available, leading to better operation.
- GentleCool control to ensure you are not bothered by cold draft
- ViroSense S filter as standard!

FROM 1.6KW TO 16KW


Ceiling cassettes	Cooling (kW)	1.6	2.2	2.8	4.0	5.6	6.3	7.1	8.0	11.2	14.0	16.0
4-WAY CASSETTE (DC) [RCI-FSRP]				●	●	●		●	●	●	●	●
NEW 4-WAY CASSETTE (DC) [RCI-FSKDN1Q]				●	●	●	●	●	●	●	●	●
4-WAY COMPACT CASSETTE (DC) [RCIM-FSRE]		●	●	●	●	●		●				
2-WAY CASSETTE (DC) [RCD-FSR]			●	●	●	●		●	●	●	●	●
1-WAY CASSETTE (DC) [RCS-FSR]			●	●	●	●		●	●			

FEATURES COMPARISON

Model	4-WAY CASSETTE TYPE (DC MOTOR TYPE)		4-WAY CASSETTE COMPACT TYPE (DC MOTOR TYPE)	2-WAY CASSETTE TYPE (DC MOTOR TYPE)	1-WAY CASSETTE TYPE (DC MOTOR TYPE)
	RCI-FSRP	NEW RCI-FSKDN1Q	RCIM-FSRE	RCD-FSR	RCS-FSR
Temperature Setting Rate	0.5°C/1.0°C	0.5°C/1.0°C	0.5°C/1.0°C	0.5°C/1.0°C	0.5°C/1.0°C
Fan Speed	4 taps	4 taps	4 taps	4 taps	4 taps
Louver Direction	7 (*4)	7 (*4)	7 (*4)	7 (*4)	7 (*5)
Individual Louver Setting	●	●	●	●	-
Auto Louver Setting	●	●	●	●	●
Dry mode Availability	●	●	●	●	●
Setback (Away Function)	●	●	●	●	●
Cold Draft Prevention Availability (*1)	●	●	●	●	●
Comfort setting Control Cool Air (GentleCool) (*2)	●	●	●	●	●
Direct/Indirect louver direction in COOL	●	●	-	-	-
Direct/Indirect louver direction in HEAT	●	●	-	-	-
FeetWarm air flow control	●	●	-	-	-
FloorSense Cool air flow control	●	●	-	-	-
ViroSense S filter as standard	P-AP160NAE2 P-AP160NA3 P-AP160KA3 P-GP160NAP P-GP160NAPU P-GP160KAP	Standard Decoration panel P-AP160NAE2	-	P-AP90DNA P-AP160DNA	P-AP36CNA P-AP56CNA P-AP80CNA
Power Saving with Motion Sensor (*2)	●	●	●	●	●
Outdoor Unit capacity control (*2)	Peak cut control ●	Moderate control ●	●	●	●
Indoor Unit Rotation Control (*2)	Indoor Unit Address ●	Indoor Air Temperature difference ●	●	●	●
Automatic Fan Operation	●	●	●	●	●
AutoBoost (quick function) (*2)	●	●	●	●	●
Daylight Saving Time	●	●	●	●	●
Power Consumption visualization (*2)	●	●	●	●	●
Weekly Schedule Setting	●	●	●	●	●
Power-Saving Setting (*2)	●	●	●	●	●
Filter cleaning reminder	●	●	●	●	●
Check Menu	Sensor Condition Check ●	Model Display (*2) ●	-	Indoor/Outdoor PCB Check ●	Alarm History Display ●
Colored Panel availability	● (*6)	-	-	● (*6)	● (*6)
Motion Sensor	P-AP160NAE2	P-AP160NAE2	SOR-NEC	SOR-NED	SOR-NES
Receiver Kit for wireless remote controller	PC-ALH3	HR4A10NEWQ PC-ALH3	PC-ALHC1	PC-ALHD1	PC-ALHS1
Drain-up mechanism availability	● (*3)	● (*3)	● (*3)	● (*3)	● (*3)
Fresh air intake accessory	● (*7)	-	● (*7)	● (*7)	● (*7)
Decoration Panel	P-AP160NAE2 P-AP160NA3 P-AP160KA3	Standard	P-AP56NAM P-AP56NAMR	P-AP90DNA P-AP160DNA	P-AP36CNA P-AP56CNA P-AP80CNA
Design Panel Silent-Iconic	P-GP160NAP P-GP160NAPU P-GP160KAP	-	-	-	-
ViroSense Z2 filter (optional) compatible with	P-AP160NAE2 P-AP160NA3 P-AP160KA3 P-GP160NAP P-GP160NAPU P-GP160KAP	Standard Decoration panel P-AP160NAE2	-	-	-
Air filter	F-71L-D1 F-160L-D1 B-160H3	-	-	F-90MD-K1 F-160MD-K1 B-90HD B-160HD	-

(*1) You can use this function to prevent cold discharged air at startup of the heating...
 (*2) Advanced wired remote controller PC-ARF1 needs to be connected.
 (*3) Included as standard equipment.
 (*4) 7 angles are available for individual louver setting, 5 angles only for the operation of Cooling or Dry.
 (*5) 5 steps only for the operation of Cooling or Dry.
 (*6) 3 colors are available (Beige, Grey, and Black).
 (*7) A Duct Adapter (Optional part) is available.

ViroSense S filter



- Features**
- New filter as standard
 - Lasts up to 5 years (12500h)
 - Anti-virus (>99% inhibition)
 - Anti-bacteria (>99% inhibition)
 - Anti-mold 100% growth stop

ViroSense Z2 filter



- Features**
- Optional Accessory
 - Lasts up to 4 years (10000h)
 - Quick & easy to install/change from existing filters
 - Anti-virus (>99.7% inhibition); better than Ion filter
 - Anti SARS-CoV-2 (>99.9% inhibition)

Solutions

Ceiling cassettes

SILENT-ICONIC™ 4-WAY CASSETTE DESIGN PANEL



Exclusive panel: architectural designers will love it!



reddot winner 2021
best of the best

[Silent-ionic] receives Red Dot: Best of the Best for ground-breaking design quality



iF Design Award 2020
Award Winning
(Discipline: Product)




Good Design Award 2020
(Category: Equipment and facilities for professional use)



The design is well-matched to the space

It is designed to harmonize with the space by creating the central part to be a blind shaped air-inlet port and reducing its occupied presence by darkening the air-outlet port.



Blind shaped air-inlet port

The air-outlet port with occupied presence suppression

Tomohiko Sato

Hitachi, Ltd. Product Design Department, Senior Designer



The designer graduated from University in the United Kingdom and soon after, he joined a London based design studio, working across a wide variety of disciplines including furniture, interior and the public realm. Currently, he dedicates himself to air conditioning design, working as a Senior Designer in the Hitachi product design department in Hitachi, Ltd.



Success that sparks



DondiSalotti

Shop information

Dondi Salotti
Via Camillo Cavour 57 Gaglianico, Biella, Italia
dondisalotti.com

General Information

Year of installation : 2022
Project type : Retrofit
Vertical application: Furniture shop
Installed unit : Total 32HP, (10 units of Silent-Iconic 4-way Cassette)






Solutions

Ceiling cassettes



NEW
4-WAY CASSETTE
(DC) [RCI-FSRP, RCI-FSKDN1Q]

DECORATION PANEL LINE-UP


Normal	Smart	Aesthetics	Maintenance
Standard	with motion sensor + radiant temperature sensor	Color Panel Design Panel	Silent-Iconic™ with Elevation Grille
P-AP160NA3	P-AP160NAE2	-	P-GP160NAPU
		Standard (Custom Order) Beige Gray Black Silent-Iconic™ White Black P-GP160NAP P-GP160KAP	
(H×W×D) 40×950×950(mm)	(H×W×D) 40×950×950(mm)	Standard (H×W×D) 40×950×950(mm) Silent-Iconic™ (H×W×D) 52×950×950(mm)	(H×W×D) 52×950×950(mm)
RCI-FSRP	RCI-FSRP, RCI-FSKDN1Q	RCI-FSRP	RCI-FSRP

TWIN-SENSE CASSETTE

Adaptive comfort for real life.


EXCLUSIVE GENTLECOOL

(standard feature)
During cooling, the anti cold-draft control function prevents the perception of a cold draft in the discharged air temperature.




FEETWARM

(with radiant temperature sensor)
During heating, ensures warmth reaches and remains on the floor and around occupants' feet and legs.



FLOORSENSE COOL

(with radiant temperature sensor)
During cooling, based on indoor unit's new radiant sensor, the multi-louvers adjust to the precise airflow position and cooling capacity to prevent the cold air from sinking and overcooling the floor area.



EXCLUSIVE CROWD-SENSE


(with motion sensor + radiant temperature sensor)
When detecting an increase of occupants in the room, Twin-Sense anticipates the additional heat source of human bodies. The cassette immediately and pro-actively adjusts operation for a more stable indoor temperature.



4-WAY COMPACT CASSETTE


(DC) [RCIM-FSRE]

① Ideal for suspended ceilings.




The 600x600 unit can fit in between lighting panels without any disruption.

② Whisper quiet sound level.




④ Suitable for high ceilings.
Standard drain pump: up to 850mm lift.



* Air flow rate: H12
* 2.0-2.5 FSRE

③ Esthetics.




Solutions

Ceiling cassettes




2-WAY CASSETTE (DC) [RCD-FSR]

- ① Individually controlled louvers.
Tailor the air flow direction to both ends of the room.




- ② Facilitated installation.



- ③ Suitable for high ceilings.

Standard drain pump: up to 850mm rise.




* Air flow rate: Hi2
* 2.0-6.0 FSR



1-WAY CASSETTE (DC) [RCS-FSR]

- ① 3 types of installation.



In corner with open louvers (typical).
Allows for ceiling planning for lighting and interiors, suitable for installation near the window.

With closed louvers & ceiling horizontal vent.


Suitable for design that focuses on lighting and suspended ceilings, in case the unit is unable to be directly embedded in the ceiling.

Open louver & ceiling horizontal vent.


Get two directions with 1-way cassette! Connect the cassette with a horizontal vent on the side, and create both downward air flow and horizontal air flow at the same time.

- ② Whisper quiet sound level.

Reduced sound pressure thanks to new design in fan inlet and fan.



- ④ Suitable for high ceilings.
Standard drain pump: up to 850mm lift.



* Air flow rate: Hi2
* 2.5-3.0 FSR
* standard corner type

Solutions

Other indoor units

WIDE RANGE OF MODELS FOR MINIMAL INSTALLATION WORKS

Hitachi range offers our widest choice of indoor units to give you the versatility to complement any interior.



WALL MOUNTED (DC) [RPK-FSRM]

- Simple installation procedure
- Flexible discreet design suitable for any interior
- Setback temperature control available, leading to better operation.
- GentleCool control to ensure you are not both



WALL MOUNTED (DC) [RPK-HNBUSQ]

- Economic choice for any type of room
- Display set-temperature and operation status on front cover by LED



FLOOR/CEILING CONVERTIBLE (AC) [RPFC-FSNQ]

- Each unit can be floor mounted or ceiling suspended
- Easy installation
- Fresh air-intake design



CEILING SUSPENDED (DC) [RPC-FSR]

- Ideal for a higher ceiling (up to 5.6m in cooling)
- Better power-saving with optional Motion Sensor
- Quiet operation level (as low as 28dB(A))
- Setback temperature control available, leading to better operation.
- GentleCool control to ensure you are not bothered by cold draft
- ViroSense S filter as standard!



FLOOR CONCEALED (AC) [RPFI-FSNQ]

- Ideal for spaces without ceiling plenum, can be visually hidden in floor cavities and along the walls.
- Space saving slim unit (only 202/220mm deep).
- Only 620mm high, ideal for under-the-window installation.

FROM 1.7KW TO 16KW

Concealed & exposed indoor units		Cooling (kW)	1.7	2.2	2.8	3.6	4.0	4.3	5.0	5.6	6.3	7.1	8.0	8.4	9.0	11.2	14.0	14.2	16.0
WALL MOUNTED (DC) [RPK-FSRM]													●	●			●		
WALL MOUNTED (DC) [RPK-HNBUSQ]			●	●	●	●		●	●	●	●	●							
FLOOR / CEILING CONVERTIBLE (AC) [RPFC-FSNQ]								●	●	●	●	●		●	●	●		●	
CEILING SUSPENDED (DC) [RPC-FSR]						●			●	●	●	●				●	●		●
FLOOR CONCEALED (AC) [RPFI-FSNQ]			●				●		●	●	●								

FEATURES COMPARISON

Model	WALL MOUNTED		FLOOR/CEILING CONVERTIBLE	CEILING SUSPENDED	FLOOR CONCEALED
	RPK-FSRM	RPK-HNBUSQ	RPFC-FSNQ	RPC-FSR	RPFI-FSNQ
Temperature Setting Rate	0.5°C/1.0°C	1.0°C	1.0°C	0.5°C/1.0°C	1.0°C
Fan Speed	4 taps	6 taps	3 taps	4 taps	3 taps
Louver Direction	7 (*5)	7 (*5)	7 (*5)	7 (*5)	-
Individual Louver Setting	-	-	-	-	-
Auto Louver Setting	-	●	-	-	-
Dry mode Availability	●	●	●	●	●
Setback (Away Function)	●	-	-	●	-
Cold Draft Prevention Availability (*1)(*6)	●	-	●	●	●
Comfort setting	●	-	-	●	-
Control Cool Air (GentleCool) (*2)	●	-	-	●	-
Direct/Indirect louver direction in COOL	-	-	-	-	-
Direct/Indirect louver direction in HEAT	-	-	-	-	-
FeetWarm air flow control	-	-	-	-	-
FloorSense Cool air flow control	-	-	-	-	-
Power Saving with Motion Sensor (*2)	-	-	-	●	-
Outdoor Unit capacity control (*2)	Peak cut control	●	-	-	●
	Moderate control	●	-	-	●
Indoor Unit Rotation Control (*2)	Indoor Unit Address	●	-	-	●
	Indoor Air Temperature difference	●	-	-	●
Automatic Fan Operation	●	●	●	●	●
AutoBoost (quick function)	●	-	-	●	-
Daylight Saving Time	●	●	●	●	●
Power Consumption visualization (*2)	●	-	-	●	-
Weekly Schedule Setting	●	●	●	●	●
Power-Saving Setting (*2)	●	-	-	●	-
Filter cleaning reminder	●	●	●	●	●
Check Menu	Sensor Condition Check	●	●	●	●
	Model Display (*2)	-	-	-	●
	Indoor/Outdoor PCB Check	●	●	●	●
	Alarm History Display	●	●	●	●
Motion Sensor	-	-	-	SOR-NEP	-
Receiver Kit for wireless remote controller	PC-ALHZ1	PC-RLH11 (*6) PC-ALHZ1	PC-RLH11 (*6) PC-ALHZ1	PC-ALHP1	PC-RLH11 (*6) PC-ALHZ1
Drain-up mechanism availability	-	-	-	DUPC-63K1 DUPC-71K1 DUPC-160K1	-
ViroSense S filter	-	-	-	●	-
Strainer kit	MSF-NP112A1	MSF-NP63A1	-	-	-

(*1) This function is utilized to prevent cold discharged air at start-up of heating operation, after defrosting operation, etc.
 (*2) Advanced wired remote controller PC-ARF1 needs to be connected.
 (*3) Included as standard equipment.
 (*4) 7 steps are available by individual louver setting, 5 steps only in the operation of Cooling or Dry.
 (*5) 5 steps only in the operation of Cooling or Dry.
 (*6) Basic Receiver kit (PC-RLH11) is equipped with the unit in package as standard optional part with Wireless Remote Controller (PC-LH7QE).

Solutions

Other indoor units



WALL MOUNTED

(DC) [RPK-FSRM]

- 1) Simple installation procedure.
- 2) Flexible discreet design suitable for any interior.
- 3) **Hotel Setback** feature available, leading to better operation.
- 4) **GentleCool** control to ensure you are not bothered by cold draft.



WALL MOUNTED

(DC) [RPK-HNBUSQ]



- 1) **Meet your detailed requirement & Display**
RDC fan motor help realize 6-step fan speed adjustment, more quiet and efficient. Also newly equipped display set-temperature and operation status on front cover by LED.
- 2) **Simple installation procedure.**
Refrigerant piping can be connected from the rear, base, or left of the unit, providing much greater flexibility for piping and selection of installation sites.
- 3) **Flexible design suitable for any décor.**
With smooth flat covers, the units match most modern interiors. Their compact size enables them to blend in, even in small spaces.
Compact cabinet design with 203mm depth up to 1.3HP and 230mm depth up to 2.5HP.
- 4) **Easy maintenance.**
Front flat panel keeps the unit from dust and facilitates maintenance work.
The front grille hinges open easily—no tools are needed to gain quick access to the filter.
The filter can be removed and cleaned as required.



Solutions

Other indoor units




FLOOR/CEILING CONVERTIBLE

(AC) [RPFC-FSNQ]

① 2-in-1 versatile unit.

Ceiling-suspended installation.


Supplies air to a wide area. Suitable for higher ceilings.



Ceiling Type

Floor-mounted installation.

Smaller footprint: only 230mm in depth. Suitable for installation beneath a window thanks to the 680mm height.



Floor Type

② New air-intake design.

Equipped with air-intakes, the unit can be connected to ventilation equipment such as a Total Heat Exchanger using a duct, providing better interior air quality.


CEILING SUSPENDED

(DC) [RPC-FSR]




① 7m reach motion sensor (option: SOR-NEP).


Use a motion sensor for extra savings when the room is vacant.




② Auto-swing available.



③ 8m air flow reach.




④ Decreased sound pressure, thanks to new fan inlet and fan designs.



⑤ Suitable for high ceilings.

Capacity model (HP)	1.5-3.0	4.0-6.0
Air flow height (m)	3.5	4.3

* air flow volume: high



* Air flow rate: Hi2
* 4.0-6.0 FSR



Solutions


Other indoor units



FLOOR CONCEALED

(AC) [RPF1-FSNQ]

- Blends unobtrusively with any interior décor: only the suction and discharge grilles are visible.
- Its low height (only 620mm) enables the unit to fit perfectly beneath a window.
- Requires little installation space thanks to its slim 202mm depth.



Specifications & accessories

NEW

HIGH ESP HIGH EXTERNAL STATIC PRESSURE

(AC) [RPIH-HNAUN1Q, RPI-FSNQ]



Model		RPIH-3.0HNAUN1Q	RPIH-3.3HNAUN1Q	RPIH-4.0HNAUN1Q	RPIH-5.0HNAUN1Q	RPIH-6.0HNAUN1Q	RPI-8.0FSNQ	RPI-10.0FSNQ	
Indoor Unit Power Supply		AC 1Φ, [220-240V/50Hz]					AC 3Φ, [380-415V/50Hz]		
Nominal Capacity	Cooling	kW	8.4	9.0	11.2	14.2	16.0	22.4	28.0
	Heating	kW	9.6	10.0	13.0	16.3	18.0	25.0	31.5
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	42/39/34	42/39/34	43/39/34	44/41/37	48/42/37	50	52
Outer Dimension	H×W×D	mm	300×1,175×800	300×1,175×800	300×1,175×800	300×1,475×800	300×1,475×800	470×1,060×1,120	470×1,250×1,120
Net Weight	kg		45	45	45	53	54	96	104
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	30/28/23	30/28/23	30/28/23	35.5/32/27	41/33/26	58	72
External Static Pressure (*3)	Pa		120(90)	120(90)	120(90)	120(90)	120(90)	180	180
Connections			Flare-Nut Connection (with Flare Nuts)				Brazing connection		
Refrigerant Piping Diameter	Liquid Line	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
	Gas Line	mm	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ19.05	Φ22.23
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume	m ³		0.40	0.40	0.40	0.49	0.49	0.90	1.06

Receiver Kit	Basic	PC-RLH11
	Advanced	PC-ALHZ1
Condensate Drain Pump Kit	PRIH-HNAUN1Q	DUPI-361Q
	PRI-FSNQ	DUPI-15H2Q
Air filter	3.0-4.0 (HP)	KW-PP9Q
	5.0-6.0 (HP)	KW-PP10Q
AQtiv-Ion Kit	PRIH-HNAUN1Q	JK-LZAQ

Notes:

- The cooling capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
 Cooling Operation Conditions
 Indoor Air Inlet Temperature:.....27.0°C DB
 19.0°C WB
 Outdoor Air Inlet Temperature:.....35.0°C DB
 Piping Length:7.5 metre
 Piping Lift:0 metre
 Heating Operation Conditions
 Indoor Air Inlet Temperature:.....20.0°C DB
 Outdoor Air Inlet Temperature:.....7.0°C DB
 6.0°C WB
 Piping Length:7.5 metre
 Piping Lift:0 metre
- The sound pressure level is based on following conditions. 1.4 metre Beneath the unit.
 With Discharge Duct (2.0 metre) and Return Duct (1.0 metre). Voltage of the power source for the indoor fan motor is 220V.(In case of the power source of 240V, the sound pressure level increases by about 1-2dB(A).)
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- The data for external pressure (*3) indicates "Standard Pressure Setting values when a filter is not used.

NEW

HIGH ESP HIGH EXTERNAL STATIC PRESSURE

(DC) [RPIH-HNDUSQ]



Model		RPIH-8.0HNDUSQ	RPIH-10.0HNDUSQ
Indoor Unit Power Supply		AC1Φ, [220-240V/50Hz] [220V/60Hz]	
Nominal Cooling	kW	23.2	28.6
Capacity (*1)	kcal/h	20,000	24,600
	Btu/h	79,200	97,600
Nominal Cooling	kW	22.4	28.0
Capacity (*2)	kcal/h	19,300	24,100
	Btu/h	76,500	95,600
Cooling Power Consumption	kW	0.49	0.83
Nominal Heating	kW	25.0	31.5
Capacity	kcal/h	21,500	27,100
	Btu/h	85,300	107,500
Heating Power Consumption	kW	0.49	0.83
Sound Pressure Level (Overall A Scale) (*4)	dB	49/48/47/46/45/44	53/52/50/49/47/45
Outer Dimensions	H×W×D	mm	470×1,250×1,120
Net Weight	kg	104	104
	(lbs.)	(229)	(229)
Refrigerant		R410A (Nitrogen-Charged for Corrosion-Resistance)	
Indoor Fan Air Flow Rate (Hi/Me/Lo)	m ³ /h	3420/3240/3120/3060/2940/2850	4320/4080/3900/3660/3450/3000
	(cfm)	(2012/1906/1835/1800/1730/1677)	(2541/2400/2294/2153/2030/1765)
External Pressure (*3)	Pa	150	150
Connections		Brazing connection	
Refrigerant Piping	Liquid Line	mm	Φ9.53
	Gas Line (*5)	mm	Φ22.2
Condensate Drain		VP25	VP25
Approximate Packing Measurement	m ³	1.08	1.08

Receiver Kit	Basic	PC-RLH11	Air filter	Normal Filter	KW-PP14Q
	Advanced	PC-ALHZ1		Coarse Filter	F-10LPIE
Condensate Drain Pump Kit		DUPI-810AQ	ePM10 Filter	F-10HPPIE	
			Filter Box	FB-10PIE	
			AQtiv-Ion Kit	JK-LZAQ	

Notes:

- The nominal cooling capacity is the combined capacity of the standard split system.
 Cooling Operation Conditions
 Indoor Air Inlet Temperature:.....27.0°C DB
 (*1) 19.5°C WB
 (*2) 19.0°C WB
 Outdoor Air Inlet Temperature:.....35.0°C DB
 Piping Length:7.5 metre
 Piping Lift:0 metre
 Heating Operation Conditions
 Indoor Air Inlet Temperature:.....20.0°C DB
 Outdoor Air Inlet Temperature:.....7.0°C DB
 6.0°C WB
 Piping Length:7.5 metre
 Piping Lift:0 metre
- The sound pressure level is based on following conditions.
 With Discharge Duct (2.0m) and Return Duct (1.0m).
 Voltage of the power source for the indoor fan motor is 220V.
 In case of the power source of 240V, the sound pressure level increases by about 1dB.
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
- The data for external pressure (*3) indicates "Standard Pressure Setting values when a filter is not used.
- (*4) The noise value is 150Pa corresponding value.
- (*5) The size of 8HP gas pipe is Φ22.2mm when leaving the factory, and the diameter can be changed to 19.05mm after welding the adapter pipe.

Specifications & accessories



NEW
MEDIUM ESP MEDIUM EXTERNAL STATIC PRESSURE
(AC) [RPIM-HNAUN1Q, RPI-FSN3Q]

Model			RPIM-0.8HNAUN1Q	RPIM-1.0HNAUN1Q	RPIM-1.3HNAUN1Q	RPIM-1.5HNAUN1Q	RPIM-1.8HNAUN1Q	RPIM-2.0HNAUN1Q	RPIM-2.3HNAUN1Q	RPIM-2.5HNAUN1Q	RPI-8.0FSN3Q	RPI-10.0FSN3Q	
Indoor Unit Power Supply			AC 1Φ, [220-240V/50Hz]									AC 3Φ, [380-415V/50Hz]	
Nominal Capacity	Cooling	kW	2.2	2.8	3.6	4.3	5.0	5.6	6.3	7.1	22.4	28.0	
	Heating	kW	2.8	3.3	4.2	4.9	5.6	6.5	7.5	8.5	25.0	31.5	
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	32/27/24	32/27/24	35/33/28	35/33/28	35.5/33/28	35.5/33/28	39/34/26	39/34/26	50	52	
Outer Dimension	(H×W×D)	mm	270×725×720	270×725×720	270×725×720	270×725×720	270×975×720	270×975×720	270×975×720	270×975×720	470×1,060×1,120	470×1,250×1,120	
Net Weight		kg	24	24	25	25	31	31	32	32	96	104	
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	10/8/7	10/8/7	12/11/9	12/11/9	16/14/11.5	16/14/11.5	20/16/11	20/16/11	58(56*)	72(70*)	
External Static Pressure (*3)		Pa	50(80)	50(80)	50(80)	50(80)	50(80)	50(80)	50(80)	50(80)	100	100	
Connections			Flare-Nut Connection (with Flare Nuts)									Braze connection	
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	
	Gas Line	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ19.05	Φ22.23	
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25	
Approximate Packing Volume		m ³	0.22	0.22	0.22	0.22	0.28	0.28	0.28	0.28	0.90	1.06	

Receiver Kit	Basic	PC-RLH11
	Advanced	PC-ALHZ1
Condensate Drain Pump Kit	0.8-2.5 (HP)	DUPI-131Q
	8.0-10.0 (HP)	DUPI-15H2Q
Air filter	0.8-1.5 (HP)	KW-PP7Q
	1.8-2.5 (HP)	KW-PP8Q
AQtiv-Ion Kit	PRIM-HNAUN1Q	JK-LZAQ

Notes:
1. The cooling capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:35.0°C DB
Piping Length: 7.5 metre
Piping Lift: 0 metre


Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
7.0°C WB
Outdoor Air Inlet Temperature:6.0°C WB
Piping Length: 7.5 metre
Piping Lift: 0 metre

2. The sound pressure level is based on following conditions. 1.4 metre Beneath the unit. With Discharge Duct (2.0 metre) and Return Duct (1.0 metre). Voltage of the power source for the indoor fan motor is 220V. (In case of the power source of 240V, the sound pressure level increases by about 1-2dB(A).) The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

3. The data for external pressure (*3) indicates "Standard Pressure Setting values when a filter is not used."



NEW
LOW ESP LOW EXTERNAL STATIC PRESSURE
(AC) [RPIL-HNAUN1Q]



Model			RPIL-0.8HNAUN1Q	RPIL-1.0HNAUN1Q	RPIL-1.3HNAUN1Q	RPIL-1.5HNAUN1Q	RPIL-1.8HNAUN1Q	RPIL-2.0HNAUN1Q	RPIL-2.3HNAUN1Q		
Indoor Unit Power Supply			AC 1Φ, [220-240V/50Hz]								
Nominal Capacity	Cooling	kW	2.2	2.8	3.6	4.3	5.0	5.6	6.3		
	Heating	kW	2.8	3.3	4.2	4.9	5.6	6.5	7.5		
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	28/25/22	28/25/22	34/32/30	34/32/30	34/32/29	34/32/29	36.5/30.5/25		
Outer Dimension	(H×W×D)	mm	270×725×720	270×725×720	270×725×720	270×725×720	270×975×720	270×975×720	270×975×720		
Net Weight		kg	24	24	25	25	31	31	32		
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A		
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	9/8/7	9/8/7	13/11/9	13/11/9	15/14/12	15/14/12	21/14/11		
External Static Pressure (*3)		Pa	30	30	30	30	30	30	30		
Connections			Flare-Nut Connection (with Flare Nuts)								
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52		
	Gas Line	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88		
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25		
Approximate Packing Volume		m ³	0.22	0.22	0.22	0.22	0.28	0.28	0.28		

Model			RPIL-2.5HNAUN1Q	RPIL-3.0HNAUN1Q	RPIL-3.3HNAUN1Q	RPIL-4.0HNAUN1Q	RPIL-5.0HNAUN1Q	RPIL-6.0HNAUN1Q
Indoor Unit Power Supply			AC 1Φ, [220-240V/50Hz]					
Nominal Capacity	Cooling	kW	7.1	8.4	9.0	11.2	14.2	16.0
	Heating	kW	8.5	9.6	10.0	13.0	16.3	18.0
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	36.5/30.5/25	38/30/24	38/30/24	38/35/31	44/39/35	46/41/35
Outer Dimension	(H×W×D)	mm	270×975×720	300×1,175×800	300×1,175×800	300×1,175×800	300×1,475×800	300×1,475×800
Net Weight		kg	32	45	45	45	53	54
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	21/14/11	29/25/21	29/25/21	29/25/21	36/31/26	42/34/26
External Static Pressure (*3)		Pa	30	60	60	60	60	60
Connections			Flare-Nut Connection (with Flare Nuts)					
Refrigerant Piping Diameter	Liquid Line	mm	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
	Gas Line	mm	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume		m ³	0.28	0.40	0.40	0.40	0.49	0.49

Receiver Kit	Basic	PC-RLH11
	Advanced	PC-ALHZ1
Condensate Drain Pump Kit	0.8-2.5 (HP)	DUPI-131Q
	3.0-6.0 (HP)	DUPI-361Q

Air filter	0.8-1.5 (HP)	KW-PP7Q
	1.8-2.5 (HP)	KW-PP8Q
	3.0-4.0 (HP)	KW-PP9Q
	5.0-6.0 (HP)	KW-PP10Q
AQtiv-Ion Kit		JK-LZAQ

Notes:
1. The cooling capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:35.0°C DB
Piping Length: 7.5 metre
Piping Lift: 0 metre

Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
7.0°C WB
Outdoor Air Inlet Temperature:6.0°C WB
Piping Length: 7.5 metre
Piping Lift: 0 metre

2. The sound pressure level is based on following conditions. 1.4 metre Beneath the unit. With Discharge Duct (2.0 metre) and Return Duct (1.0 metre). Voltage of the power source for the indoor fan motor is 220V. (In case of the power source of 240V, the sound pressure level increases by about 1-2dB(A).) The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

3. The data for external pressure (*3) indicates "Standard Pressure Setting values when a filter is not used."

Specifications & accessories



NEW
COMPACT
(DC) [RPIZ-HNDTS1Q]


Model	RPIZ-0.8HNDTS1Q	RPIZ-1.0HNDTS1Q	RPIZ-1.3HNDTS1Q	RPIZ-1.5HNDTS1Q	RPIZ-1.8HNDTS1Q	RPIZ-2.0HNDTS1Q	RPIZ-2.3HNDTS1Q	RPIZ-2.5HNDTS1Q		
Indoor Unit Power Supply	AC 1Φ, [220-240V/50Hz] [220V/60Hz]									
Nominal Capacity	Cooling	kW	2.2	2.8	3.6	4.0	5.0	5.6	6.3	7.1
	Heating	kW	2.5	3.2	4.0	4.5	5.6	6.3	7.1	8.0
Sound Pressure Level	(6 taps)	dB(A)	33/31/28/25/23.5/22.5	33/31/28/25/23.5/22.5	33/31/28/25/23.5/22.5	31/30/28/25/22/20	36/33.5/31/28/24.5/22.5	36/33.5/31/28/24.5/22.5	37/36/33/30/28/25	37/36/33/30/28/25
Outer Dimension	H×W×D	mm	192×700×447	192×700×447	192×700×447	192×910×447	192×1,180×447	192×1,180×447	192×1,180×447	192×1,180×447
Net Weight		kg	17	17	17	20	24	24	24	24
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(6 taps)	m ³ /min	8.5/8/7/6/5.5/5	8.5/8/7/6/5.5/5	8.5/8/7/6/5.5/5	10/9/8/7.5/6.5/6	14.5/13.2/11.8/10.5/9.2/8.0	14.5/13.2/11.8/10.5/9.2/8.0	16.5/15/13/12/10/9	16.5/15/13/12/10/9
External Static Pressure (*3)		Pa	10(0-10-30)	10(0-10-30)	10(0-10-30)	10(0-10-30)	10(0-10-50)	10(0-10-50)	10(0-10-50)	10(0-10-50)
Connections	Flare-Nut Connection (with Flare Nuts)									
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52
	Gas Line	mm	Φ12.70	Φ12.70	Φ12.70	Φ12.70	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume		m ³	0.142	0.142	0.142	0.15	0.18	0.18	0.18	0.18

Receiver Kit	Basic	PC-RLH11
	Advanced	PC-ALHZ1
Condensate Drain Pump Kit	- (included as standard equipment)	

Air filter	0.8-1.5 (HP)	KW-PP5Q
	1.8-2.5 (HP)	KW-PP6Q
AQtiv-Ion Kit	JK-LZQA	

Notes:
1. The cooling capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:35.0°C DB
Piping Length:7.5 metre
Piping Lift:0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
Outdoor Air Inlet Temperature:7.0°C DB
6.0°C WB
Piping Length:7.5 metre
Piping Lift:0 metre
2. The sound pressure level is based on following conditions. 1.4 metre Beneath the unit.
With Discharge Duct (2.0 metre) and Return Duct (1.0 metre).
Voltage of the power source for the indoor fan motor is 220V.
(In case of the power source of 240V, the sound pressure level increases by about 1~2dB(A).)
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
3. The data for external pressure (*3) indicates *Standard Pressure Setting values when a filter is not used.

4-WAY CASSETTE
(DC) [RCI-FSRP]



Model	RCI-1.0FSRP	RCI-1.5FSRP	RCI-2.0FSRP	RCI-2.5FSRP	RCI-3.0FSRP	RCI-4.0FSRP	RCI-5.0FSRP	RCI-6.0FSRP		
Indoor Unit Power Supply	AC 1Φ, [220-240V/50Hz] [220V/60Hz]									
Nominal Capacity	Cooling	kW	2.8	4.0	5.6	7.1	8.0	11.2	14.0	16.0
	Heating	kW	3.2	4.8	6.3	8.5	9.0	12.5	16.0	18.0
Sound Pressure Level	(Hi2/Hi/Me/Lo)	dB(A)	33/30/28/27	35/31/30/27	37/32/30/27	42/36/32/28	42/36/32/28	48/43/39/33	48/45/40/35	48/46/41/37
Outer Dimension	(H×W×D)	mm	248×840×840	248×840×840	248×840×840	248×840×840	298×840×840	298×840×840	298×840×840	298×840×840
Net Weight		kg	20	21	21	22	26	26	26	26
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo)	m ³ /min	15/13/11/9	21/17/14/11	22/17/14/11	27/23/18/14	27/23/18/14	37/31/24/20	37/33/26/21	37/35/28/22
Connections	Flare-Nut Connection (with flare Nuts)									
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
	Gas Line	mm	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume		m ³	0.21	0.21	0.21	0.21	0.25	0.25	0.25	0.25

Decoration panel	Twin-Sense panel	P-AP160NAE2
	Standard (without sensor)	P-AP160NA3
Receiver kit	Advanced	PC-ALH3
Condensate Drain Pump Kit	- (Standard)	
Duct Adapter	PD-75A	
Fresh Air Intake Kit	OACI-160K3	

3-Way Outlet Parts Set	PI-160LS2	
T-Pipe Connection Kit	TKCI-160K	
Deodorant Air Filter	1.0-2.5 (HP)	F-71L-D1
	3.0-6.0 (HP)	F-160L-D1
Filter Box	B-160H3	
ViroSense Z2 filter	F-160L-ZV	
ViroSense S filter	- (Standard)	

Notes:
1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:35.0°C DB
Piping Length:7.5 metre
Piping Lift:0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
Outdoor Air Inlet Temperature:7.0°C DB
6.0°C WB
Piping Length:7.5 metre
Piping Lift:0 metre
2. The sound pressure level is based on following conditions. 1.5 metre Beneath the unit.
The data in the table above was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

NEW
4-WAY CASSETTE
(DC) [RCI-FSKDN1Q]



Model	RPIZ-0.8HNATN1Q	RPIZ-1.0HNATN1Q	RPIZ-1.3HNATN1Q	RPIZ-1.5HNATN1Q	RPIZ-1.8HNATN1Q	RPIZ-2.0HNATN1Q	RPIZ-2.3HNATN1Q	RPIZ-2.5HNATN1Q		
Indoor Unit Power Supply	AC 1Φ, [220-240V/50Hz]									
Nominal Capacity	Cooling	kW	2.2	2.8	3.6	4.0	5.0	5.6	6.3	7.1
	Heating	kW	2.5	3.2	4.0	4.5	5.6	6.3	7.1	8.0
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	30/23/20	30/23/20	34/25/22	32.5/26/23	34/26/25	34/26/25	37/29/27	37/29/27
Outer Dimension	H×W×D	mm	192×700×447	192×700×447	192×700×447	192×910×447	192×1,180×447	192×1,180×447	192×1,180×447	192×1,180×447
Net Weight		kg	17	17	17	21	27	27	28	28
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	9.5/6.5/5.5	9.5/6.5/5.5	9.5/6.5/5.5	10/7/6	15/10/9	15/10/9	17/10/9	17/10/9
External Static Pressure (*3)		Pa	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)	10(30)
Connections	Flare-Nut Connection (with Flare Nuts)									
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52
	Gas Line	mm	Φ12.70	Φ12.70	Φ12.70	Φ12.70	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume		m ³	0.142	0.142	0.142	0.15	0.18	0.18	0.18	0.18

Receiver Kit	Basic	PC-RLH11
	Advanced	PC-ALHZ1
Condensate Drain Pump Kit	- (included as standard equipment)	

Air filter	0.8-1.5 (HP)	KW-PP5Q
	1.8-2.5 (HP)	KW-PP6Q
AQtiv-Ion Kit	JK-LZQA	

Notes:
1. The cooling capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:35.0°C DB
Piping Length:7.5 metre
Piping Lift:0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
Outdoor Air Inlet Temperature:7.0°C DB
6.0°C WB
Piping Length:7.5 metre
Piping Lift:0 metre
2. The sound pressure level is based on following conditions. 1.4 metre Beneath the unit.
With Discharge Duct (2.0 metre) and Return Duct (1.0 metre).
Voltage of the power source for the indoor fan motor is 220V.
(In case of the power source of 240V, the sound pressure level increases by about 1~2dB(A).)
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
3. The data for external pressure (*3) indicates *Standard Pressure Setting values when a filter is not used.

Model	RCI-1.0FSKDN1Q	RCI-1.5FSKDN1Q	RCI-2.0FSKDN1Q	RCI-2.3FSKDN1Q	RCI-2.5FSKDN1Q	RCI-3.0FSKDN1Q	RCI-4.0FSKDN1Q	RCI-5.0FSKDN1Q	RCI-6.0FSKDN1Q		
Indoor Unit Power Supply	AC 1Φ, [220-240V/50Hz] [220V/60Hz]										
Nominal Capacity	Cooling	kW	2.8	4.0	5.6	6.3	7.1	8.0	11.2	14.0	16.0
	Heating	kW	3.2	4.8	6.3	7.1	8.5	9.0	12.5	16.0	18.0
Sound Pressure Level	(Hi2/Hi/Me/Lo)	dB(A)	33/30/28/27	35/31/30/27	37/32/30/27	42/36/32/28	42/36/32/28	42/36/32/28	48/43/39/33	48/45/40/35	48/46/41/37
Outer Dimension	(H×W×D)	mm	238×840×840	238×840×840	238×840×840	238×840×840	238×840×840	288×840×840	288×840×840	288×840×840	288×840×840
Net Weight		kg	20	21	21	22	22	26	26	26	26
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo)	m ³ /min	15/13/11/9	21/17/14/11	22/17/14/11	27/23/18/14	27/23/18/14	27/23/18/14	37/31/24/20	37/33/26/21	37/35/28/22
Connections	Flare-Nut Connection (with flare Nuts)										
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	
	Gas Line	mm	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25	
Approximate Packing Volume		m ³	0.21	0.21	0.21	0.21	0.21	0.25	0.25	0.25	

Receiver Kit	Basic	HR4A10NEWQ
	Advanced	PC-ALH3

Condensate Drain Pump Kit	- (Standard)
ViroSense Z2 filter	F-160L-ZV
ViroSense S filter	- (Standard)

Notes:
1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB (80.0°F DB)
19.0°C WB (66.2°F WB)
Outdoor Air Inlet Temperature:35.0°C DB (95.0°F DB)
Piping Length: 7.5 metre
Piping Lift: 0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB (68.0°F DB)
Outdoor Air Inlet Temperature:7.0°C DB (45.0°F DB)
6.0°C WB (43.0°F WB)
Piping Length: 7.5 metre
Piping Lift: 0 metre
2. The sound pressure level is based on following conditions. 1.5 metre Beneath the unit.
The data in the table above was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
3. Decoration panel is included.

Specifications & accessories

SILENT-ICONIC™ 4-WAY CASSETTE DESIGN PANEL FOR 4-WAY CASSETTE [RCI-FSRP]



Model	P-GP160NAP	P-GP160NAPU	P-GP160KAP
Standard/option	Design Panel Standard	Design Panel with an Elevation Grille	Design Panel Standard
Color	Natural White	Natural White	Black



4-WAY CASSETTE COMPACT (DC) [RCIM-FSRE]

Model	RCIM-0.6FSRE	RCIM-0.8FSRE	RCIM-1.0FSRE	RCIM-1.5FSRE	RCIM-2.0FSRE	RCIM-2.5FSRE
Indoor Unit Power Supply	AC 1Φ, [230V/50Hz] [220-240V/50Hz] [220V/60Hz]					
Nominal Capacity	Cooling kW 1.6	2.2	2.8	4.0	5.6	7.1
Capacity	Heating kW 1.9	2.5	3.2	4.8	6.3	8.5
Sound Pressure Level	(Hi2/Hi/Me/Lo) dB(A) 34/30/28/24.5	36/33/29/24.5	38/34/30/24.5	41/37/33/27.5	45/39/35/31	47/43/39/35
Outer Dimension	(H×W×D) mm 285×570×570	285×570×570	285×570×570	285×570×570	285×570×570	285×570×570
Net Weight	kg 16	16	16	16	17	17
Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo) m³/min 10/8.5/7.5/6	11/9.5/8/6	12/10/8.5/6	13/11/9.5/7	15/12/10/8	16/14/12/10
Connections	Flare-Nut Connection (with Flare Nuts)					
Refrigerant	Liquid Line mm Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52
Piping Diameter	Gas Line mm Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.88
Condensate Drain	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume	m³ 0.13	0.13	0.13	0.13	0.13	0.13
Decoration panel	P-AP56NAM		Motion Sensor		SOR-NEC	
Decoration panel with Receiver kit	Advanced P-AP56NAMR		Condensate Drain Pump Kit		-(Standard)	
Receiver kit	Advanced PC-ALHC1		Duct Adapter		PD-75C	

Notes:
1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:.....35.0°C DB
Piping Length:7.5 metre
Piping Lift:0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
7.0°C DB
Outdoor Air Inlet Temperature:.....6.0°C WB
Piping Length:7.5 metre
Piping Lift:0 metre

2. The sound pressure level is based on following conditions. 1.5 metre Beneath the unit.
The data in the table above was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

3. RCIM-0.6FSRE cannot be connected to HNRQ series.
Please refer to the technical catalogue for the details.

2-WAY CASSETTE (DC) [RCD-FSR]



Model	RCD-0.8FSR	RCD-1.0FSR	RCD-1.5FSR	RCD-2.0FSR	RCD-2.5FSR	RCD-3.0FSR	RCD-4.0FSR	RCD-5.0FSR	RCD-6.0FSR
Indoor Unit Power Supply	AC 1Φ, [220-240V/50Hz] [220V/60Hz]								
Nominal Capacity	Cooling kW 2.2	2.8	4.0	5.6	7.1	8.0	11.2	14.0	16.0
Capacity	Heating kW 2.5	3.2	4.8	6.3	8.5	9.0	12.5	16.0	18.0
Sound Pressure Level	(Hi2/Hi/Me/Lo) dB(A) 30/29/28/27	31/29/28/27	37/34/31/30	39/36/33/30	42/39/36/33	45/42/38/33	43/40/37/34	47/44/41/35	48/45/42/39
Outer Dimension	(H×W×D) mm 298×860×630	298×860×630	298×860×630	298×860×630	298×860×630	298×860×630	298×1,420×630	298×1,420×630	298×1,420×630
Net Weight	kg 23	23	25	25	25	25	39	39	39
Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo) m³/min 10/9/7.5/6.5	11/9.5/8.5/7	15/13/11.5/10	16.5/14.5/12.5/10.5	18.5/16.5/14.5/12.5	21/18.5/16/12.5	30/26.5/23/20	35/31/27/21	37/32.5/28.5/24
Connections	Flare-Nut Connection (with Flare Nuts)								
Refrigerant	Liquid Line mm Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
Piping Diameter	Gas Line mm Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain	VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume	m³ 0.24	0.24	0.24	0.24	0.24	0.24	0.36	0.36	0.36
Decoration panel	0.8-3.0 (HP) P-AP90DNA		4.0-6.0 (HP) P-AP160DNA		0.8-3.0 (HP) F-90MD-K1		4.0-6.0 (HP) F-160MD-K1		
Receiver kit	Advanced PC-ALHD1		Motion Sensor		SOR-NED		Normal Air Filter		
Motion Sensor	-(Standard)		Condensate Drain Pump Kit		-(Standard)		Filter Box		
Condensate Drain Pump Kit	-(Standard)		Duct Adapter		PD-150D		4.0-6.0 (HP) B-90HD		
Duct Adapter	PD-150D		Duct Adapter		PD-150D		4.0-6.0 (HP) B-160HD		
							ViroSense S filter		
							-(Standard)		

Notes:
1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:.....35.0°C DB
Piping Length:7.5 metre
Piping Lift:0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
7.0°C DB
Outdoor Air Inlet Temperature:.....6.0°C WB
Piping Length:7.5 metre
Piping Lift:0 metre

2. The sound pressure level is based on following conditions. 1.5 metre Beneath the unit.
The data in the table above was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

1-WAY CASSETTE (DC) [RCS-FSR]



Model	RCS-0.8FSR	RCS-1.0FSR	RCS-1.5FSR	RCS-2.0FSR	RCS-2.5FSR	RCS-3.0FSR
Indoor Unit Power Supply	AC 1Φ, [220-240V/50Hz] [230V/50Hz] [220V/60Hz]					
Nominal Capacity	Cooling kW 2.2	2.8	4.0	5.6	7.1	8.0
Capacity	Heating kW 2.5	3.2	4.8	6.3	8.5	9.0
Sound Pressure Level	(Hi2/Hi/Me/Lo) dB(A) 34/32/29/27	36/34/31/28	40/37/33/31	42/38/35/31	43/39/36/32	43/40/37/33
Outer Dimension	(H×W×D) mm 235×900×710	235×900×710	235×900×710	235×900×710	235×1,210×710	235×1,210×710
Net Weight	kg 25	25	26	26	33	33
Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo) m³/min 8.5/7.5/6.5/6	9.5/8.5/7.5/6.5	13/11.5/10/8.5	14.5/13/11/9.5	18.5/16.5/14.5/12.5	20/17.5/15.5/13
Connections	Flare-Nut Connection (with Flare Nuts)					
Refrigerant	Liquid Line mm Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.52	Φ9.52
Piping Diameter	Gas Line mm Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88
Condensate Drain	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume	m³ 0.25	0.25	0.25	0.25	0.32	0.32
Decoration panel	0.8-1.0 (HP) P-AP36CNA		1.5-2.0 (HP) P-AP56CNA		Duct Adapter	
	2.5-3.0 (HP) P-AP80CNA		Advanced PC-ALHS1		0.8-2.0 (HP) DG-56SW1	
Receiver kit	Advanced PC-ALHS1		Motion Sensor		2.5-3.0 (HP) DG-80SW1	
Motion Sensor	SOR-NES		Condensate Drain Pump Kit		0.8-2.0 (HP) PIS-56LS	
Condensate Drain Pump Kit	-(Standard)		Duct Adapter		2.5-3.0 (HP) PIS-80LS	
Duct Adapter	PD-100		Duct Adapter		-(Standard)	
					ViroSense S filter	
					-(Standard)	

Notes:
1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.
Cooling Operation Conditions
Indoor Air Inlet Temperature:.....27.0°C DB
19.0°C WB
Outdoor Air Inlet Temperature:.....35.0°C DB
Piping Length:7.5 metre
Piping Lift:0 metre
Heating Operation Conditions
Indoor Air Inlet Temperature:.....20.0°C DB
7.0°C DB
Outdoor Air Inlet Temperature:.....6.0°C WB
Piping Length:7.5 metre
Piping Lift:0 metre

2. The sound pressure level is based on following conditions. 1.5 metre Beneath the unit.
The data in the table above was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.

Specifications & accessories



WALL MOUNTED (DC) [RPK-FSRM]

Type		Expansion Valve built-in type		
Model		RPK-2.5FSRM	RPK-3.0FSRM	RPK-4.0FSRM
Indoor Unit Power Supply		AC 1Φ, [220-240V/50Hz] [220V/60Hz]		
Nominal Capacity	Cooling	kW	7.1	8.0
	Heating	kW	8.5	9.0
Sound Pressure Level	(Hi2/Hi/Me/Lo)	dB(A)	45/42/38/35	47/44/40/35
				51/48/44/39
Color		White		
Outer Dimension	(H×W×D)	mm	300×1,100×260	300×1,100×260
Net Weight		kg	15	15
Refrigerant			R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo)	m ³ /min	18.5/16.5/14/12	20/17.5/15.5/12.5
Motor			38	38
Connections		Flare-Nut Connection (with Flare Nuts)		
Refrigerant Piping Diameter	Liquid Line	mm	Φ9.52	Φ9.52
	Gas Line	mm	Φ15.88	Φ15.88
Condensate Drain			VP16	VP16
Approximate Packing Volume		m ³	0.14	0.14
Accessory included		Wall Mounting Bracket		

Receiver kit	Advanced	PC-ALHZ1
Strainer kit		MSF-NP112A1

Notes:


1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.

Cooling Operation Conditions	Heating Operation Conditions
Indoor Air Inlet Temperature: 27.0°C DB 19.0°C WB	Indoor Air Inlet Temperature: 20.0°C DB 7.0°C DB
Outdoor Air Inlet Temperature: 35.0°C DB	Outdoor Air Inlet Temperature: 6.0°C WB
Piping Length: 7.5 metre Piping Lift: 0 metre	Piping Length: 7.5 metre Piping Lift: 0 metre

2. The sound pressure level is based on following conditions.
1.0 metre Beneath the Unit.
1.0 metre from Discharge Grille.

The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
When bottom air inlet is adopted, sound pressure will increase according to factors such as installation mode and the room structure.

Strainer kit



A strainer kit ensures that solid foreign substances, like small particles of metal, are caught before they enter the electric expansion valves of a wall-mounted indoor unit. Without the strainer kit's filter, these particles may prevent the valves from being fully sealed, creating a risk of explosive condensation when the unit becomes active.

WALL MOUNTED (DC) [RPK-HNBUSQ]



Model		RPK-0.8HNBUSQ	RPK-1.0HNBUSQ	RPK-1.3HNBUSQ	RPK-1.5HNBUSQ	RPK-1.8HNBUSQ	RPK-2.0HNBUSQ	RPK-2.3HNBUSQ	RPK-2.5HNBUSQ	
Indoor Unit Power Supply		AC 1Φ, 220-240V/50Hz, 220V/60Hz								
Nominal Capacity	Cooling	kW	2.2	2.8	3.6	4.0	5.0	5.6	6.3	7.1
	Heating	kW	2.5	3.3	4.0	4.5	5.6	6.3	7.1	8.0
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	36/35/33/32/30/28	36/35/33/32/30/28	38/35/33/32/30/28	38/37/36/32/31/29	44/42/41/38/31/29	40/38/36/35/33/31	41/40/38/35/33/31	45/42/41/38/35/31
	Color		White							
Outer Dimension	(H×W×D)	mm	270×815×203	270×815×203	270×815×203	315×915×230	315×915×230	315×1085×230	315×1085×230	315×1085×230
Net Weight		kg	9.0	9.0	9.0	12.5	12.5	14.0	14.0	14.0
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	9.8/9.2/8.7/8.2/7.5/7.0	9.8/9.2/8.7/8.2/7.5/7.0	10.3/9.2/8.7/8.2/7.5/7.0	11.5/11.0/10.3/9.0/8.7/8.0	14.3/13.5/12.8/11.5/9.0/8.0	16.2/15.0/14.2/13.3/12.2/11.5	17.0/16.2/15.0/13.3/12.2/11.5	20.0/18.0/17.0/15.0/13.3/11.7
Connections		Flare-Nut Connection (with Flare Nuts)								
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ6.35	Φ9.53	Φ9.53	Φ9.53
	Gas Line	mm	Φ9.53	Φ9.53	Φ9.53	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP16	VP16	VP16	VP16	VP16	VP16	VP16	VP16
Approximate Packing Volume		m ³	0.11	0.11	0.11	0.15	0.15	0.17	0.17	0.17
Receiver kit	Basic		PC-RLH11							
	Advanced		PC-ALHZ1							
Strainer kit			MSF-NP63A1							

Notes:

1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.

Cooling Operation Conditions	Heating Operation Conditions
Indoor Air Inlet Temperature: 27.0°C DB (80.0°F DB) 19.0°C WB (66.2°F WB)	Indoor Air Inlet Temperature: 20.0°C DB (68.0°F DB) 7.0°C DB (45.0°F DB)
Outdoor Air Inlet Temperature: 35.0°C DB (95.0°F DB)	Outdoor Air Inlet Temperature: 6.0°C WB (43.0°F WB)
Piping Length: 7.5 metre Piping Lift: 0 metre	Piping Length: 7.5 metre Piping Lift: 0 metre

2. The sound pressure level is based on following conditions.

1.0 metre Beneath the unit.
1.0 metre from Discharge grille.
The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
When bottom air inlet is adopted, sound pressure will increase according to factors such as installation mode and the room structure.

FLOOR/CEILING CONVERTIBLE (AC) [RPFC-FSNQ]



Model		RPFC-1.8FSNQ	RPFC-2.0FSNQ	RPFC-2.3FSNQ	RPFC-2.5FSNQ	RPFC-3.0FSNQ	RPFC-3.3FSNQ	RPFC-4.0FSNQ	RPFC-5.0FSNQ	
Indoor Unit Power Supply		AC 1Φ, [220-240V/50Hz] [220V/60Hz]								
Nominal Capacity	Cooling	kW	5.0	5.6	6.3	7.1	8.4	9.0	11.2	14.2
	Heating	kW	5.6	6.5	7.5	8.5	9.6	10.0	13.0	16.3
Sound Pressure Level	Ceiling Mode	dB(A)	39/35/30	39/35/30	45/41/37	45/41/37	43/39/34	45/40/36	51/46/40	50/46/42
	Floor Mode	dB(A)	43/38/35	43/38/35	48/44/40	48/44/40	46/41/37	48/43/39	54/49/43	55/50/46
Outer Dimension	(H×W×D)	mm	230×990×680	230×990×680	230×990×680	230×990×680	230×1,285×680	230×1,285×680	230×1,285×680	230×1,580×680
Net Weight		kg	31	31	32	32	39	40	41	47
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /h	780/660/540	780/660/540	966/840/678	966/840/678	1,092/912/732	1,164/978/798	1,488/1,230/978	1,980/1,680/1,380
Connections		Flare-Nut Connection (with Flare Nuts)								
Refrigerant Piping Diameter	Liquid Line	mm	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
	Gas Line	mm	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP25	VP25	VP25	VP25	VP25	VP25	VP25	VP25
Approximate Packing Volume		m ³	0.31	0.31	0.31	0.31	0.40	0.40	0.40	0.48
Receiver kit	Basic		PC-RLH11							
	Advanced		PC-ALHZ1							

Notes:

1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.

Cooling Operation Conditions	Heating Operation Conditions
Indoor Air Inlet Temperature: 27.0°C DB 19.0°C WB	Indoor Air Inlet Temperature: 20.0°C DB 7.0°C DB
Outdoor Air Inlet Temperature: 35.0°C DB	Outdoor Air Inlet Temperature: 6.0°C WB
Piping Length: 7.5 metre Piping Lift: 0 metre	Piping Length: 7.5 metre Piping Lift: 0 metre

2. The sound pressure level is based on following conditions.
1.0 metre Beneath the unit.
1.0 metre from Discharge grille.

The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
When bottom air inlet is adopted, sound pressure will increase according to factors such as installation mode and the room structure.

Specifications & accessories



CEILING SUSPENDED (DC) [RPC-FSR]

Model		RPC-1.5FSR	RPC-2.0FSR	RPC-2.5FSR	RPC-3.0FSR	RPC-4.0FSR	RPC-5.0FSR	RPC-6.0FSR	
Indoor Unit Power Supply		AC 1Φ, [220-240V/50Hz] [220V/60Hz]							
Nominal Capacity	Cooling	kW	4.0	5.6	7.1	8.0	11.2	16.0	
	Heating	kW	4.8	6.3	8.5	9.0	12.5	18.0	
Sound Pressure Level	(Hi2/Hi/Me/Lo)	dB(A)	37/35/31/28	38/35/31/28	38/35/31/28	40/37/33/29	44/42/37/32	48/45/41/35	49/47/42/36
Color		Neutral White							
Outer Dimension	(H×W×D)	mm	235×960×690	235×960×690	235×1,270×690	235×1,270×690	235×1,580×690	235×1,580×690	235×1,580×690
Net Weight		kg	26	27	35	35	41	41	41
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi2/Hi/Me/Lo)	m ³ /min	15/13/11/9	15/13/11/9	19/16.5/14/11.5	21/18.5/15.5/12.5	30/26.5/22/17	35/31/25.5/20	37/32.5/27/21
Connections		Flare-Nut Connection (with Flare Nuts)							
Refrigerant	Liquid Line	mm	Φ6.35	Φ6.35	Φ9.52	Φ9.52	Φ9.52	Φ9.52	Φ9.52
Piping	Gas Line	mm	Φ12.7	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88
Condensate Drain			VP20	VP20	VP20	VP20	VP20	VP20	VP20
Approximate Packing Volume		m ³	0.23	0.23	0.31	0.31	0.38	0.38	0.38
Receiver kit	Advanced		PC-ALHP1						
Motion Sensor			SOR-NEP						
Condensate Drain Pump Kit	1.5 (HP)		DUPC-63K1						
	2.0 (HP)		DUPC-71K1						
	2.5-6.0 (HP)		DUPC-160K1						
ViroSense S filter			- (Standard)						

Notes:

1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.

Cooling Operation Conditions

Indoor Air Inlet Temperature:.....27.0°C DB
 19.0°C WB
 Outdoor Air Inlet Temperature:.....35.0°C DB
 Piping Length: 7.5 metre
 Piping Lift: 0 metre

Heating Operation Conditions

Indoor Air Inlet Temperature:.....20.0°C DB
 Outdoor Air Inlet Temperature:.....7.0°C DB
 6.0°C WB
 Piping Length: 7.5 metre
 Piping Lift: 0 metre

2. The sound pressure level is based on following conditions.

1.0 metre Beneath the unit.
 1.0 metre from Discharge grille.
 The above data was measured in an anechoic chamber so that reflected sound should be taken into consideration in the field.
 When bottom air inlet is adopted, sound pressure will increase according to factors such as installation mode and the room structure.



FLOOR CONCEALED (AC) [RPFI-FSNQ]

Model		RPFI-1.0FSNQ	RPFI-1.5FSNQ	RPFI-2.0FSNQ	RPFI-2.5FSNQ	
Indoor Unit Power Supply		AC 1Φ, [220-240V/50Hz]				
Nominal Capacity	Cooling	kW	2.8	4.3	5.6	7.1
	Heating	kW	3.3	4.9	6.5	8.5
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	37/34/31	40/38/35	42/38/36	45/43/40
Outer Dimension	(H×W×D)	mm	620×900×202	620×900×202	620×1,170×202	620×1,170×202
Net Weight		kg	25	26	34	34
Refrigerant			R410A	R410A	R410A	R410A
Indoor Fan Air Flow Rate	(Hi/Me/Lo)	m ³ /min	8.5/7/6	12/8/7	16/12.5/10.5	16/14/11
Connections		Flare-Nut Connection (with Flare Nuts)				
Refrigerant	Liquid Line	mm	Φ6.35	Φ6.35	Φ6.35	Φ9.52
Piping	Gas Line	mm	Φ12.70	Φ12.70	Φ15.88	Φ15.88
Condensate Drain			VP25	VP25	VP25	VP25
Packaging Volume		m ³	0.19	0.19	0.23	0.23
Receiver kit	Basic		PC-RLH11			
	Advanced		PC-ALHZ1			

Notes:

1. The cooling and heating capacities above show the maximum capacities when the outdoor and indoor temperature are under the following conditions.

Cooling Operation Conditions

Indoor Air Inlet Temperature:.....27.0°C DB
 19.0°C WB
 Outdoor Air Inlet Temperature:.....35.0°C DB
 Piping Length: 7.5 metre
 Piping Lift: 0 metre

Heating Operation Conditions

Indoor Air Inlet Temperature:.....20.0°C DB
 Outdoor Air Inlet Temperature:.....7.0°C DB
 6.0°C WB
 Piping Length: 7.5 metre
 Piping Lift: 0 metre

2. The sound pressure level is based on following conditions.

1.0 metre from the unit.
 1.0 metre from floor level.
 Voltage of the power source for the indoor fan motor is 220V.
 The above data was measured in an anechoic chamber.





Improve indoor air quality!

Today, the average person spends more than 75% of their day indoors. Without proper ventilation, CO₂ levels rise, pollutants circulate and potentially harmful bacteria build-up, impacting on the wellbeing, comfort and productivity of occupants. Make these spaces as healthy and comfortable as possible by connecting our ventilation solutions into your Hitachi VRF systems.

VENTILATION

113 Our ventilation line-up

115 Ventilation Solutions

- 115 All fresh air unit
- 116 Total heat exchanger

117 DX-KIT



Our ventilation line-up


Our line-up fulfils the ventilation requirements of the desired space by drawing in clean air from the outside and replenishing indoor spaces. It features solutions that suit every type of building; you can use the ventilation technology as it is or it can be incorporated into a Hitachi indoor unit via the fresh-air port. Thanks to our ventilation options, you can optimize the design of your system to meet your needs.

ALL FRESH AIR UNIT



- Creates a comfortable and healthy indoor environment, thanks to the fresh air and heat/cool functions.
- Various controllers can be selected and interfaced with the H-LINK system.
- Longer ducts can be connected on-site, thanks to the higher ESP.

TOTAL HEAT EXCHANGER



- Creates a healthy indoor environment thanks to the fresh air and ventilation functions.
- Every unit is equipped with a remote controller for the total heat exchanger as a standard part.

FROM 150 TO 6,000m³/h

Fan Air Flow Rate (m ³ /h)	150	200	210	230	300	400	500	550	650	700	800	1,000	1,080	1,250	1,500	1,680	2,000	2,100	2,500	3,000	4,000	5,000	6,000	
All Fresh Air Unit													•			•		•		•	•	•	•	
Total Heat Exchanger	•	•	•	•	•	•	•	•	•	•	•	•		•	•		•		•	•	•	•		

EXTRA AIR-RENEWAL SOLUTION OFFERINGS

We offer two additional options to meet both occupants' needs and your building's requirements.

DX-KIT

- Offers great flexibility by enabling you to integrate Hitachi VRF into your building's existing air handling units (AHU).
- Wide capacity range (available up to 96HP AHU).
- Wide configuration options with AHU/Indoor units.



FRESH-AIR INTAKE PORT



- Optional duct adapter which enables fresh air into the unit so that it can be blown out with conditioned air.
- Connects with the indoor units: 4-way cassette type, 4-way compact cassette type, 2-way cassette type, 1-way cassette type.



Ventilation solutions



ALL FRESH AIR UNIT

Model	RPI-5.0KFNQ		RPI-8.0KFNQ		RPI-10.0KFNQ		RPI-12.0KFNQ	
Power Supply	AC 1Φ 220-240V/ 50Hz	AC 1Φ 220V/ 60Hz	AC 1Φ 220-240V/ 50Hz	AC 1Φ 220V/ 60Hz	AC 1Φ 220-240V/ 50Hz	AC 1Φ 220V/ 60Hz	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz
Cooling	Capacity	kW	14.0	14.0	22.4	22.4	28.0	28.0
	Power	kW	0.30	0.35	0.48	0.55	0.50	0.58
	Nominal Current	A	1.4	1.61	2.2	2.53	2.3	2.65
Heating	Capacity	kW	13.7	13.7	21.9	21.9	24.5	24.5
	Power	kW	0.30	0.35	0.48	0.55	0.50	0.58
	Nominal Current	A	1.4	1.61	2.2	2.53	2.3	2.65
Sound Pressure Level (overall a scale)	dB(A)	42	42	44	44	47	47	56
Dimensions	H×W×D	mm	370×1320×800		486×1270×1069		486×1270×1069	
Net Weight	kg	63	63	110	110	110	110	110
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A
Air Flow Rate	m ³ /min		18	18	28	28	35	35
External Pressure	Pa		200	200	220	220	220	220
Piping	Liquid	mm	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ9.53	Φ12.7
	Gas	mm	Φ15.88	Φ15.88	Φ19.05	Φ19.05	Φ22.2	Φ25.4
Condensate Drain			VP25, Outer Diameter: Φ32mm					
Temperature range of fresh air drawn			Cooling: 20.0°C~43.0°C, Heating: -7.0°C~15.0°C					

Model	RPI-16.0KFNQL		RPI-16.0KFNQH		RPI-20.0KFNQL		RPI-20.0KFNQH		RPI-20.0KFNQLF		RPI-20.0KFNQHF	
Power Supply	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz	AC 3Φ 380-415V/ 50Hz	AC 3Φ 380V/ 60Hz
Connectable Outdoor Unit	RAS-160HNCEL(R)/W				RAS-200HNCEL(R)WS, RAS-200HNCEL(R)WP, RAS-200HNCEL(R)WS							
Cooling	Capacity	kW	45.0	45.0	45.0	45.0	56.0	56.0	56.0	56.0	56.0	56.0
	Power	kW	0.72	0.83	1.06	1.22	1.06	1.22	1.39	1.6	1.39	1.60
	Nominal Current	A	1.8	2.07	2.2	2.53	2.22	2.55	3.14	3.61	3.0	3.45
Heating	Capacity	kW	36.0	36.0	36.0	36.0	44.8	44.8	44.8	44.8	44.8	44.8
	Power	kW	0.72	0.83	1.06	1.22	1.06	1.22	1.39	1.6	1.39	1.60
	Nominal Current	A	1.8	2.07	2.2	2.53	2.22	2.55	3.14	3.61	3.0	3.45
Sound Pressure Level (overall a scale)	dB(A)	58	58	62	62	61	61	65	65	63	63	67
Dimensions	H×W×D	mm	635×1950×805		635×1950×805		735×1950×805		735×1950×805		735×1950×805	
Net Weight	kg	196	196	196	196	222	222	222	222	222	222	222
Refrigerant			R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A	R410A
Air Flow Rate	m ³ /min		67	67	67	67	83	83	83	100	100	100
External Pressure	Pa		200	200	300	300	200	200	300	300	200	300
Piping	Liquid	mm	Φ12.7	Φ12.7	Φ12.7	Φ12.7	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88	Φ15.88
	Gas	mm	Φ25.4	Φ25.4	Φ25.4	Φ25.4	Φ28.6	Φ28.6	Φ28.6	Φ28.6	Φ28.6	Φ28.6
Condensate Drain			RC1 (Internal Screw)									
Temperature range of fresh air drawn			Cooling: 20.0°C~43.0°C, Heating: -7.0°C~15.0°C									

Notes:


- Cooling capacity and heating capacity tested in the following conditions:
Cooling conditions: 33.0°CDB, 28.0°CWB, pipeline length 7.5 metre, pipe height difference 0 metre.
Heating conditions: 0°CDB, -2.9°CWB, pipeline length 7.5 metre, pipe height difference 0 metre (heating is the data without defrosting).
- Noise test conditions are as follows:
At a distance of 1.5 metre from the unit surface.
The above parameters are measured in the anechoic chamber without reflected echo, therefore the impact of the reflected echo must be counted at the scene.
- An air filter with dust removal efficiency of 50% or more needs to be installed at the air inlet.
- When the field duct resistance is small and the fan speed is too high, the unit will appear the phenomena of abnormal shutdown, fault, water spray etc., and the duct pipe should be insulated to prevent generating dew.
- Air processor can only be used for processing fresh air, indoor air conditioning load processing need to use other air conditioners.
- Fresh air processing unit should be connected with Hitachi Top Flow VRF unit.
When fresh air processing unit and other indoor units air all connected to the same outdoor unit, its equivalent cooling capacity is calculated by the following criteria:
Type_5HP class: 21.0kW; 8HP class: 33.3kW; 10HP class: 42.0kW
- Refer to capacity restrains shown on Table below for indoor unit capacity connectable to outdoor unit.

System	All Fresh Air Unit System (Only All Fresh Air Unit)	Mixed System (All Fresh Air Unit and Other Indoor Unit)
Range of Combination Capacity	80 to 100%	i) 80 to 100% and ii) Total Capacity of All Fresh Air: 30%

Mixed system is only available with RPI-5.0/8.0/10.0KFNQ.

RPI-12.0KFNQ or above is only available as one to one All Fresh Air Unit system.

- When outdoor temperature is below 20.0°C in cooling operation, the system will be automatically converted to ventilation operation.
When outdoor temperature is higher than 15.0°C in heating operation, it will be automatically converted to ventilation operation. When lower than -7.0°C, the fresh air processing unit will stop running.



TOTAL HEAT EXCHANGER

Model	KPI-20H-A-GQ	KPI-30H-A-GQ	KPI-40H-A-GQ	KPI-50H-A-GQ	KPI-65H-A-GQ	KPI-80H-A-GQ	KPI-100H-A-GQ	KPI-125H-A-GQ
Unit Power Supply	AC 1Φ, [220/50Hz]							
Temp. Efficiency	Summer (Hi/Me/Lo)	%	64/64/70	60/60/65	61/61/66	60/60/62	65/65/69	65/65/69
	Winter (Hi/Me/Lo)	%	80/80/83	77/77/80	79/79/81	75/75/76	75/75/78	74/74/78
Enthalpy Efficiency	Summer (Hi/Me/Lo)	%	69/69/76	63/63/70	64/64/69	63/63/65	57/57/60	60/60/63
	Winter (Hi/Me/Lo)	%	75/75/78	70/70/75	70/70/75	69/69/71	65/65/70	70/70/72
Sound Pressure Level	(Hi/Me/Lo)	dB(A)	32/30/25	36/34/28	39/37/30	40/38/31	40/38/35	40/38/34
Outer Dimension	(H×W×D)	mm	220×962×735	220×962×735	220×1,112×735	220×1,112×735	388×1,119×884	388×1,119×884
Net Weight	kg	38	40	46	52	61	69	95
Air Flow Rate	(Hi/Me/Lo)	m ³ /h	200/200/150	300/300/210	400/400/230	500/500/400	650/650/550	800/800/650
External Static Pressure	(Hi/Me/Lo)	Pa	100/70/40	120/90/50	120/90/50	120/90/50	130/100/90	130/100/90
Power Input	(Hi/Me/Lo)	W	120/110/75	165/155/120	210/200/130	330/310/230	2×(188/173/142)	2×(207/188/165)
Current	(Hi/Me/Lo)	A	0.6/0.5/0.4	0.8/0.7/0.6	1.0/1.0/0.7	1.6/1.5/1.1	1.72/1.58/1.31	2.04/1.93/1.73
Connection Duct Diameter	mm	Φ144	Φ144	Φ144	Φ194	Φ242	Φ242	Φ242
Approximate Packing Volume	m ³	0.37	0.37	0.43	0.49	0.94	1.15	1.15

Model	KPI-150H-E-GQ	KPI-200H-E-GQ	KPI-250H-E-GQ	KPI-300H-E-GQ	KPF-400H-E-GQ	KPF-500H-E-GQ
Unit Power Supply	AC 3Φ, [380/50Hz]					
Temp. Efficiency	Summer	%	63	63	63	63
	Winter	%	68	72	75	75
Enthalpy Efficiency	Summer	%	57	57	55	55
	Winter	%	68	68	72	72
Sound Pressure Level	dB(A)	50	51	53	54	57
Outer Dimension	(H×W×D)	mm	536×1,500×1,300	536×1,500×1,400	640×1,700×1,500	640×1,750×1,600
Net Weight	kg	144	155	180	220	225
Air Flow Rate	m ³ /h	1,500	2,000	2,500	3,000	4,000
External Static Pressure	Pa	165	160	180	200	220
Power Input	W	2×440	2×810	2×925	2×1080	2×1,470
Current	A	2.84	3.08	4.19	5.23	5.57
Connection Duct Diameter	mm	400×320 +400×320	400×320 +400×320	500×350 +500×350	500×350 +500×350	400×320 +590×320
Approximate Packing Volume	m ³	1.82	1.95	2.63	2.93	3.01

Note:

Please confirm the model name for "wires remote controller" compatible with Total Heat Exchanger to your local distributor.





DX-KIT

Integrate Hitachi VRF into your pre-existing Air Handling Units (AHU).



Dimensions



Capacity (HP)		2	4	6	8/10	12~20	22~30
Model		DXF-2.0A1	DXF-4.0A1	DXF-6.0A1	DXF-10.0A1	DXF-20.0A1	DXF-30.0A1
Control Box (C Box)	Power Supply	AC1Φ, [220-240V /50Hz] [220V 60Hz]					
	Height	mm	112	112	112	112	112
Expansion Valve Box (EXV Box)	Width	mm	435	435	435	435	435
	Depth	mm	349	349	349	349	349
AHU Suction Temperature Range	Cooling	21.0°C to 32.0°C (DB) / 15.0°C to 23.0°C (WB)					
	Heating	15.0°C to 27.0°C (DB)					
Connection Ratio in different configurations → Total AHU or AHU & IDU Connection Ratio against ODU capacity = X (In case of "Inlet Air Temperature Control")		• 1 ODU to 1 AHU : 50% < X ≤ 100% • 1 ODU to 1 AHU (Separate Heat Exchanger Type) : 50% < X ≤ 100% • 1 ODU to Multiple AHUs : 50% < X ≤ 100% • 1 ODU to AHU & IDUs : 1 ODU to AHU & IDUs : (1) 50% < X ≤ 100% → Total AHU capacity: No limitation / Each AHU capacity: No limitation (2) 100% < X ≤ 110% → Total AHU capacity: less than 30% of total capacity / Each AHU capacity: between 2-6HP class • 1,000 (When the number of connected [AHU & IDU] in the system is the same or less than the recommended.) • 300 (When the number of connected [AHU & IDU] in the system is more than the recommended.)					
	Maximum Piping Length	Total	m	5	5	5	5
Maximum Level Difference	Between AHU Heat Exchanger and EXV Box	m	2	2	2	2	2
	Control wiring between AHU Heat Exchanger and EXV Box	m	10	10	10	10	10
Temperature Control Modes (*1)	Thermistor to AHU Heat Exchanger from C Box	m	10	10	10	10	10
			• Inlet Air Temperature Control • Outlet Air Temperature Control • Duty Control				


(*1) [Outlet Air Temperature Control] & [Duty Control] are available only in case of connections "1 ODU to 1 AHU" & "1 ODU to 1 AHU (Separate Heat Exchanger Type)".

DX-KIT: GREAT FLEXIBILITY FOR SIMPLIFIED HVAC UPGRADE

① Wide range of capacity:

- (DX-Kit) Single capacity from 2HP to 30HP
- (Custom AHU) up to 112HP available by DX-Kit combination

Our DX-Kit can cover from small to large capacity AHU. It can meet any requirement in any application!




DX-Kit Above : Expansion Valve Box (EXV Box). Below : Control Box (C Box).

② Flexible installation:

- Both outdoor & indoor installation of DX-Kit available
- Design Flexibility in wiring & piping

DX-Kit facilitates system design!

Both outdoor & indoor installations available!





③ 4 examples of configuration:

- 1 VRF outdoor unit + 1 AHU
- 1 VRF outdoor unit + 1 AHU (external heat exchanger)
- 1 VRF Outdoor unit + multiple AHUs
- 1 VRF Outdoor unit + VRF indoor units + AHUs

[Example]

DX-Kit
 Left: Control Box (C Box)
 Right: Expansion Valve Box (EXV Box)





New generation: simple and smart!

Everyone deserves comfort, but comfort does not mean the same to everyone. That's why control is key. Our controllers offer best-in-class simplicity. Using our praised central stations, building managers can instantly optimize air conditioning in targeted zones. For occupants, our new advanced color controller provides intuitive navigation with a premium design. With airCloud Pro, our exclusive new-generation solution, users can manage from one indoor unit to several systems remotely via IoT (web/smartphone).

CONTROLLERS

121 Centralized controllers

- 121 Line-up overview
- 123 **air**Cloud Pro
- 125 Central Station EX
- 126 Central Station EZ
- 126 Central Station MINI

127 Individual controllers

- 127 Line-up overview
- 129 **air**Cloud Tap
- 131 Advanced color wired remote controller
- 133 Eco-compact controller
- 135 Wired remote controller
- 136 Advanced wireless remote controller
- 136 Wireless remote controller
- 136 Receiver kit

137 Accessories

139 H-LINK: enjoy more freedom

Centralized controllers

Control each indoor unit, one specific zone or even multiple systems from one place!

airCLOUD PRO (HC-IoTGW)

- Remote access via smartphone app or web.
- Unlimited number of systems, zones and users.
- Intuitive scheduling function.
- Troubleshooting with access to error history and alerts.
- Filter sign display to quickly overview daily maintenance needs.
- Ideal for all types of applications.

CENTRAL STATION EX (PSC-A128EX3)

- Control capacity: max 2,560 indoor units (+15x Extension Adapter PSC-AD128EX3).
- With energy calculation software (PSC-AS01EXC), determine each tenant's energy usage.
- Easy monitoring with simplified interface.
- Best option for middle-large size buildings.
- Remote access! Operate Central Station EX from your laptop PC or touch-panel PC.

CENTRAL STATION EZ (PSC-A64GT)

- Control capacity: max 64 remote control group of indoor units.
- Compact and optimized 170x250mm body screens fitting in even small walls.
- Easy monitoring with simplified interface.
- Best option for middle size buildings.

CENTRAL STATION MINI (PSC-A32MN)

- Control capacity: max 32 remote control group of indoor units.
- Compact and optimized 120x140mm body screens fitting in even small walls.
- Easy monitoring with simplified interface.
- Best option for small size buildings.

SMALL TO LARGE SYSTEMS & FIXED OR CLOUD-BASED

		airCLOUD PRO HC-IoTGW	CENTRAL STATION EX PSC-A128EX3	CENTRAL STATION EZ PSC-A64GT	CENTRAL STATION MINI PSC-A32MN
Capacity comparison	Total Connection capacity	RC group 64 (*6)	2,560 (*1)	64	32
		Group 64 (*6)	2,048 (*1)	64	32
		Block Unlimited (*7)	512 (*2)	4	2/4/8/16
		Area Unlimited (*7)	512 (*2)	-	-
		Indoor unit 80 (*6)	2,560 (*1)	160	160
		Outdoor unit 16 (*6)	1,024 (*1)	64	64
	Building scale	Small to Large	Large	Medium	Small
	Operation	Web + Mobile Phone	Touch screen + Web (New!)	Touch screen	Touch screen
Display	Operation panel size options	Adaptive	7	2	3
	Layout	-	●	-	-
	List options	-	3	-	-
Operation unit	All together	●	●	●	●
	By layout	-	●	-	-
	By area	●	●	-	-
	By block	●	●	●	●
	By group	●	●	-	-
	By RC group	-	-	●	●
Control Function	By indoor unit	●	●	-	-
	Main 5 functions (*5)	●	●	●	●
	Individual controller lock	●	●	Δ (*3)	●
	Filter sign reset	●	●	●	●
Monitor Function	Outdoor unit capacity control	-	●	-	Δ (*4)
	Outdoor unit noise control	-	●	-	-
	Main 5 functions (*5)	●	●	●	●
	Individual controller lock	●	●	●	●
	Alarm status & code	●	●	●	●
	Filter sign	●	●	●	●
Schedule Function	Air inlet temperature of indoor unit	-	●	-	●
	Air inlet temperature of outdoor unit	-	●	-	●
	Weekly	●	●	●	-
	Setting times per day	16	16	10	10
	Special day setting	5	5	-	-
	Holiday setting	-	●	-	-
Other function	Annual/Summer/Winter schedule	Future Version	●	-	-
	Alarm history (records number)	Unlimited	10,000	100	100
	External in/output history	-	1,000	-	-
	Management report visualization(*11)	Energy Estimation (*8) - Future	●	●	●
	Data output by external media	Download from Web - Future	SD card, USB flash device	-	-
	Individual WRC clock synchronization	-	●	-	-
IoT Functions	Connectivity	Ethernet + 4G (*9)	-	-	-
	Future Extendability	Firmware OTA (*10) Web + Mobile Update	-	-	-

(*1) One Extension Adapter (PSC-AD128EX3) enable CENTRAL STATION EX to control additional 160 RC groups /128 groups / 160 IDUs / 64 ODU, and up to 15 adapters can connect to one Central Station EX.

(*2) No restriction on the number of H-LINK.

(*3) Individual Feature Control in Each Remote Controller is not available.

(*4) Applicable only with Schedule function or external signal input. You cannot set it up directly from monitoring panel.

(*5) Main 5 functions meaning: 1) Run/Stop 2) Operation mode 3) Temperature setting 4) Fan speed 5) Louver control.

(*6) Ability to connect unlimited number of "HC-IoTGW" in one project and control all AC units via one single screen on Web or Mobile Phone.

(*7) Unlimited creation of zones, across multiple "HC-IoTGW" units within the same project.

(*8) Visualization of outdoor unit energy consumption.

(*9) 4G available through optional 4G module; 4G module package comes with global SIM and pre-paid global data plan.


(*10) OTA: Over-the-air firmware update, provides always up-to-date firmware and latest functionalities.

(*11) Mini, EZ: Accumulated operation time (min), Accumulated thermo - ON (min).

EX: Accumulated operation time (min), Accumulated thermo - ON time (min), Average air intake temperature of indoor unit, Average air intake temperature of outdoor unit, Average setting temperature, Average RC sensor temperature.

Centralized controllers

airCLOUD PRO



Specifications

Gateway	HC-IoTGW
Net weight (g)	540
Connection capacity	16 outdoor + 80 indoor units
Power supply (V) (Hz)	100-240, AC 50/60
Max. power consumption (W)	10
Communication port	1 H-LINK, 1 RS485 Port
Internet connection	LAN (Ethernet) or 4G ³
External interface (log storage)	1 micro SD card slot

Functions

IoT connection (cloud-based)	<ul style="list-style-type: none"> Access via smartphone app or web Unlimited number of gateways Unlimited number of locations Unlimited number of users
Operation unit	<ul style="list-style-type: none"> Per entire location Per system Per zone (unlimited zone creation) Per indoor unit remote control group
Control function	<ul style="list-style-type: none"> On/Off Mode Set temperature Fan speed Louver RC lock Filter sign reset

Monitor Function	<ul style="list-style-type: none"> On/Off Mode Set temperature Air intake temperature RC sensor temperature (*3) Air intake temperature of outdoor unit Fan Speed Louver RC prohibition Thermo-ON information Filter sign/Auto cleaning fault Alarm status/Alarm codes
Schedule function	<ul style="list-style-type: none"> Weekly schedule Easy selection of days and zones Setting items in schedule is as below; On/Off Operation mode Setting temperature Louver Fan speed

*All Groups Run/Stop" command signal exception function for selected groups is available by "Exception of Run/Stop Operation." function.

System configuration.



Recommended facilities (examples.)



Is airCloud Pro for me?

All VRF users can enjoy these benefits!


- Save energy
- Save time and unnecessary transportation
- Delegate VRF systems administration
- Create a comfortable climate for guests

Future-proof

With updates and new features added regularly, airCloud Pro ensures you are always up to date.

- Compatible with new and former
- Hitachi Variable Refrigerant
- Flow systems*1


Control is in your hands.
24/7 control at your fingertips on smartphone, tablet, or PC.



- ✓ Intuitive simplicity
airCloud Pro is designed to make your job easier. An intuitive app that anyone can use, airCloud Pro makes managing your VRF systems easier than ever before.
- ✓ Control from anywhere
Enjoy the freedom of remote access from your smartphone, tablet or laptop. airCloud Pro allows you to remotely control your VRF system(s) from a single app, saving you travel time.

A simple yet powerful tool.

- 👍 Simplify your job
The pilot app makes managing your VRF systems easy.
- 🌍 Save more energy
Monitor energy consumption and optimize usage.
- Centralized control
Control your entire VRF system or selected zones in one touch.
- Simplified troubleshooting
A clear error history, concise error description and follow-up.
- Smartphone alerts²
In the event of a critical malfunction.
- Flexible user management²
Add users and custom access restrictions.
- Energy consumption data²
Simple graphs visualize power consumption.
- Intuitive scheduling
Plan operations ahead based on your business hours.
- Individual controller lock
Prevent inappropriate usage from occupants.



- ♥ Create better comfort
Adjust temperature, fan speed, and modes with ease, creating total comfort and the ideal climate throughout your building.
- ✂ Easy plug-and-play
Our airCloud gateway makes installation a breeze.
- An integrated weather forecast² display helps you determine the most suitable conditions for your indoor spaces all year round.
- Connect to the airCloud via 3G/4G³ or ethernet and pair your VRF systems via QR code scan. With automatic detection of indoor units and an optimized installer view, configuring your site and zones has never been quicker.

+ data security

Best-in-class standards:
TLS.v1.2, HTTPS 2038 encryption.

Minimal personal details:
Only your name, email address and phone number are required for login.

*1 Confirm compatibility of your VRF installation with your Hitachi Cooling & Heating representative.

² Functions not available as of September 2019, coming soon.
³ 4G module available as a side accessory.

Centralized controllers

CENTRAL STATION EX FOR LARGE-SCALE BUILDINGS

(PSC-A128EX3)



For middle or large-scale buildings such as hotels, educational facilities, and hospitals, our Central Station EX features a highly intuitive and functional 12.1-inch wide, wall-mountable, color LCD screen.

Control up to 2,560 indoor units with our proprietary H-LINK system with 15 extension adapters (PSC-AD128EX3).

Also, with energy calculation software (PSC-AS01EXC), Central Station EX can help you easily manage each tenant's electricity & report the power consumption of VRF system for each tenant.


Install by add-on software and activate, then, you can select electricity ratio or usage ratio from several methods.

Capacity

H-LINK	16
RC group	2,560 (*1)
Group	2,048 (*1)
Block	512 (*2)
Area	512 (*2)
Indoor unit	2,560 (*1)
Outdoor unit	1,024 (*1)
Building scale	Large



PSC-AD128EX3
(*1) 1 extension adapter (PSC-AD128EX3) enables Central Station EX to control additional 160 RC groups / 128 groups / 160 IDUs / 64 ODU. Central Station EX can connect up to 15 adapters.
(*2) No restriction on the number of H-LINK



Specifications

Rated power supply	100-240VAC ±10% (50/60Hz)
Electrical power consumption	50W (Max.)
Communication unit	Units of Adopting for H-LINK
Communication line	Two-wire non-polar
Communication speed	9,600bps
Wiring length	1,000m (Total Length)
Display	12.1 inch TFT color liquid crystal display
Display control	Touch Panel


Functions

Operation unit	All together Each area Each block Each group Each indoor unit	Each of the following settings is available in 3 different [annual] [summer][winter] categories: → Weekly schedule → Up to 16 actions can be set per day → Exception day setting: 5 different types → Holiday setting	Energy saving: • Run/Stop • RC prohibition • Temperature shift (For Cool/Dry mode: +1.0°C~+9.0°C (+1.0°F~+18.0°F)) (For Heat mode: -1.0°C~-9.0°C (-1.0°F~-18.0°F)) • Mode shift (Mode shifted to Fan when in Cool/Dry mode, and shifted to Stop in Heat mode) • Capacity control on outdoor units • Lower noise control for outdoor units
Control function	On/Off Mode Set temperature Fan speed Louver RC prohibition Filter sign reset Function selection for indoor units (*1) Function selection for outdoor units (*2) Capacity control for outdoor units (*2) Lower noise control for outdoor units (*2)	Schedule function Setting items in schedule is as below: • On/Off • Operation mode • Setting temperature • Louver • Fan speed • RC operation prohibition • Capacity control for outdoor units • Lower noise control for outdoor units	External input / output Control/Monitor → Controlled items: • Run/Stop • Mode (Cool/Heat) → Monitored items: • Run/Stop • Mode (Cool/Heat) • Alarm state
Monitor function	On/Off Mode Set temperature Air intake temperature RC sensor temperature (*3) Air intake temperature of outdoor unit Fan Speed Louver RC prohibition Thermo-ON information Filter sign/Auto cleaning fault Alarm status/Alarm codes	History Alarm history: 10,000 records External In/Output history: 1,000 records Pulse input history: 6 months	Others: • Power consumption signal input • Emergency stop
	Management report visualization Up to 2 years worth of data history can be displayed for the following: • Accumulated operation time (min.) • Accumulated thermo-ON time (min.) • Average air intake temp temperature of indoor unit • Average air intake temperature of outdoor unit • Average setting temperature • Average RC sensor temperature		

(*1) Some indoor units may not fully support all functions.
(*2) Available for applicable outdoor units only.
(*3) Whether this is shown on the screen depends on the remote controller settings.

Remote access.

You can now operate Central Station EX from your laptop PC or touch panel PC. Install our software and you can connect from anywhere, using our VPN network.



CENTRAL STATION EZ FOR MEDIUM-SCALE BUILDINGS

(PSC-A64GT)



With easy control via an 8.5 inch color touch panel, its detailed control functionalities such as Weekly Scheduling, Operation hours tracking, and more, help you save energy.

Up to 64 remote-controlled groups and up to 160 indoor units can be connected to the Central Station EZ.

Capacity

RC group	64
Group	64
Block	4
Indoor Unit	160
Outdoor Unit	64
Building Scale	Small-Medium

Specifications

Rated Power Supply	1-, AC 100-240V, 50/60Hz
Electrical Power Consumption	30W (Max.)
Communication Unit	Units of Adopting for H-LINK
Communication Line	Non-polar 2-wire
Communication Speed	9,600bps
Wiring Length	1,000m (Total Length)
Display	8.5-inch Wide Color LCD (Full Dot)
Display Control	Touch Panel

Functions

Monitor Function	• Run/Stop/Abnormality • Setting Temperature • RC Operation Prohibited Setting • Accumulated Operating Time • Operation Mode • Setting Fan Speed • Setting Louver • Filter Sign • Alarm Code
Control Function	• Run/Stop* • Fan Speed • Operation Mode • Louver • Temperature Setting • RC Operation Prohibited • Filter Sign Reset

*The "All Groups Run/Stop" command signal exception function for selected groups is available via the "Exception of Run/Stop Operation" function.

CENTRAL STATION MINI FOR SMALL-SCALE BUILDINGS

(PSC-A32MN)



With easy control via an 5.0 inch color touch panel, its detailed control functionalities such as weekly scheduling, operation hours tracking, help you save energy. Up to 32 remote-controlled groups and up to 160 indoor units can be connected to the Central Station mini.

Capacity

RC group	32
Group	32
Block	4 Patterns (2/4/8/16)
Indoor Unit	160
Outdoor Unit	64
Building Scale	Small

Specifications

Rated Power Supply	1-, AC 100-240V, 50/60Hz
Electrical Power Consumption	20W (Max.)
Communication Unit	Units of Adopting for H-LINK
Communication Line	Non-polar 2-wire
Communication Speed	9,600bps
Wiring Length	1,000m (Total Length)
Display	5.0-inch Wide Color LCD (Full Dot)
Display Control	Touch Panel

Functions

Monitor Function	• Run/Stop/Abnormality • Setting Temperature • RC Operation Prohibited Setting • Accumulated Operating Time • Operation Mode • Setting Fan Speed • Setting Louver • Filter Sign • Alarm Code"
Control Function	• Run/Stop* • Fan Speed • Operation Mode • Louver • Temperature Setting • RC Operation Prohibited • Filter Reset Signal

*"All Groups Run/Stop" command signal exception function for selected groups is available by "Exception of Run/Stop Operation." function.

Individual controllers

A new generation of room controller now available!

With two new room controllers, the experience of controls has become easier and more stylish than ever

NEW ADVANCED-COLOR CONTROLLER (PC-ARFG1-*)



Contactless settings via airCloud Tap

Complete controls in a rich interface

- Colored screen displaying visual charts and descriptive texts
- Access to all existing Hitachi VRF indoor unit features including user features settings, installation & maintenance features settings.
- Energy consumption monitoring
- Ideal for indoor units with motion sensors, cassettes with elevating grilles
- Multiple languages available

*Except Sleep Mode timer

NEW ECO-COMPACT CONTROLLER (PC-ARC-*)



Contactless settings via airCloud Tap

Value without compromise

- Segment screen displaying pictograms
- Essential controls in a glimpse
- On/Off weekly schedule
- Some extra advanced features such as GentleCool, Power-Saving Peak-Cut mode and Sleep Mode Timer
- Embedded IR receiver, ideal for ducted units

Still available for order

WIRED REMOTE CONTROLLER (HCWA10NEGQ)



- 88mm square controller with LCD screen.
- Smaller body with multiple features.
- Best option for spaces frequented by recurring users, e.g. offices.

Controls from anywhere in the room

ADVANCED WIRELESS REMOTE CONTROLLER (PC-AWR)



- Wireless remote controller with more features.
- Several temperature units and settings available; 0.5°C/1.0°C/1.0°F.
- Ideal for controlling the unit from anywhere in the room, e.g. residential spaces.

WIRELESS REMOTE CONTROLLER (PC-LH7QE)



- Budget option featuring primary control settings.
- 1.0°C temperature step.
- Ideal for visitors to control the unit from anywhere in the room, e.g. hotel suite.

From basic to advanced controls



	No of RC-Group No of indoor units	NEW PC-ARFG1	NEW PC-ARC	HCWA10NEGQ	PC-AWR	PC-LH7QE
Connection Capacity		1	1	1	-	-
Product Size	Width*Height*Depth (mm)	120*120*16.5 (D: thinnest part)	90*90*15.5 (D: thinnest part)	88*88*15.5	140*55*16.8	140*52*19.3
Screen		Color LCD with backlight	Segment LCD with backlight	Segment LCD with backlight	Segment LCD	Segment LCD
Embedded IR receiver		-	●	-	-	-
Smartphone App	Use With airCloud Tap	● (support NFC)	● (support NFC)	-	-	-
Essential Operations	Run / Stop	●	●	●	●	●
	Operation Mode	●	●	●	●	●
	Auto Mode Setting	●	●	●	●	●
	Temperature Setting	●	●	●	●	●
	Fan Speed	●	●	●	●	●
	Louver Direction	●	●	●	●	●
	Simple Timer	●	● (On/Off Timer)	● (On/Off Timer)	● (On/Off Timer)	● (On/Off Timer)
	Weekly Operation Schedule	●	●	●	-	-
	Power Savings Setting	●	● (Capacity Control only)	-	-	-
	Night Quiet Operation	●	-	-	-	-
Advanced Feature Settings	Power Savings/Night Quiet Schedule	●	-	-	-	-
	Power Consumption Display	●	-	-	-	-
	AutoBoost	●	●	-	-	-
	Comfort Setting	●	● (GentleCool only)	-	-	-
	Sleep Mode	-	●	-	-	-
	Motion Sensor Setting (1)	●	-	-	-	-
	Setback Setting	●	-	-	-	-
	Elevating Grille	●	-	-	-	-
	Filter Reminder Time Reset	●	●	●	●	●
	Filter Auto-Cleaning (1)	●	-	-	-	-
Display Settings	Individual Louver Setting	●	●	●	-	-
	Louver Open/Close	●	-	-	-	-
	Ventilation	●	-	-	-	-
	Total Heat Exchanger SET	●	-	-	-	-
	Adjusting Date/Time	●	●	●	-	-
	Daylight Saving Time	●	-	-	-	-
	Run Indicator Brightness Adjustment	●	● (Only On/Off setting)	-	-	-
	Display Adjustment	●	-	-	-	-
	Temperature Units (°C/°F)	●	●	●	●	- (°C only)
	Temperature setting at 0.5°C step	●	●	●	●	- (1.0°C only)
Room Temperature Display	●	-	-	-	-	
Service Functions	Language available	EN, JPN, CN (traditional & simplified), FR, ES, PT	EN	EN	EN	EN
	Keypad Touch Sound	●	●	● (Cannot turn off)	-	-
	Lock Function	●	● (Lock function individually)	● (Lock whole keypad)	-	-
	Password Setting	●	-	-	-	-
	Hotel Mode	●	-	-	-	-
	Power Saving Details Setting	●	-	-	-	-
	Temperature Range Restriction	●	● (in Function Selection)	● (in Function Selection)	-	-
	Dual Setpoint	●	-	-	-	-
	Main/Sub Display	●	-	-	-	-
	Set Room Name	●	-	-	-	-
Installation Functions	Set Contact Information	●	-	-	-	-
	NFC Setting	●	●	-	-	-
	Simple Maintenance Check Menu	●	-	-	-	-
	Test Run	●	●	●	-	-
	Function Selection	●	●	●	-	-
	Thermistor Selection	●	● (in Function Selection)	● (in Function Selection)	-	-
	Input/Output	●	●	●	-	-
	Thermistor Calibration in Controller	●	● (in Function Selection)	-	-	-
	Fan Speed At Thermo-Off	●	● (in Function Selection)	● (in Function Selection)	-	-
	Indoor Unit Address Change	●	●	●	-	-
Check Menu	Address Check Operation	●	-	-	-	-
	Address Initialization	●	-	-	-	-
	Setting Initialization	●	●	-	-	-
	Main/Sub Controller Setting	●	●	●	-	-
	Priority Setting	●	-	-	-	-
	Cancel Preheating Control	●	-	-	-	-
	Elevating Grille Setting	●	-	-	-	-
	Power Up Setting	●	-	-	-	-
	Setback Trigger Unit	●	-	-	-	-
	Refrigerant Leak Sensor Setting	●	-	-	-	-
Other features	Check 1	●	●	●	-	-
	Check 2	●	●	●	-	-
	Alarm History Display	●	●	●	-	-
	Display Model Number	●	-	-	-	-
	Check PCB of the Units	●	-	-	-	-
	Self Check	●	●	-	-	-
	Synchronize Date/ time with Central Controller	● (Only available from Central Station EX PSC-A128EX3)	● (Only available from Central Station EX PSC-A128EX3)	-	-	-
	Stop operation delay	●	-	-	-	-
	Emergency operation	●	●	-	-	-
	Two WRC Control	●	●	-	-	-
Alarm Display	●	●	●	-	-	
Filter cleaning reminder sign display	●	●	●	-	-	

(*1) Available when the controller is connected with selected indoor unit offering this feature.

AIRCLOUD TAP

Download
airCloud Tap!



For HVAC professionals:
Quicker commissioning & service by airCloud Tap
Contactless 'read and write' settings

Ready-to-tap controllers

- NFC chip embedded in the controller

Convenience using with a mobile app

- Easy browsing of all settings by scrolling phone's screen
- Complete text description of each setting


More savvy than traditional settings by physical device

- Less buttons to press, no AC hardware to manipulate
- Time saving setting process
- Reduced need of documentation support




What you can do with airCloud Tap | some highlights:

Installation & Commissioning



Date/time setting


Import the date & time from your phone into the controller



Function selection

Scroll your phone's screen and browse over 140 commissioning settings available


Operation



Scheduling


Save preferred AC schedule and save to copy to other controllers of the same building

Maintenance & Service



Troubleshooting

Visualize all the service check data on your phone



Temperature range restrictions


Apply min/max set temperature to prevent excessive cooling/heating

Special tip: Save time on multi-room commissioning

Specify settings for one room, save them, then apply these settings to other similar rooms in one tap. Particularly useful for multiple zones with similar needs! Hotel guestrooms, office meeting rooms, condominium units, etc.


STEP1

Read the settings from one device and save settings.



STEP2

Hold the mobile device over each product and write settings of STEP1.



How does airCloud Tap works?



1. Activate the NFC function on the AC equipment.

2. Open the airCloud Tap app and tap the AC equipment with your phone to read the current settings.

3. Edit the desired settings on your phone.

4. Tap again your equipment to apply the new settings.

Individual controllers

NEW ADVANCED COLOR WIRED REMOTE CONTROLLER (PC-ARFG1)

Simplicity with style

Combining the best of form and function, enjoy climate control made easy with Hitachi's most advanced wall controller yet.



- Super user-friendly interface
- Easy-to-navigate menus
- Available in 7 languages
- Pictograms and colors for an optimal user experience

Award-winning design

- Minimalist design aesthetic
- Distinctive curves for ergonomics
- Modern and subtle colors

With **Near-field communication (NFC) contactless-enabled system** commissioning via the airCloud Tap smartphone app, you can now save, copy, and paste settings to the Advanced Color Controller with a simple tap.



- 1 Room name
- 2 Set temperature
- 3 Operation mode
- 4 Indoor unit ON/OFF light
- 5 Indoor unit ON/OFF
- 6 Navigation buttons
- 7 Back button
- 8 OK button
- 9 Fan speed
- 10 Louver direction
- 11 Access to menu
- 12 Filter cleaning reminder

Outer dimensions (H×W×D)

- 120×120×16.5mm (thinnest part)
- 120×120×21.5mm (thickest part)


Capacity

Power Supply	Powered by indoor unit, 15VDC±10% 180g (approx.)
Installation	Indoor, on the wall or switch box
Connection capacity	Up to 16 indoor units (with the same wired remote controller)
▲ Display	When two wired Advanced Controller units are connected to the same indoor unit, the maximum brightness of each controller will be halved


* H is the height of the unit from the front, without the protrusion at the bottom.

System configuration example

Possibility of 2 Wired Controller Connection



Up to 16 IDU connection




Simultaneous control for up to 16 IDU with transition wiring


— H-LINK
— Remote Control Cable

Energy optimization


Power-saving features enable VRF system operators to optimize energy usage




Energy consumption visualization



Capacity - peak cut control



Choice of power-saving method




Power saving setting


Set specific schedules for features like peak capacity cuts and the thermal operation rotation of indoor units, enabling you to match energy-saving operation hours with your utility tariffs plan. Building managers can also set the minimum and maximum temperature range for occupants and visualize energy consumption with daily, weekly or monthly comparison options.

From basic to advanced functions


Users can control the main temperature settings from Advanced-Color controller's main screen. In addition, more advanced comfort settings help customizing the air to their occupants' specific needs.



GentleCool limits the temperature of conditioned air, preventing cold drafts for optimal comfort.




AutoBoost automatically activates for 30 minutes every time the AC is turned on, helping the room reach the desired temperature faster.




AC Scheduling is easier than ever, thanks to flexible features such as the holiday calendar.


The latest VRF features



NEW Fan speed at thermo-off reduces air circulation when cooling or heating is not effective.



Individual **4-way cassette louvers** optimizes air flow direction to each corner layout.



Schedule **Night Quiet** mode to minimize the outdoor unit's operation noise so you and your neighbors get a better night's sleep.

Special features for hotels

NEW **Hotel mode** enables instant access to the functions demanded most by hotel guests. After guests check out, housekeeping can reset the controller in one touch. **Hotel setback** allows interlocking with hotel key cards. When the room is vacant, the indoor unit switches to a selected energy-saving setback temperature, ensuring the room remains at a comfortable temperature when unoccupied.



Ideal for indoor units with motion sensor features

NEW Active intelligent comfort features connected to your indoor unit's motion sensor and/or radiant sensor*: choice of direct/indirect air flow, **FeetWarm NEW**, **FloorSense Cool NEW** and the exclusive **Crowd-Sense NEW** to prevent heat peak from rapid crowd arrival.

Individual controllers

NEW ECO-COMPACT CONTROLLER (PC-ARC-*)

Climate control in a compact size


- Great value for money that combines the best of form and function.
- Minimalist design aesthetic that reflects Hitachi's Duality Design philosophy.



- Budget-sensitive VRF projects
- Users who prefer simple controls
- Functional spaces

Stylish & Intuitive

With distinctive curves and an aesthetic inspired by Hitachi's Duality Design philosophy, the Eco-Compact Controller is stylish, ergonomic, cost-effective, and convenient. Enjoy climate control made easy through an optimized interface with easy-to-understand pictograms for a truly intuitive user experience.



With Near-field communication (NFC) contactless-enabled system commissioning via the airCloud Tap smartphone app, you can now save, copy, and paste settings to the Eco-Compact Controller with a simple tap.



- 1 Set Temperature
- 2 Operation mode
- 3 Run indicator
- 4 On/Off button
- 5 Operation mode button
- 6 Fan speed button
- 7 Menu buttons
- 8 Directional key
- 9 Fan speed
- 10 Louver direction
- 11 Current time

Outer dimensions (H×W×D)


90mm×90mm×15.5mm(thinnest part)
90mm×90mm×18.5mm(thickest part)

Capacity


Power Supply	Powered by indoor unit, 15VDC±10%
	100g (approx.)
Installation	Indoor, on the wall or switch box
Connection capacity	Up to 16 indoor units (with the same wired remote controller)

System configuration example

Possibility of 2 Wired Controller Connection




Up to 16 IDU connection




— H-LINK
— Remote Control Cable

Easy access to essential controls

Simplified navigation enables users to change temperatures and adjust essential controls directly from the home screen in one touch.




Operation modes



Fan speed



Louvers' positions



Set temperature with 0.5°C precision*

Energy-saving features

The Eco-Compact Controller includes energy-saving features to minimize unnecessary AC operation.



The **Peak-Cut** feature enables users to save even more energy during peak consumption periods.



Weekly scheduling automatically turns the indoor unit on/off at set times, great for classrooms, retail businesses or other premises with regular opening hours.

Accrued comfort

The Eco-Compact Controller includes energy-saving features to minimize unnecessary AC operation.




Include **GentleCool**, which controls the discharged air temperature for a smooth cooling down and prevents cold drafts.



AutoBoost activates for 30 minutes every time the AC is turned on, helping the room reach the desired temperature faster with a powerful automatic mode, which is ideal for meeting rooms and other areas requiring fast temperature reach.

Supports easy maintenance

A filter symbol appears when it's time to clean the filter. In the event of an error, the error code and the related indoor unit number is clearly displayed for ease of maintenance.



- 1 Alarm Icon
- 2 Indoor Unit No. (Refrigerant system)
- 3 Indoor Unit No. (Refrigerant system)
- 4 Alarm Code

Special features




For residential users: set the Sleep mode timer **NEW** to gradually change the room temperature for a better night's sleep. The unit will turn off automatically after a set time.



For hotels: interlock the Eco-Compact Controller with your hotel key card receiver and activate setback temperature while guest is away.

Embedded IR receiver

For use with the Wireless Remote Controller. Ideal for indoor units without embedded IR receiver (ex: ducted units)



When IR receiver receives the commands, the buzzer sounds.
*Compatible HCRB10NEWQ and PC-LH7QE/PC-LH7QE1 wireless controllers

Individual controllers

WIRED REMOTE CONTROLLER (HCWA10NEGQ)

Temperature display
Room temperature
RT 26.0°C RT 79.0°F

Set temperature
SET 26.0°C SET 79.0°F

ON/OFF button
Mode button

Liquid Crystal Display (LCD) screen

Up button & down button

Operation mode

- Cooling mode
- Heating mode
- Dry mode
- Fan mode
- Auto mode

Fan speed setting

Timer/Clock setting

Fan speed (flickering)

Timer setting

- ON Timer ON
- OFF Timer OFF
- ONCE Timer valid for one time
- DAILY Timer valid for one day
- WEEKLY Timer set for a week

Outer dimensions (H×W×D)
(mm) 88.0×88.0×15.5

Functions

Run/Stop
Operation Mode
Auto Mode Setting
Temperature Setting
Temperature Setting Rate 0.5°C/1.0°C/1.0°F
Fan Speed 3/4/6 taps
Louver Direction
Sensor Condition Check
Sensor Data Check
Alarm History Display
Test Run
Function Selection (Optional Function Setting)
Thermistor Selection
Thermistor Calibration
Input / Output Setting
Indoor Unit Address Change
key pad lock
Management
Lower Limit for Cooling Operation
Upper Limit for Heating Operation
Schedule
Date/time setting

Notes:
1. Fan speed taps setting unit availability varies with the indoor unit. Please check each technical catalog in advance.
2. Initial setting of temperature display is "Set temperature" display only. Please contact your dealer to display room temperature.

ADVANCED WIRELESS REMOTE CONTROLLER (PC-AWR)

Transmitter

Transmitting indication
LCD (Liquid Crystal Display)

Mode selection switch
Reset switch

Fan speed switch
On switch
Off switch

Louver angle switch
Temp. switch
Filter reset switch

Timer switches

Outer dimensions (H×W×D) (mm) 140.0×55.0×16.8

Functions

Run/Stop
Operation Mode
Auto Mode Setting
Temperature Setting
Temperature Setting Rate 0.5°C/1.0°C/1.0°F
Fan Speed 3/4/6 Taps
Louver Direction
Service
Filter Sign Reset
Side-by-side indoor unit identification
Temperature Unit °C/°F
Schedule
Built-in Timer (On/Off)

WIRELESS REMOTE CONTROLLER (PC-LH7QE)

Transmitter

Transmitting indication
LCD (Liquid Crystal Display)

Run/Stop switch

Temp. switch

Louver angle switch

Timer switches

Reset switch

Outer dimensions (H×W×D) (mm) 140.0×52.0×19.3

Functions

Run/Stop
Operation Mode
Auto Mode Setting
Temperature Setting
Temperature Setting Rate 1.0°C
Fan Speed 3/4/6 Taps
Louver Direction
Service
Side-by-side indoor unit identification
Temperature Unit °C
Schedule
Built-in Timer (On/Off)



RECEIVER KIT FOR WIRELESS REMOTE CONTROLLER

	PC-RLH11 (Basic)				PC-ALHZ1 (Advanced)				
Model									
Indoor unit	Ducted High ESP (AC Motor) RPIH-HNAUN1Q RPI-FSNQ	Ducted High ESP (DC Motor) RPIH-HNDUSQ	Ducted Medium ESP (AC Motor) RPIM-HNAUN1Q RPI-FSN3Q	Ducted Low ESP (AC Motor) RPIL-HNAUN1Q	Ducted Compact AC Motor DC Motor		Wall-Mounted (DC Motor) RPK-HNBUSQ	Floor / Ceiling Convertible (AC Motor) RPFC-FSNQ	Floor Concealed (AC Motor) RPFI-FSNQ
Advanced Wireless Remote Controller PC-AWR	○	○	○	○	○	○	○	○	○
Standard Wireless Remote Controller PC-LH7QE	○	○	○	○	○	○	○	○	○
Model	HR4A10NEWQ (Basic) 	PC-ALH3 (Advanced) 	PC-ALHC1 (Advanced) 	P-AP56NAMR (Advanced) 	PC-ALHD1 (Advanced) 	PC-ALHS1 (Advanced) 	PC-ALHP1 (Advanced) 	PC-ALHZ1 (Advanced) 	
Indoor unit	4-way Cassette (DC Motor) RCI-FSKDN1Q	4-way Cassette (DC Motor) RCI-FSRP	4-way compact Cassette (AC Motor) RCIM-FSRE	4-way compact Cassette (AC Motor) RCIM-FSRE	2-way Cassette (DC Motor) RCD-FSR	1-way Cassette (DC Motor) RCS-FSR	Ceiling Suspended (DC Motor) RPC-FSR	Wall-Mounted (DC Motor) RPK-FSRM	
Advanced Wireless Remote Controller PC-AWR	○	○	○	○	○	○	○	○	
Standard Wireless Remote Controller PC-LH7QE	○	-	-	-	-	-	-	-	

(*) Basic function receiver kit is installed as a standard part in this wall-mounted unit. Wireless remote controller (PC-LH7QE) is delivered as a standard accessory as well. If separate placement of receiver kit is required, please use optional basic receiver kit [PC-RLH11] or optional advanced receiver kit [PC-ALHZ1].

Notes:
When using a basic receiver kit PC-RLH11 or HR4A10NEWQ together with wireless remote controller PC-LH7QE:
1) It won't be possible to lock individual remote controllers from Hitachi Central Stations (mini/EZ/EX)
2) It won't be possible to apply min/max restrictions on set temperature from Hitachi Central Stations (mini/EZ/EX)

Basic
Limited function available for centralized controllers
Temperature setting rate [1.0°C] only

Advanced
Full function available for centralized controllers
Temperature setting rate [0.5°C/1.0°C/1.0°F]

Accessories



3P CONNECTOR CABLE PCC-1A



FOR CONNECTION TO REMOTE ON/OFF DEVICE/RECEIPT OF OUTPUT SIGNAL

Operation example

- **Cooling operation:**
Compressor is ON by closing terminals 2 and 3 of CN3.
Compressor is OFF by opening terminals 2 and 3 of CN3.
- **Heating operation:**
Compressor is ON by closing terminals 1 and 2 of CN3.
Compressor is OFF by opening terminals 1 and 2 of CN3.

*One set contains five 3P connector cables.
*PCC-1A can connect to external signal input-output terminal both in outdoor unit and indoor unit.

System configuration example




REMOTE SENSOR THM-R2A

ROOM TEMPERATURE SENSOR

Outer dimensions (H×W×D)
(mm) 50.0×50.0×15.0

Length m 8.00

System configuration example




REMOTE CONTROL CABLE PRC-5K, 10K, 15K

FOR PC-ARFG1 CONNECTION (TO IDU)

	PRC-5K	PRC-10K	PRC-15K
Length m	5.00	10.00	15.00

System configuration example



BMS ADAPTER for BACnet® HC-A64BNP1

CONTROL UP TO 64 INDOOR UNITS


Specifications

Outer dimensions (H×W×D)
(mm) 68.0×240.0×154.0

Functions

Corresponding BACnet® Standard	ANSI/ASHRAE Standard 135-2004 BACnet®
Control Item at Upper System	<ul style="list-style-type: none"> • Run Stop (Setting) • Operation Mode (Setting) • Fan Speed Level (Setting) • Indoor Temperature (Setting) • RC Operation lock (Setting) • Filter Sign Reset
Monitoring Item at Upper System	<ul style="list-style-type: none"> • Run Stop (State) • Operation Mode (State) • Fan Speed Level (State) • Indoor Temperature (State) • Prohibiting RC Operation (State) • Filter Signal • Indoor Air Intake Temperature • Alarm Signal • Alarm Code • Communication State

System configuration example



H-LINK: enjoy more freedom

WHAT IS H-LINK?

H-LINK is Hitachi Cooling & Heating original communication system to control multiple VRF refrigerant systems from one centralized control point.

H-LINK simplifies commissioning and service maintenance for installers and service engineers. For building owners and occupants, it provides outstanding versatility enabling the connection of various types of central control options, enabling better system management. Our proprietary high-performance communication system enables the connection of control wiring between indoor and outdoor units, and between a centralized control system and indoor/outdoor units across two or more refrigerant systems.

Examples



Educational institutions such as primary schools where installation work cannot be performed on weekdays.



Hotels where it is preferable to complete installation work during late evenings.



Rehabilitation facilities or hospitals where it is necessary to minimize the burden on users.

3x

more benefits!

1

Flexible wiring routes:

no restrictions & time-saving at installation.

2


Can connect with various types of Hitachi air conditioning products, including VRF and mini splits, for centralized controls.

3

No adapter is needed!

Simple connection to terminal blocks.

Definition of terms in Hitachi centralized control systems




- ① CS-NET/Central station
→ Hitachi original centralized controller.
- ② RC Group (Remote Controller System Group)
→ Stands for a number of indoor units (up to 16 units) connected using "same remote controller" wiring. In this group, connected indoor units are all controlled in the same way.
- ③ Group
→ Stands for the multiple "RC groups" that are registered in the centralized controller network setting.
- ④ Block
→ Stands for the multiple "groups" that are registered in the centralized controller network setting.

CENTRALIZED CONTROLS: FLEXIBLE WIRING ROUTE!

- (1) • Multiple refrigerant systems located in one area.
- Central monitoring room in separate area.

H-LINK SOLUTION


- Wire the central station to the closest indoor unit.
- Wiring distance is reduced substantially.



- (2) • Refrigeration systems in different places.
- Some indoor units of each respective system are close to one another.

H-LINK SOLUTION


- Where two indoor units of each respective system are close together: you can connect two refrigerant systems via the indoor units.
- Wiring distance is reduced substantially.



- (3) • One refrigerant system far away from the remaining ones.

H-LINK SOLUTION


- Connect the farthest refrigerant system directly to central station either to outdoor units or indoor units.
- The central station can make the central link between the different refrigerant systems.



- (4) • Each refrigerant system in separate areas.
- Indoor units are closer from one group to another.

H-LINK SOLUTION

- Centralized control can be achieved by connecting the refrigerant systems via the closer indoor units.
- Wiring can be indoors only.



// H-LINK solution
 // H-LINK
 // Remote control cable